

AS. 122.670

SUPERINTENDENCIA DE INDUSTRIA Y COMERCIO



No. 12-187288-00003-0000

Fecha: 2013-02-15 16:27:28 Dep. 2020 DIR.NUEVASCR
Tra. 2 PATENTES Eve: 1 REGDEPOSITO
Act. 444 RESPUESTAREQUE Folios: 93

Señores

DIRECCIÓN DE NUEVAS CREACIONES

SUPERINTENDENCIA DE INDUSTRIA Y COMERCIO

E. S. / D.

REF: Expediente No. 12 187.288 - Solicitud de Patente
a favor de **INTEVEP, S.A.**

Titulada: FLUIDO DE TRABAJO/CONTROL PARA POZOS DE CRUDO PESADO Y
EXTRA PESADO

JUAN PABLO CADENA SARMIENTO, vecino de Bogotá, portador de la tarjeta profesional No. 57492, obrando como apoderado de la sociedad **INTEVEP, S.A.**, según lo acredita el documento de poder presentado en esa Dirección, me permito anexar al presente escrito el siguiente documento:

1. Copias certificadas por la Oficina de Patentes de Estados Unidos de las primeras solicitudes presentadas para la misma invención de las cuales REIVINDICAMOS PRIORIDAD, junto con sus correspondientes traducciones al español.

Del señor Director atentamente,

JUAN PABLO CADENA SARMIENTO


C.C. No. 80.410.337 de Usaquén

T.P. No. 57492 del C.S.J.

Calle 70A No. 4-41

Bogotá, 12 de enero de 2013
JPCjpg
Folios: 93

PA 7395887



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

January 10, 2013

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 61/549,534

FILING DATE: October 20, 2011

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS CONVENTION, IS US61/549,534

**By Authority of the
Under Secretary of Commerce for Intellectual Property
and Director of the United States Patent and Trademark Office**



**M. TARVER
Certifying Officer**

Electronic Acknowledgement Receipt	
EFS ID:	11232439
Application Number:	61549534
International Application Number:	
Confirmation Number:	7825
Title of Invention:	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS
First Named Inventor/Applicant Name:	Pablo Manrique
Customer Number:	34704
Filer:	George A. Coury/Eva Kendrick
Filer Authorized By:	George A. Coury
Attorney Docket Number:	11-194
Receipt Date:	20-OCT-2011
Filing Date:	
Time Stamp:	16:57:29
Application Type:	Provisional

Payment information:

Submitted with Payment	yes
Payment Type	Deposit Account
Payment was successfully received in RAM	\$ 250
RAM confirmation Number	3499
Deposit Account	020184
Authorized User	
The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows: Charge any Additional Fees required under 37 C.F.R. Section 1.16 (National application filing, search, and examination fees) Charge any Additional Fees required under 37 C.F.R. Section 1.17 (Patent application and reexamination processing fees)	

Charge any Additional Fees required under 37 C.F.R. Section 1.19 (Document supply fees)					
Charge any Additional Fees required under 37 C.F.R. Section 1.20 (Post Issuance fees)					
Charge any Additional Fees required under 37 C.F.R. Section 1.21 (Miscellaneous fees and charges)					
File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Application Data Sheet	11-194_Application_Data_Sheet_10-20-11.pdf	1390765	no	5
			9b1fe82c983b21a78cc3a45c608081cb88ff37e2		
Warnings:					
Information:					
2		11-194_Application_10-20-11.pdf	111384	yes	21
			b7c3d74bdcdd58a3fc73402524fdccd5ab6dbf5		
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	17	
	Claims		18	20	
	Abstract		21	21	
Warnings:					
Information:					
3	Drawings-only black and white line drawings	11-195_Drawings_10-20-11.pdf	807999	no	5
			a2f43b0de44f2f0b8b9f3d7bf81649e06dabb06a4		
Warnings:					
Information:					
4	Fee Worksheet (SB06)	fee-info.pdf	29932	no	2
			098fb73be27491cd05d9aba6522a7b2fbb33f542		
Warnings:					
Information:					
Total Files Size (in bytes):			2340080		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS**BACKGROUND OF THE INVENTION**

[0001] The invention relates to a formulation and method of using same for improving well productivity in hydrocarbon reservoirs.

[0002] Improvement in productivity of heavy and extra heavy oil wells such as those found in the Orinoco River Belt in Venezuela is clearly desirable. Some of the largest reservoirs of heavy and extra heavy oil in the world are in Venezuela and hold oil having API gravity within the range of 6 to 16. Unfortunately, the production rate of much of this oil is unacceptable.

[0003] It is a high concern in the exploitation of heavy and extra heavy oil reservoirs to increase productivity during the well lifetime. With these wells, primary cold production schemes are quickly abandoned in favor of thermal methods to improve well flowability by reducing oil viscosity in the reservoir. These processes are costly and also still produce a low output in terms of final recovery. They also have serious problems of sour gases production such as H₂S and CO₂ which are very costly to address. Such thermal recovery methods typically produce final oil recovery below 35 - 40%.

[0004] Venezuelan heavy and extra heavy Orinoco River Belt oil sandstones are exceptional reservoirs. 60% of the reservoirs of this type have a KH/U value between 40 and close to 1,000 in very many cases. Unlike other reservoirs, however, the oil in Venezuelan extra heavy oil reservoirs is flowable at reservoir conditions.

[0005] Even these wells, however, have a final recovery by cold production which is very low and perhaps in most cases below three (3) per cent of the original oil in place. The

11-194

conditions for flow of oil in those reservoirs, with even excellent petrophysical properties, are very unfavorable to the flow of oil. The components of the heavy and extra heavy oil, particularly the asphaltenes in natural form in the native oil, are capable by natural fluid-rock interactions of generating an oil-wet condition at the surface of the natural mineral components of the sandstone. This produces the most adverse conditions to flow of oil in a porous media. This is a natural oil-wet condition of the reservoir media, which is a completely different condition as compared to formation damage in the well resulting from drilling or production activities, which could also happen in the well.

[0006] The need exists for improvement in production rates from wells producing from formations containing heavy and extra heavy wells, particularly those which contain asphaltenes and other hydrocarbons which lead to oil wet flow environments.

SUMMARY OF THE INVENTION

[0007] As a response to the above problems, especially to the natural oil wet conditions of the sandstone and the extremely low well productivity and recovery of the original oil in place, the present invention provides a formulation or stimulation fluid and a method of using the formulation for improving well productivity in cold production schemes and also in producing wells using thermal methods. The result is reflected by a better flow rate in the well, a lower pressure drawdown, and an improved recovery from the drainage area of the formation.

[0008] In accordance with the invention, a method is therefore provided for altering flow conditions in a porous media containing hydrocarbons, which method comprises the steps of preparing a mixture of a surfactant, a co-surfactant and a carrier fluid; transporting the mixture to the porous media; and holding the mixture in the porous media in the presence of water

11-194

for a period of time sufficient to form a water film on the surfaces of the porous media.

[0009] It should be appreciated that the holding step involves holding the mixture in the well under substantially static flow conditions to allow the water film to form as desired. Thus, according to the invention, the treatment is advantageously carried out during other servicing of the well when production or drilling would be stopped anyway, thereby taking advantage of the down-time of the well and gaining a flow advantage in the well while the flow is being serviced.

[0010] In further accordance with the invention, therefore, a method, is provided for improving flow conditions in a porous media while servicing a well penetrating to the porous media, comprising the steps of: stopping drilling or production activities on the well; introducing a well control fluid into the well, the well control fluid comprising a mixture of a surfactant, a co-surfactant and a carrier fluid and holding the well control fluid in the well and the porous media in the presence of water while the well is being serviced, such that the fluid penetrates the porous media and forms a water film on surfaces of the porous media; and when well servicing is finished, resuming drilling or production activities on the well.

[0011] The result of the treatment of the present invention is a novel treated surface which enhances flow of hydrocarbons through pores defined by the treated surface, and this comprises a porous media having pore surfaces and containing heavy hydrocarbon including asphaltene, wherein the asphaltene is adhered to the pore surfaces, and wherein a water film is adhered to the pore surfaces and asphaltene.

11-194

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] A detailed description of preferred embodiments of the present invention follows, with reference to the accompanying drawings, wherein:

[0013] Figure 1 schematically illustrates a treated surface in accordance with the invention;

[0014] Figure 2 illustrates typical and preferred flow rates from the hydrocarbon producing well;

[0015] Figures 3 and 4 illustrate a test glass plate which is oil-wet in Figure 3, and which has been treated in accordance with the present invention in Figure 4;

[0016] Figure 5 shows the test plate is still oil-wet even after solvent cleaning;

[0017] Figure 6 illustrates results of use of the present invention in the form of pressure drop in a porous media before and after several treatments in accordance with the present invention;

[0018] Figure 7 further illustrates pressure drop in a test system following initial and subsequent treatments in accordance with the present invention; and Figures 8-10 illustrate the method of present invention being carried out while a well is being serviced; and

[0019] Figures 8-10 illustrate the method of the present invention being carried out while a well is being serviced.

DETAILED DESCRIPTION

[0020] The invention relates to a formulation or stimulation fluid which has a surfactant/co-surfactant mixture and a method for using same to treat surfaces of a hydrocarbon bearing formation and thereby enhance flow of hydrocarbons through same. This method is advantageously used to alter flow conditions in the formation to improve production of hydrocarbons from hydrocarbon-bearing formations. This can be done at any

11-194

suitable time, but one particularly useful time to treat the well and formation is when a well is shut down for servicing.

[0021] As mentioned above, many significant hydrocarbon deposits in the world contain very large quantities of hydrocarbons under conditions where it is very difficult to produce them. One example of this is asphaltene-bearing hydrocarbon deposits in the Orinoco River Belt of Venezuela. In these formations, which typically have high and low pressures in the range of 300-1,500 psi, the heavy hydrocarbon fractions contained in the formation, especially asphaltenes, tend to adhere to the pore surfaces of the hydrocarbon and thereby create an oil-wet environment in the reservoir. As detailed above, this oil-wet flow environment is not at all conducive to production of those hydrocarbons from the formation. Further, as will be demonstrated below, this asphaltene is not easily removed because a portion of the hydrocarbon adsorbs into the rock surface making even cleaned surfaces oil wet and, therefore, unfavorable for good hydrocarbon flow. According to the invention, a water film is formed over the rock surfaces and also over the chemically adsorbed hydrocarbon so that the surfaces when coated in this manner are water wet. This greatly increases the flowability of hydrocarbons through the treated rock formation.

[0022] In accordance with the present invention, the surfactant/co-surfactant mixture is used to form a water film over the pore spaces of the formation, and also over the asphaltenes adhered to the pore surfaces, so as to provide a water-wet surface between the flow surfaces defined by the pore surface of the rock and asphaltene adhered thereto, and the volume of hydrocarbon in the formation which is intended to be produced. This water film increases flow of hydrocarbons through the formation, and thereby enhances production of hydrocarbon from the formation. Over a period of time, the

11-194

water film eventually is removed by fluids flowing past the film, at which point the surfactant/co-surfactant mixture of the present invention can again be introduced into the hydrocarbon bearing formation to again deposit a fresh water film for use in the next period of production.

[0023] According to the invention, the surfactant/co-surfactant mixture preferably contains surfactant, co-surfactant and a fluid carrier, each of which has the following preferred constituents.

[0024] The surfactant is preferably selected from the group consisting of cationic surfactants, non-ionic surfactants, amphoteric surfactants and combinations thereof. The surfactant is further preferably an ethoxylated fatty alcohol having between 4 and 60 ethoxylated groups.

[0025] Suitable non-ionic surfactants include but are not limited to octilphenol having 9-16 EO, nonylphenol with an EO number from 4 to 25, preferably 9 - 18, fatty acids of 9-20 EO, n-tetradecanol of 9-20 EO, n-hexadecanol of 9-20 EO, laurate of sorbitan, and polyethoxilated fatty alcohols with EO number from 4 to 25, preferably 9 - 20. Suitable ionic surfactants include but are not limited to n-alkyl sulfates of K or Na, n-alkyl trimethyl ammonium chloride and combinations thereof.

[0026] The co-surfactant is preferably an alcohol co-surfactant, preferably one or more n-alcohols (C1-C6), and more preferably selected from the group consisting of methanol, ethanol, propanol, butanol, pentanol, isopropanol and combinations thereof. The most preferred co-surfactant is methanol and/or ethanol.

[0027] The carrier fluid can be selected from the group consisting of organic solvents, light hydrocarbons, diluents, light crude oil and combinations thereof and water. More specifically, the carrier fluid can be light oil, a light refinery cut, gasoil, diesel, diluent and water. The most

11-194

preferred carrier fluid is an oil fluid. One example is compatible light crude oils with API gravity between 20 and 45 API preferably between 20 and 25 API. Also, some mixtures of compatible crude oil with the formation fluids and/or naphtha can be used for reducing viscosity of the heavy and extraheavy oil fluid flow for transportation in surface facilities.

[0028] The surfactant/co-surfactant mixture preferably is prepared having substantially equal amounts by volume of the surfactant and co-surfactant, and the overall mixture with carrier fluid preferably contains each of the surfactant and co-surfactant in an amount between 0.5 and 20% by volume, more preferably between 1 and 4% by volume.

[0029] In accordance with the invention, the surfactant/co-surfactant mixture can be prepared by mixing the above-identified constituents at the surface and then transporting, for example by pumping, the resulting mixture or stimulation fluid into a hydrocarbon producing formation, for example through a well positioned from the surface to the subterranean formation, so that the mixture penetrates into the hydrocarbon-bearing formation around the well, typically into a radius surrounding the well of at least about 2 inches, preferably between 12 inches and as large as possible, for example up to 3 feet. The penetration area into the formation is the area to be treated in accordance with the present invention.

[0030] Once a sufficient volume of fluid is pumped into the formation, this volume is then held in place in the formation in the presence of water for a time sufficient to form the desired water film over surfaces of the pore spaces of the hydrocarbon and also over the hydrocarbons adhered to these surfaces. This advantageously provides a water-wet flow environment which is advantageous to the flow of hydrocarbon through the porous media, and therefore produces a flow environment which is far more conducive to the flow of oil than the natural oil-wet flow

11-194

environment present in the well under natural formation conditions wherein the heavy hydrocarbons, and especially asphaltenes, are adhered to the pore surfaces of the porous media. The suitable amount of time to hold the fluid in the formation will vary with different wells, fluids and conditions, but will typically be between 12 and 24 hours and a preferred range of time between 18 and 24 hours.

[0031] Production from the treated well can be conducted while monitoring pressure drawdown in the well, and when the pressure drops sufficiently, the formation can be treated again in accordance with the present invention.

[0032] The typical formation for which the present invention can be utilized can be any formation wherein the forming of a water film over the pore surfaces would be beneficial to the overall hydrocarbon production from the formation. A particularly desirable application of the present invention is in formations having hydrocarbons with an API gravity of between 6 and 16, and even more preferably in formations containing hydrocarbons having an API gravity of between 6 and 12. These heavy and extra heavy hydrocarbon deposits in certain areas typically are very large in volume, but also contain asphaltenes as discussed above, and these are ideal candidates for treatment according to the present invention to enhance production. The typical rock formations containing such hydrocarbons have pore spaces which define the void volume which holds the hydrocarbons and which creates the permeability that allows the hydrocarbons to flow. The rock defining the pore surfaces of these formations are typically defined by quartz, feldspar, siliceous mineral, carbonaceous mineral, clays and combinations thereof.

[0033] Figure 1 schematically illustrates a surface of a hydrocarbon bearing formation treated in accordance with the present invention. As seen in Figure 1, a mineral surface **10**

11-194

which defines the pore space of the formation has rock mineral active sites **12** along surface **10**, and these rock mineral active sites **12** interact with hydrocarbons under the typical pressure in the formation such that chemically adsorbed hydrocarbons **14** are closely adhered to surface **10**, particularly at rock mineral active sites **12**.

[0034] According to the invention, the surfactant/co-surfactant mixture of the present invention is introduced to the formation and held there in the presence of water so that a film of water is formed over the adsorbed hydrocarbons **14** as well as the rock mineral active sites **12** of mineral surface **10**. Figure 1 shows surfactant/co-surfactant mixture adsorbed in the form of water film **16** which is schematically illustrated as a double layer to represent the surfactant/co-surfactant mixture. This produces a water-wet condition at the surface, which enhances flow of hydrocarbon through flow areas and pore space defined by such a treated surface. The water which forms the film can be water already present in the rock formation fluids and/or from the carrier fluid if a water containing carrier fluid is used. The water salinity can be in the range between 800 ppm up to 45,000 ppm.

[0035] Pressure drawdown, or the pressure drop from the formation to the well bore, is a good measure of the flowability in the formation. When the pressure drawdown is relatively small, this indicates good flowing properties in the formation to the well. While producing from a well that has been treated according to the invention, it is desirable to monitor the pressure drawdown, and after a certain amount of oil has been produced from a treated well, the pressure drawdown starts to increase. This increase in pressure drawdown indicates that the water film has been worn away or removed due to relatively high velocity flow of well fluids passing over the film to the well. This stream removes the water film by desorption of the

11-194

surfactant and co-surfactant from the mineral surface and restoring the natural oil-wet initial condition at the mineral surface. At this stage, according to the invention, the well can be treated again with the same formulation, and this process can be repeated as many times as necessary until no more hydrocarbon fluids flow to the well even after treatment. With cyclic stimulation, the porous media will improve final recovery of the initial oil in place in the drainage area by cold production by potentially many times the amount of 3% typically reported as the well output obtained without stimulation. The present invention also reduces the time and need of costly thermal processes to reach this level of oil recovery.

[0036] Figure 2 illustrates typical and desired flow rates from a hydrocarbon production well. The starts and stops shown in actual flow show a trend (line A) which is not desirable, while a preferred pressure behavior is shown at line B. The difference of the area between lines A and line B is an indication of greater recovery of oil from same well in same well drained area.

[0037] Turning to Figures 8-10, a well **22** is shown extending from surface **24** to a subterranean formation **26**. Well **22** communicates with formation **26** through perforations **28**. From time to time, such a well must be taken out of production, for example for servicing of various surface equipment, static pressure testing and the like. When such a procedure is to be conducted, it is typical to leave a column of fluid in the well to balance pressure of the formation. According to this aspect of the invention, the above-described mixture of surfactant and co-surfactant is used to simultaneously balance formation pressure and treat surface wettability of the porous media in the formation as well. Thus, Figure 8 shows mixture **30** being introduced to well **22**, and Figure 9 shows mixture **30** being held

11-194

in well **22** while servicing is being carried out (schematically illustrated at **32**).

[0038] It should be noted that while Figures 8-10 are presented in terms of a producing well, the method of use of the mixture of surfactant and co-surfactant according to the invention can likewise be advantageously applied to a well during drilling when drilling operations are to be suspended for various servicing and the like. During such stoppages, pressure in the formation must likewise be balanced and a column of fluid is typically left in the well for this purpose. Since flow conditions in the well itself are still important for effective flow, as well as potentially some of the porous media through which drilling is conducted, holding the surfactant/co-surfactant mixture in the well during a break from drilling can likewise be advantageous.

[0039] Upon completion of servicing, well **22** can be returned to service, preferably while recovering the mixture for use on other wells. Figure 10 shows well **22** returned to normal operation which is indicated schematically by arrow **34**.

[0040] The following example further illustrates the invention and the results which are obtained using same.

Example 1

[0041] Crude oil and water from several wells in different areas of the Orinoco River Belt fields were collected. The oil and water were placed in closed glass vessels at several oil and water saturations, at reservoir conditions of water salinity and temperature, in a thermally controlled oven. Inside each vessel was placed a small glass plate which was monitored for wettability conditions starting with a water-wet condition and further being naturally changed to oil wet after a medium time period of about three to four weeks at reservoir temperature of 145°F. For each glass plate, wettability was measured by

contact angle measurement techniques at the well temperature ranging from water-wet at the initial condition to oil wet after three weeks of aging process in the vessels at reservoir conditions.

[0042] After this treatment, the glass plates had a contact angle with oil which shows a strongly oil-wet condition as can be seen in Figure 3, which shows the oil spreading over the plate surface.

[0043] Each plate was then placed in a beaker for a soaking time with a mixture of equal amount of the well fluids in a mean average of 18% formation water and 82% extra heavy oil at 145°F temperature, with the formulation of the present invention, which in this particular example comprised a solution of 1% volume of tridecanol with 16 ethoxylated groups and 1% volume of ethanol, both admixed with 98% diluent which was a light hydrocarbon cut used in the production area to improve the flowability of extra heavy oil at surface conditions. The mixture and the plate were held for an 8 hour exposure time at reservoir temperature of 145°F and contact angle measurement showed wettability reversal from oil wet as shown in Figure 3 to water wet as shown in Figure 4. Note the bubbling up of the oil, and contact angle clearly indicative of the now water wet surface.

[0044] Similar results can be obtained by using various non-ionic and ionic surfactants. Suitable non-ionic surfactants include but are not limited to octilphenol having 9-16 EO, nonylphenol with an EO number from 4 to 25, preferably 9-18, fatty acids of 9-20 EO, n-tetradecanol of 9-20 EO, n-hexadecanol of 9-20 EO, laurate of sorbitan, and polyethoxilated fatty alcohols with EO number from 4 to 25, preferably 9 - 20.

[0045] Suitable ionic surfactants include but are not limited to n-alkyl sulfates of K or Na, n-alkyl trimethyl ammonium chloride and combinations thereof.

11-194

[0046] Suitable co-surfactants include but are not limited to any alcohol of the series of n-alcohols (C1 - C6), such as methanol, ethanol, propanol, butanol, pentanol, isopropanol and mixtures thereof.

[0047] The carrier fluid of the surfactant composition can be light oil, a light refinery cut, gasoil, diesel, diluent and water. The most preferred carrier fluid is an oil fluid.

[0048] Returning to the example, the glass plates were then soaked with a solution of mutual solvent for more than twenty four (24) hours to remove the water film and any visible hydrocarbon. The cleaned glass plates showed a clear and clean surface, but when a drop of water was placed on the plate, the water drop did not spread on the surface. The contact angle was measured and the plate still exhibited an oil-wet condition, as shown in Figure 5.

[0049] This indicates that even though the mineral surface, such as sandstone, can be cleaned of adhered hydrocarbons still on that surface, there remains a chemically adsorbed film of hydrocarbon and therefore on such a mineral surface there exists a strong oil-wet wettability. As mentioned previously, the oil-wet wettability is the most adverse condition for the recovery of oil in a porous media. Thus, even by undertaking the cost and steps of removing the adhered asphaltenes, the resulting cleaned surface remains oil wet.

[0050] Use of the formulation and method of the present invention creates a water film on the mineral surface, covering the previously chemically adsorbed hydrocarbons. This film creates an interface that will conduct hydrocarbon flow for very long periods of time between stimulation cycles. A very low pressure drawdown is achieved with the increased oil flow rates, thereby providing great benefits to the productivity and final recovery of oil from the drained area of the well.

11-194

Example 2

[0051] Porous media displacement equipment was set up to run a displacement test to simulate well flow conditions with and without the use of the formulation of the present invention. A Hassler cell was selected since a simulation of the formation grain pressure can be achieved with such a cell. Synthetic core material was made with commercial sand obtaining a core permeability between 6-7 Darcies. Pressure change at the inlet and outlet of the cell was monitored with sensors. Cylinders were coupled to the cell to provide, at reservoir temperature and pressure, the reservoir fluids and the stimulation fluid. After a long period of stabilization of constant flow with only reservoir fluid, the stimulation fluid of the present invention was injected from the outlet and held for a soaking period of 24 hours. After soaking, flow was restarted and the pressure drop was monitored. A measurement was taken of the porous volume displaced and time through the core as a production fluid. The oil used as reservoir fluid had the following characteristics:

Saturated % : 9 wt
 Aromatics % : 42 wt
 Resins %: 38 wt
 Asphaltenes % : 11 wt
 Acidity: 3.02 mg KOH/g
 Viscosidad CP 12,620 at 145 F
 API: 7.6
 % C wt 70.65
 % H wt 11.48
 Water with 13,000 ppm NaCl

[0052] The water used had 13,000 ppm of NaCl. The temperature of the oven was 145 °F. The formulation of the

11-194

present invention for the displacement test was a solution of 98 ml of diluent admixed with a previously mixed and homogenized mixture of 1 ml of tridecanol ethoxylated having 17 EO groups and 1 ml of ethanol.

[0053] Continuous flow was reached through the synthetic sand packed core saturated with oil to about 78% volume and a water saturation of about 22% by volume. The core was aged to reach an oil wet condition exposing it to pressure and temperature conditions of 1,150 psi and 145°F, which are typical of the Carabobo field of The Orinoco River Belt reservoirs, for about four weeks. Fluid flow was then reestablished by displacing oil until continuous flow was again reached. The stimulation system with diluent as a carrier fluid was then squeezed into the production area of the core and held at rest for a 24 hour time period. After that, oil was again allowed to flow, and an excellent lower differential pressure was observed for about three (3) pore volumes of oil produced in the collecting recipient. A second stimulation squeeze identical to the initial one was made and after 24 hours the flow was restarted, showing again improved properties to flow in two (2) porous media volumes of flow. A third cycle of stimulation was made observing the same results as the first cycle. Figure 6 shows a graph of the measured pressure during the several cycles of production and squeeze.

[0054] The same test was run with the reservoir fluids as shown below:

OIL:

Saturated % : 8 wt

Aromatics % : 44 wt

Resins %: 35 wt

Asphaltenes % : 13 wt

Acidity: 3.90 mg KOH/g

Viscosidad CP 10,420 at 145 F

11-194

API: 12
 % C wt 84.55
 % H wt 11.12

Water with 2,500 ppm NaCl

[0055] Figure 7 shows the results in pressure behavior in the displacement system while producing an average of three porous volumes in between each stimulation injection.

Example 3

[0056] Two highly deviated Orinoco River Belt wells from the Cerro Negro area were selected for pilot testing. Main characteristics of the wells are:

Well name	Reservoir name	Completion Date	Rock properties				Production Method	Original pressure psi	Actual pressure psi	Lithology
			Porosity	K	Vsh	Thickness				
			%	Darcy		ft				
CD 36	OFIM CNX9	04/1992	33	2.3	5.3	194	Mechanical pump & Gravel pack	1100	1095	sandstone
CD 37	OFIM CNX9	02/1993	32	5	7.0	192	PCP Gravel pack	1350	1000	sandstone

[0057] An amount of 270 barrels of diluent, which is a light crude oil of 23 API gravity, was admixed with a previously homogenized mix of 1.3 barrels of tridecyl alcohol of 12 EO groups and 1.3 barrels of methanol in a tank of a pumping truck. The admixture was recirculated in the tank for homogenization and pumped to well CD 36 through the annular space between the tubing and the casing. The stimulation fluid of the present invention contacted the gravel pack downhole and passed to about two feet penetration in the formation. The well was closed for a soaking period of 24 hours. The well was restarted thereafter and showed an increased production of about 200 bpd that has been stable for a period of 60 days.

[0058] Another amount of 133 barrels of diluent, a light crude oil of 23 API gravity was admixed with a previously

11-194

homogenized mix of 0.7 barrels of tridecyl alcohol of 12 EO groups and 0.7 barrels of methanol in a tank of a pumping truck. The admixture was recirculated in the tank for homogenization and pumped to well CD 37 through the annular space between the tubing and the casing. The stimulation fluid of the present invention contacted the gravel pack downhole and passed to about two inches of penetration in the formation. The well was closed for a soaking period of 24 hours. The well was restarted thereafter and showed a production of 80 barrels net of oil per day and has been stable for a period of 60 days thereafter. The net oil production before the stimulation was 24 barrels of net oil.

[0059] These pilot tests establish that the stimulation fluid, or formulation, of the present invention is highly effective at improving hydrocarbon flow and production through porous media treated with fluid. The fluid is made from readily available constituents, and the method can be carried out using known equipment already available for injecting other well stimulation fluids.

[0060] It is to be understood that the invention is not limited to the illustrations described and shown herein, which are deemed to be merely illustrative of the best modes of carrying out the invention, and which are susceptible of modification of form, size, arrangement of parts and details of operation. The invention rather is intended to encompass all such modifications which are within its spirit and scope as defined by the claims.

11-194

We Claim:

1. A method for improving flow conditions in a porous media while servicing a well penetrating to the porous media, comprising the steps of:

stopping drilling or production activities on the well;

introducing a well control fluid into the well and the porous media, the well control fluid comprising a mixture of a surfactant, a co-surfactant and a carrier fluid

holding the well control fluid in the well and the porous media in the presence of water while the well is being serviced, such that the fluid penetrates the porous media and forms a water film on surfaces of the porous media; and

when well servicing is finished, resuming drilling or production activities on the well.

2. The method of claim 1, wherein the surfaces of the porous media prior to treatment with the mixture have hydrocarbons adhered to them, and wherein the water film is formed over the surfaces and the hydrocarbon adhered to the surfaces.

3. The method of claim 1, wherein the porous media is a subterranean hydrocarbon bearing formation containing asphaltene and wherein the asphaltene is adhered to the surfaces of the porous media.

4. The method of claim 3, wherein the hydrocarbon has an API gravity of between 6 and 16.

5. The method of claim 3, wherein the hydrocarbon has an API gravity of between 6 and 12.

11-194

6. The method of claim 1, wherein the surfactant is selected from the group consisting of cationic surfactants, nonionic surfactants, amphoteric surfactants and combinations thereof.

7. The method of claim 1, wherein the co-surfactant is an alcohol co-surfactant.

8. The method of claim 7, wherein the alcohol co-surfactant is selected from the group consisting of methanol, ethanol, propanol, butanol, pentanol, isopropanol, and combinations thereof.

9. The method of claim 1, wherein the carrier fluid is selected from the group consisting of organic solvents, light hydrocarbons, diluents, light crude oil, and combinations thereof, and water.

10. The method of claim 1, wherein the carrier fluid is a light crude oil with an API gravity between 20 to 25.

11. The method of claim 1, wherein the surfactant is an ethoxylated fatty alcohol having between 4 and 60 ethoxylated groups, and wherein the co-surfactant is methanol and/or ethanol.

12. The method of claim 11, wherein the mixture contains substantially equal amounts by volume of surfactant and co-surfactant.

13. The method of claim 11, wherein the mixture contains each of the surfactant and the co-surfactant at a concentration of between 0.5 and 10% wt.

11-194

14. The method of claim 11, wherein the mixture contains each of the surfactant and the co-surfactant at a concentration of between 1 and 4% wt.

15. The method of claim 1, wherein the surfaces of the porous media define pore space for the hydrocarbon, and wherein the surfaces are defined by a material selected from quartz, feldspar, siliceous mineral, carbonaceous mineral, clays, and combinations thereof.

11-194

ABSTRACT

A method for improving flow conditions in a porous media while servicing a well penetrating to the porous media, comprising the steps of: stopping drilling or production activities on the well; introducing a well control fluid into the well and the porous media, the well control fluid comprising a mixture of a surfactant, a co-surfactant and a carrier fluid holding the well control fluid in the well and the porous media in the presence of water while the well is being serviced, such that the fluid penetrates the porous media and forms a water film on surfaces of the porous media; and when well servicing is finished, resuming drilling or production activities on the well.




FIG. 1




FIG. 2




FIG. 3






FIG. 4

**FIG. 5****FIG. 6**




FIG. 7




FIG. 8




FIG. 9




FIG. 10

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194
		Application Number	
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	---

Applicant Information:

Applicant 1					Remove
Applicant Authority		☒ Inventor		☐ Legal Representative under 35 U.S.C. 117	☐ Party of Interest under 35 U.S.C. 118
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Pablo		Manrique		
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service					
City	Caracas	Country Of Residenceⁱ	VE		
Citizenship under 37 CFR 1.41(b) ⁱ		VE			
Mailing Address of Applicant:					
Address 1		Edificio Caroata Apartamento 10C			
Address 2		Parque Central			
City	Caracas	State/Province			
Postal Code		Countryⁱ	VE		
Applicant 2					Remove
Applicant Authority		☒ Inventor		☐ Legal Representative under 35 U.S.C. 117	☐ Party of Interest under 35 U.S.C. 118
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Franklin		Archer		
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service					
City	Caracas	Country Of Residenceⁱ	VE		
Citizenship under 37 CFR 1.41(b) ⁱ		VE			
Mailing Address of Applicant:					
Address 1		Edificio Lagunillas Apto. 9C2, El Valle			
Address 2					
City	Caracas	State/Province			
Postal Code		Countryⁱ	VE		
Applicant 3					Remove
Applicant Authority		☒ Inventor		☐ Legal Representative under 35 U.S.C. 117	☐ Party of Interest under 35 U.S.C. 118
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Maria	Gracia	Araujo		
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service					
City	Barinas	Country Of Residenceⁱ	VE		

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194	
		Application Number		
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS			
Citizenship under 37 CFR 1.41(b) i		VE		
Mailing Address of Applicant:				
Address 1		Urb. Raul Leoni, Sector 5 Vereda 23		
Address 2		Casa Nro. 11		
City	Barinas	State/Province		
Postal Code		Country ⁱ	VE	
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button. Add				

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).			
☐ An Address is being provided for the correspondence information of this application.			
Customer Number	34704		
Email Address	docket@bachlap.com	Add Email	Remove Email

Application Information:

Title of the Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		
Attorney Docket Number	11-194	Small Entity Status Claimed	☐
Application Type	Provisional		
Subject Matter	Utility		
Suggested Class (if any)		Sub Class (if any)	
Suggested Technology Center (if any)			
Total Number of Drawing Sheets (if any)	5	Suggested Figure for Publication (if any)	

Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☐ Request Not to Publish. I hereby request that the attached application not be published under 35 U.S. C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country; or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Enter either Customer Number or complete the Representative Name section below. If both sections are completed the Customer Number will be used for the Representative Information during processing.			
Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194
		Application Number	
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		
Customer Number	34704		

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78(a)(2) or CFR 1.78(a)(4), and need not otherwise be made part of the specification.

Prior Application Status		Remove	
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the [Add](#) button.

Foreign Priority Information:

This section allows for the applicant to claim benefit of foreign priority and to identify any prior foreign application for which priority is not claimed. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55(a).

			Remove
Application Number	Country ⁱ	Parent Filing Date (YYYY-MM-DD)	Priority Claimed
			☒ Yes ☐ No

Additional Foreign Priority Data may be generated within this form by selecting the [Add](#) button.

Assignee Information:

Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office.

Assignee 1			Remove
If the Assignee is an Organization check here. ☒			
Organization Name	Intevep, S.A.		

Mailing Address Information:

Address 1	Apartado 76343		
Address 2			
City	Caracas	State/Province	
Country ⁱ	VE	Postal Code	1070A
Phone Number		Fax Number	
Email Address			

Additional Assignee Data may be generated within this form by selecting the [Add](#) button.

Signature:

A signature of the applicant or representative is required in accordance with 37 CFR 1.33 and 10.18. Please see 37 CFR 1.4(d) for the form of the signature.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number		11-194	
		Application Number			
Title of Invention		WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS			
Signature		/george a. coury/		Date (YYYY-MM-DD)	2011-10-20
First Name	George	Last Name	Coury	Registration Number	34309

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

TRADUCCIÓN DEL INGLÉS AL ESPAÑOL del documento de prioridad relacionado con la solicitud de Patente de los Estados Unidos No. 61/549,534 titulada:

FLUIDO DE TRABAJO/CONTROL PARA POZOS DE CRUDO PESADO Y EXTRA PESADO

ANEXOS. La solicitud de Patente de los Estados Unidos No. 61/549,534 arriba mencionada y Certificación del Comisionado de Patentes y Marcas de los Estados Unidos.

LOS ESTADOS UNIDOS DE AMÉRICA
A TODO AQUEL QUE PUEDA LLEGARLE LA PRESENTE:

DEPARTAMENTO DE COMERCIO DE ESTADOS UNIDOS
Oficina de Marcas y Patentes de Estados Unidos

10 de enero de 2013

LA PRESENTE CERTIFICA QUE EL ANEXO ES UNA COPIA VERDADERA TOMADA DE LOS ARCHIVOS DE LA OFICINA DE MARCAS Y PATENTES DE LOS ESTADOS UNIDOS DE LOS DOCUMENTOS DE LA SOLICITUD DE PATENTE IDENTIFICADA ABAJO LA CUAL CUMPLIÓ CON LOS REQUERIMIENTOS PARA OTORGÁRSELE UNA FECHA DE PRESENTACIÓN BAJO EL 35 USC 111.

SOLICITUD NÚMERO: 61/549,534
FECHA DE PRESENTACIÓN: *Octubre 20, 2011*

EL CÓDIGO DEL PAÍS Y EL NÚMERO DE SU SOLICITUD PRIORITARIA A SER UTILIZADO PARA PRESENTACIÓN EN EL EXTRANJERO BAJO LA CONVENCION DE PARÍS ES *US61/549,534*.

Por autoridad del
Subsecretario de Comercio para la Propiedad Intelectual
y Director de la Oficina de Marcas y Patente de Estados Unidos

(firma)

M. TARVER
Funcionario que Certifica

Hay un sello que dice:
OFICINA DE MARCAS Y PATENTE DE ESTADOS UNIDOS
DEPARTAMENTO DE COMERCIO

REIVINDICACIONES

1. Un método para mejorar las condiciones de flujo en un medio poroso mientras se rehabilita un pozo que penetra al medio poroso, que comprende las etapas de:

detener la perforación o actividades de producción del pozo;

introducir un fluido de control de pozo en el pozo y el medio poroso, el fluido de control de pozo comprende una mezcla de un tensoactivo, un co-tensoactivo y un fluido portador;

mantener el fluido de control de pozo en el pozo y el medio poroso en la presencia de agua aunque el pozo este siendo rehabilitado, de tal manera que el fluido penetra el medio poroso y forma una película de agua sobre las superficies del medio poroso; y

cuando la rehabilitación del pozo termina, se resumen el perforado o las actividades de producción en el pozo.

2. El método de la reivindicación 1, en donde las superficies del medio poroso antes del tratamiento con la mezcla tiene hidrocarburos adheridos a ellos, y en donde la película de agua se forma sobre las superficies y el hidrocarburo adherido a las superficies.

3. El método de la reivindicación 1, en donde el medio poroso es una formación que posee hidrocarburo subterráneo que contiene asfaleno y en donde el asfaleno se adhiere a la superficie del medio poroso.

4. El método de la reivindicación 3, en donde el hidrocarburo tiene una gravedad API de entre 6 y 16.

5. El método de la reivindicación 3 en donde el hidrocarburo tiene una gravedad API de entre 6 y 12.

6. El método de la reivindicación 1, en donde el tensoactivo se selecciona del grupo que consiste de tensoactivo catiónico, tensoactivos no iónicos, tensoactivos anfotéricos y combinaciones de los mismos.

7. El método de la reivindicación 1, en donde el co-tensoactivo es un co-tensoactivo de alcohol.

8. El método de la reivindicación 7, en donde el co-tensoactivo de alcohol se selecciona del grupo que consiste de metanol, etanol, propanol, butanol, pentanol, isopropanol, y combinaciones de los mismos.

9. El método de la reivindicación 1, en donde el fluido portador se selecciona del grupo que consiste de disolventes orgánicos, hidrocarburos ligeros, diluyentes, petróleo crudo ligero, y combinaciones de los mismos, y agua.

10. El método de la reivindicación 1, en donde el fluido portador es un petróleo crudo ligero con una gravedad API entre 20 a 25.

11. El método de la reivindicación 1, en donde el tensoactivo es un nonil fenol etoxilado que tiene entre 4 y 60 grupos etoxilados, y en donde el co-tensoactivo es etanol.


12. El método de la reivindicación 11, en donde la mezcla contiene cantidades sustancialmente iguales en volumen del tensoactivo y el co-tensoactivo.

13. El método de la reivindicación 11, en donde la mezcla contiene cada uno del tensoactivo y el co-tensoactivo a una concentración de entre 0,5 y 10% en peso.

14. El método de la reivindicación 11, en donde la mezcla contiene cada uno del tensoactivo y el co-tensoactivo a una concentración de entre 1 al 4% en peso.

15. El método de la reivindicación 1, en donde las superficies del medio poroso definen el espacio de poro para el hidrocarburo, y en donde las superficies se definen mediante un material seleccionado del grupo que consiste de cuarzo, feldespato, mineral silíceo, mineral carbonáceo, arcilla, y combinaciones de los mismos.

PA 7396301



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

January 16, 2013

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: *13/529,140*

FILING DATE: *June 21, 2012*

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS CONVENTION, IS *US13/529,140*

By Authority of the
Under Secretary of Commerce for Intellectual Property
and Director of the United States Patent and Trademark Office



N. Williams
N. WILLIAMS
Certifying Officer

Electronic Acknowledgement Receipt

EFS ID:	13070960
Application Number:	13529140
International Application Number:	
Confirmation Number:	1923
Title of Invention:	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS
First Named Inventor/Applicant Name:	Pablo Manrique
Customer Number:	34704
Filer:	George A. Coury/Rachel Piscitelli
Filer Authorized By:	George A. Coury
Attorney Docket Number:	11-194-2
Receipt Date:	21-JUN-2012
Filing Date:	
Time Stamp:	13:24:48
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	Deposit Account
Payment was successfully received in RAM	\$1250
RAM confirmation Number	13318
Deposit Account	020184
Authorized User	

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
-----------------	----------------------	-----------	-------------------------------------	---------------------	---------------------

1		11-194-2_Specification_6-21-12.pdf	192427 9d51ac18a6665bcc0a8f0e30e7051d74ac9b7778	yes	29
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	25	
	Claims		26	28	
	Abstract		29	29	
Warnings:					
Information:					
2	Oath or Declaration filed	11-194-2_Declaration_.pdf	170374 1ea654ce49c730b95d0c2e6cce27accaf7dddc1	no	3
Warnings:					
Information:					
3	Drawings-only black and white line drawings	11-194-2_6-21-2012.pdf	1155993 b1b43f28fd2ac1a0b2c2cee4fe83b14f4d64f80	no	9
Warnings:					
Information:					
4	Application Data Sheet	11-194-2_ADS_6-21-12.pdf	897148 6e2e2fd25a92ce5890d71ecce3d8198b68e668d	no	5
Warnings:					
Information:					
5	Fee Worksheet (SB06)	fee-info.pdf	33506 42fc33bafb11c1352bef9f05c99d8cf30870b35	no	2
Warnings:					
Information:					
Total Files Size (in bytes):			2449448		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

11-194-2

WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation-in-part of U.S. patent application Serial Number 12/973,022 which was filed on December 20, 2010. This application also claims the benefit of provisional application 61/549,534 which was filed on October 20, 2011.

BACKGROUND OF THE INVENTION

[0002] The invention relates to a formulation and method of using same for improving well productivity in hydrocarbon reservoirs.

[0003] Improvement in productivity of heavy and extra heavy oil wells such as those found in the Orinoco River Belt in Venezuela is clearly desirable. Some of the largest reservoirs of heavy and extra heavy oil in the world are in Venezuela and hold oil having API gravity within the range of 6 to 16. Unfortunately, the production rate of much of this oil is unacceptable.

[0004] It is a high concern in the exploitation of heavy and extra heavy oil reservoirs to increase productivity during the well lifetime. With these wells, primary cold production schemes are quickly abandoned in favor of thermal methods to improve well flowability by reducing oil viscosity in the reservoir. These processes are costly and also still produce a low output in terms of final recovery. They also have serious problems of production of sour gas such as H₂S and CO₂ which are very costly to address. Such thermal recovery methods typically produce final oil recovery below 35 - 40%.

[0005] Venezuelan heavy and extra heavy Orinoco River Belt oil sandstones are exceptional reservoirs. 60% of the

11-194-2

reservoirs of this type have a KH/U value between 40 and close to 1,000 in very many cases. Unlike other reservoirs, however, the oil in Venezuelan extra heavy oil reservoirs is flowable at reservoir conditions.

[0006] Even these wells, however, have a final recovery by cold production which is very low and perhaps in most cases below three (3) per cent of the original oil in place. The conditions for flow of oil in those reservoirs, with even excellent petrophysical properties, are very unfavorable to the flow of oil. The components of the heavy and extra heavy oil, particularly the asphaltenes in natural form in the native oil, are capable by natural fluid-rock interactions of generating an oil-wet condition at the surface of the natural mineral components of the sandstone. This produces the most adverse conditions to flow of oil in a porous media. This is a natural oil-wet condition of the reservoir media, which is a completely different condition as compared to formation damage in the well resulting from drilling or production activities, which could also happen in the well.

[0007] The need exists for improvement in production rates from wells producing from formations containing heavy and extra heavy wells, particularly those which contain asphaltenes and other hydrocarbons which lead to oil wet flow environments.

SUMMARY OF THE INVENTION

[0008] As a response to the above problems, especially to the natural oil wet conditions of the sandstone and the extremely low well productivity and recovery of the original oil in place, the present invention provides a formulation or stimulation fluid and a method of using the formulation for improving well productivity in cold production schemes and also in producing wells using thermal methods. The result is reflected by a

11-194-2

better flow rate in the well, a lower pressure drawdown, and an improved recovery from the drainage area of the formation.

[0009] In accordance with the invention, a method is therefore provided for altering flow conditions in a porous media containing hydrocarbons, which method comprises the steps of preparing a mixture of a surfactant, a co-surfactant and a carrier fluid; transporting the mixture to the porous media; and holding the mixture in the porous media in the presence of water for a period of time sufficient to form a water film on the surfaces of the porous media.

[0010] It should be appreciated that the holding step involves holding the mixture in the well under substantially static flow conditions to allow the water film to form as desired. Thus, according to the invention, the treatment is advantageously carried out during other servicing of the well when production or drilling would be stopped anyway, thereby taking advantage of the down-time of the well and gaining a flow advantage in the well while the flow is being serviced.

[0011] In further accordance with the invention, therefore, a method is provided for improving flow conditions in a porous media while servicing a well penetrating to the porous media, comprising the steps of: stopping drilling or production activities on the well; introducing a well control fluid into the well, the well control fluid comprising a mixture of a surfactant, a co-surfactant and a carrier fluid; and holding the well control fluid in the well and the porous media in the presence of water while the well is being serviced, such that the fluid penetrates the porous media and forms a water film on surfaces of the porous media; and when well servicing is finished, resuming drilling or production activities on the well.

[0012] The result of the treatment of the present invention is a novel treated surface which enhances flow of hydrocarbons

11-194-2

through pores defined by the treated surface, and this comprises a porous media having pore surfaces and containing heavy hydrocarbon including asphaltene, wherein the asphaltene is adhered to the pore surfaces, and wherein a water film is adhered to the pore surfaces and asphaltene.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] A detailed description of preferred embodiments of the present invention follows, with reference to the accompanying drawings, wherein:

[0014] FIG. 1 schematically illustrates a treated surface in accordance with the invention;

[0015] FIG. 2 illustrates typical and preferred flow rates from the hydrocarbon producing well;

[0016] FIGS. 3 and 4 illustrate a test glass plate which is oil-wet in FIGS. 3, and which has been treated in accordance with the present invention in FIG. 4;

[0017] FIG. 5 shows the test plate is still oil-wet even after solvent cleaning;

[0018] FIGS. 6-8 illustrate the method of the present invention being carried out while a well is being serviced;

[0019] FIG. 9 illustrates the return permeability test using the formulation and method of the present invention with three cycles of injection in a reservoir core plug;

[0020] FIG. 10 illustrates relative permeability curves in a reservoir core plug using formation water and the formulation of the present invention with produced water as a carrier fluid;

[0021] FIG. 11 illustrates a test glass plate before the plate is treated with the formulation of present invention and after treatment and 24 hours soaking time with fluids of the well CD 1405 of Cabrutica Field, Junin Division, Orinoco River Belt;

11-194-2

[0022] FIG. 12 illustrates the evolution of well VB19 in parameters as intake pump pressure, progressive cavity pump rpm before and after treatment with the formulation of the present invention; and

[0023] FIG. 13 illustrates the reported monitored downhole parameters as intake pump pressure, progressive cavity pump rpm in the well VD 18 of Petrocedeno field, Venezuela before and after treatment with the formulation of the present invention.

DETAILED DESCRIPTION

[0024] The invention relates to a formulation or stimulation fluid which has a surfactant/co-surfactant mixture and a method for using same to treat surfaces of a hydrocarbon bearing formation and thereby enhance flow of hydrocarbons through same. This method is advantageously used to alter flow conditions in the formation to improve production of hydrocarbons from hydrocarbon-bearing formations. This can be done at any suitable time, but one particularly useful time to treat the well and formation is when a well is shut down for servicing.

[0025] As mentioned above, many significant hydrocarbon deposits in the world contain very large quantities of hydrocarbons under conditions where it is very difficult to produce them. One example of this is asphaltene-bearing hydrocarbon deposits in the Orinoco River Belt of Venezuela. In these formations, which typically have high and low pressures in the range of 300-1,500 psi, the heavy hydrocarbon fractions contained in the formation, especially asphaltenes, tend to adhere to the pore surfaces of the hydrocarbon and thereby create an oil-wet environment in the reservoir. As detailed above, this oil-wet flow environment is not at all conducive to production of those hydrocarbons from the formation. Further, as will be demonstrated below, this asphaltene is not easily removed because a portion of the hydrocarbon adsorbs into the

11-194-2

rock surface making even cleaned surfaces oil wet and, therefore, unfavorable for good hydrocarbon flow. According to the invention, a water film is formed over the rock surfaces and also over the chemically adsorbed hydrocarbon so that the surfaces when coated in this manner are water wet. This greatly increases the flowability of hydrocarbons through the treated rock formation.

[0026] In accordance with the present invention, the surfactant/co-surfactant mixture is used to form a water film over the pore spaces of the formation, and also over the asphaltenes adhered to the pore surfaces, so as to provide a water-wet surface between the flow surfaces defined by the pore surface of the rock and asphaltene adhered thereto, and the volume of hydrocarbon in the formation which is intended to be produced. This water film increases flow of hydrocarbons through the formation, and thereby enhances production of hydrocarbon from the formation. Over a period of time, the water film eventually is removed by fluids flowing past the film, at which point the surfactant/co-surfactant mixture of the present invention can again be introduced into the hydrocarbon bearing formation to again deposit a fresh water film for use in the next period of production. This follow up treatment can advantageously be done at each well servicing, thereby keeping a water film in place as desired.

[0027] According to the invention, the surfactant/co-surfactant mixture preferably contains surfactant, co-surfactant and a fluid carrier, each of which has the following preferred constituents.

[0028] The surfactant is preferably selected from the group consisting of cationic surfactants, non-ionic surfactants, amphoteric surfactants and combinations thereof. The surfactant is further preferably an ethoxylated nonyl phenol having between 4 and 60 ethoxylated groups.

11-194-2

[0029] Suitable non-ionic surfactants include but are not limited to octilphenol having 9-16 EO, nonylphenol with an EO number from 4 to 80, preferably 20 - 55, fatty acids of 9-20 EO, n-tetradecanol of 9-20 EO, n-hexadecanol of 9-20 EO, laurate of sorbitan, and polyethoxilated fatty alcohols with EO number from 4 to 25, preferably 9 - 20. Suitable ionic surfactants include but are not limited to n-alkyl sulfates of K or Na, n-alkyl trimethyl ammonium chloride and combinations thereof.

[0030] The co-surfactant is preferably an alcohol co-surfactant, preferably one or more n-alcohols (C1-C6), and more preferably selected from the group consisting of methanol, ethanol, propanol, butanol, pentanol, isopropanol and combinations thereof. The most preferred co-surfactant is methanol and/or ethanol.

[0031] The carrier fluid can be selected from the group consisting of organic solvents, light hydrocarbons, diluents, light crude oil and combinations thereof, brine, produced formation water and water. More specifically, the carrier fluid can be light oil, a light refinery cut, gasoil, diesel, diluent and water. The most preferred carrier fluid is water compatible with the formation fluids and minerals present in the formation rock. One example is produced water from wells in the same field or potable water with the same salinity of the formation brine and clay control additives.

[0032] The surfactant/co-surfactant mixture preferably is prepared having substantially equal amounts by volume of the surfactant and co-surfactant, and the overall mixture with carrier fluid preferably contains each of the surfactant and co-surfactant in an amount between 0.5 and 5% by volume, more preferably between 1 and 4% by volume.

[0033] In accordance with the invention, the surfactant/co-surfactant mixture can be prepared by mixing the above-identified constituents at the surface and then transporting,

11-194-2

for example by pumping, the resulting mixture or stimulation fluid into a hydrocarbon producing formation, for example through a well positioned from the surface to the subterranean formation, so that the mixture penetrates into the hydrocarbon-bearing formation around the well, typically into a radius surrounding the well of at least about 2 inches, preferably between 12 inches and as large as possible, for example up to 10 feet. There is no limitation in the amount of fluid that can drain to the formation since at all distances, contact of the rock surface with the fluid will be beneficial. The penetration area into the formation is the area to be treated in accordance with the present invention.

[0034] Once a sufficient volume of fluid is pumped into the formation, this volume is then held in place in the formation in the presence of water. The holding step can be done for the duration of a well servicing procedure which would require a temporary shutdown of the well, and in any event the holding should also be for a time sufficient to form the desired water film over surfaces of the pore spaces of the hydrocarbon and also over the hydrocarbons adhered to these surfaces. This advantageously provides a water-wet flow environment which is advantageous to the flow of hydrocarbon through the porous media, and therefore produces a flow environment which is far more conducive to the flow of oil than the natural oil-wet flow environment present in the well under natural formation conditions wherein the heavy hydrocarbons, and especially asphaltenes, are adhered to the pore surfaces of the porous media. The suitable amount of time to hold the fluid in the formation will vary with different wells, fluids and conditions, but will typically be between 12 and 24 hours and a preferred range of time between 18 and 24 hours. Any further time will not affect the benefits of the treatment in the formation.

[0035] Production from the treated well can be conducted while monitoring pressure drawdown in the well, and when the pressure drops sufficiently, or the well again needs servicing, the formation can be treated again in accordance with the present invention.

[0036] The typical formation for which the present invention can be utilized can be any formation wherein the forming of a water film over the pore surfaces would be beneficial to the overall hydrocarbon production from the formation. A particularly desirable application of the present invention is in formations having hydrocarbons with an API gravity of between 6 and 16, and even more preferably in formations containing hydrocarbons having an API gravity of between 6 and 12. These heavy and extra heavy hydrocarbon deposits in certain areas typically are very large in volume, but also contain asphaltenes as discussed above, and these are ideal candidates for treatment according to the present invention to enhance production. The typical rock formations containing such hydrocarbons have pore spaces which define the void volume which holds the hydrocarbons and which creates the permeability that allows the hydrocarbons to flow. The rock defining the pore surfaces of these formations are typically defined by quartz, feldspar, siliceous mineral, carbonaceous mineral, clays and combinations thereof.

[0037] FIG. 1 schematically illustrates a surface of a hydrocarbon bearing formation treated in accordance with the present invention. As seen in FIG. 1, a mineral surface 10 which defines the pore space of the formation has rock mineral active sites 12 along surface 10, and these rock mineral active sites 12 interact with hydrocarbons under the typical pressure in the formation such that chemically adsorbed hydrocarbons 14 are closely adhered to surface 10, particularly at rock mineral active sites 12.

11-194-2

[0038] According to the invention, the surfactant/co-surfactant mixture of the present invention is introduced to the formation and held there in the presence of water so that a film of water is formed over the adsorbed hydrocarbons 14 as well as the rock mineral active sites 12 of mineral surface 10. FIG. 1 shows surfactant/co-surfactant mixture adsorbed in the form of water film 16 which is schematically illustrated as a double layer to represent the surfactant/co-surfactant mixture. This produces a water-wet condition at the surface, which enhances flow of hydrocarbon through flow areas and pore space defined by such a treated surface. The water which forms the film can be water already present in the rock formation fluids and/or from the carrier fluid if a water containing carrier fluid is used. The water salinity can be in the range between 80 ppm up to 45,000 ppm.

[0039] Pressure drawdown, or the pressure drop from the formation to the well bore, is a good measure of the flowability in the formation. When the pressure drawdown is relatively small, this indicates good flowing properties in the formation to the well. While producing from a well that has been treated according to the invention, it is desirable to monitor the pressure drawdown, and after a certain amount of oil has been produced from a treated well, the pressure drawdown starts to increase. This increase in pressure drawdown indicates that the water film has been worn away or removed due to relatively high velocity flow of well fluids passing over the film to the well. This stream removes the water film by desorption of the surfactant and co-surfactant from the mineral surface and restoring the natural oil-wet initial condition at the mineral surface. At this stage, according to the invention, the well can be treated again with the same formulation, and this process can be repeated as many times as necessary until no more hydrocarbon fluids flow to the well even after treatment. With cyclic

11-194-2

stimulation, the porous media will improve final recovery of the initial oil in place in the drainage area by cold production by potentially many times the amount of 3% typically reported as the well output obtained without stimulation. The present invention also reduces the time and need of costly thermal processes to reach this level of oil recovery. Further, the treatment is carried out during periods when the well is down for other servicing, thereby maximizing the overall efficiency by reducing or altogether avoiding any down time solely for treatment according to the invention.

[0040] FIG. 2 illustrates typical and desired flow rates from a hydrocarbon production well. The starts and stops shown in actual flow show a trend (line A) which is not desirable, while a preferred pressure behavior is shown at line B. The difference of the area between lines A and line B is an indication of greater recovery of oil from the same well in the same well drained area.

[0041] Turning to FIGS. 6-8, a well 22 is shown extending from surface 24 to a subterranean formation 26. Well 22 communicates with formation 26 through perforations 28. From time to time, such a well must be taken out of production, for example for servicing of various surface equipment, static pressure testing and the like. When such a procedure is to be conducted, it is typical to leave a column of fluid in the well to balance pressure of the formation. According to this aspect of the invention, the above-described mixture of surfactant and co-surfactant is used to simultaneously balance formation pressure and treat surface wettability of the porous media in the formation as well. Thus, FIG. 6 shows mixture 30 being introduced to well 22, and FIG. 7 shows mixture 30 being held in well 22 while servicing is being carried out (schematically illustrated at 32).

11-194-2

[0042] It should be noted that while FIGS. 6-8 are presented in terms of a producing well, the method of use of the mixture of surfactant and co-surfactant according to the invention can likewise be advantageously applied to a well during drilling when drilling operations are to be suspended for various servicing and the like. During such stoppages, pressure in the formation must likewise be balanced and a column of fluid is typically left in the well for this purpose. Since flow conditions in the well itself are still important for effective flow, as well as potentially some of the porous media through which drilling is conducted, holding the surfactant/co-surfactant mixture in the well during a break from drilling can likewise be advantageous.

[0043] Upon completion of servicing, well 22 can be returned to service, preferably while recovering the mixture for use on other wells. FIG. 8 shows well 22 returned to normal operation which is indicated schematically by arrow 34.

[0044] In deviated, horizontal, and/or multilateral wells, the formulation can be used in the same way. In those cases, the drainage of the formulation to the porous media will occur through the best channels of flow in the well making the water wet and highly conductive to oil channels thereby improving oil flow to the well. In the case of horizontal wells where pressure drawdown is very high at the heel of the well, during treatment while servicing the well for pump, rods, tubing replacements or other service jobs, the use of the formulation of the present invention as a servicing fluid will be very beneficial to oil production. When the pressure of reservoir is sufficiently high that servicing fluid are kept away from the rock surface, pumping of some volume of the fluid to the formation while servicing the well can be done to stimulate the well formation.

[0045] The following example further illustrates the invention and the results which are obtained using same.

11-194-2

Example 1

[0046] Crude oil and water from several wells in different areas of the Orinoco River Belt fields were collected. The oil and water were placed in closed glass vessels at several oil and water saturations, at reservoir conditions of water salinity and temperature, in a thermally controlled oven. Inside each vessel was placed a small glass plate which was monitored for wettability conditions starting with a water-wet condition and further being naturally changed to oil wet after a medium time period of about three to four weeks at reservoir temperature of 145°F. For each glass plate, wettability was measured by contact angle measurement techniques at the well temperature ranging from water-wet at the initial condition to oil wet after three weeks of aging process in the vessels at reservoir conditions.

[0047] After this treatment, the glass plates had a contact angle with oil which shows a strongly oil-wet condition as can be seen in FIG. 3, which shows the oil spreading over the plate surface.

[0048] Each plate was then placed in a beaker for a soaking time with a mixture of equal amount of the well fluids in a mean average of 18% formation water and 82% extra heavy oil at 145°F temperature, with the formulation of the present invention, which in this particular example comprised a solution of 1% volume of tridecanol with 16 ethoxylated groups and 1% volume of ethanol, both admixed with 98% diluent which was a light hydrocarbon cut used in the production area to improve the flowability of extra heavy oil at surface conditions. The mixture and the plate were held for an 8 hour exposure time at reservoir temperature of 145°F and contact angle measurement showed wettability reversal from oil wet as shown in FIG. 3 to water wet as shown in FIG. 4. Note the bubbling up of the oil,

11-194-2

and contact angle clearly indicative of the now water wet surface.

[0049] Returning to the example, the glass plates were then soaked with a solution of mutual solvent for more than twenty four (24) hours to remove the water film and any visible hydrocarbon. The cleaned glass plates showed a clear and clean surface, but when a drop of water was placed on the plate, the water drop did not spread on the surface. The contact angle was measured and the plate still exhibited an oil-wet condition, as shown in FIG. 5.

[0050] This indicates that even though the mineral surface, such as sandstone, can be cleaned of adhered hydrocarbons still on that surface, there remains a chemically adsorbed film of hydrocarbon and therefore on such a mineral surface there exists a strong oil-wet wettability. As mentioned previously, the oil-wet wettability is the most adverse condition for the recovery of oil in a porous media. Thus, even by undertaking the cost and steps of removing the adhered asphaltenes, the resulting cleaned surface remains oil wet.

[0051] Use of the formulation and method of the present invention creates a water film on the mineral surface, covering the previously chemically adsorbed hydrocarbons. This film creates an interface that will conduct hydrocarbon flow for very long periods of time between stimulation cycles. A very low pressure drawdown is achieved with the increased oil flow rates, thereby providing great benefits to the productivity and final recovery of oil from the drained area of the well.

Example 2

[0052] Crude oil and formation water from well CD1405 was collected as well as production water from disposal tank 903 from principal station of Cabrutica field in the Orinoco River.

11-194-2

Belt field. The characteristics of the crude oil and formation water are:

OIL:

Saturated % : 8 wt

Aromatics % : 44 wt

Resins %: 35 wt

Asphaltenes % : 13 wt

Acidity: 3.90 mg KOH/g

Viscosity CP 10,420 at 145 F

API: 9

% C wt 84.55

% H wt 11.12

Formation Water with 2,500 ppm NaCl

[0053] The oil and formation water were placed in closed glass vessels at 20 % saturation of formation water and 80 % of oil saturations, at reservoir conditions of temperature of 145°F, in a thermally controlled oven. Inside each vessel was placed a small glass plate which was monitored for wettability conditions starting with a water-wet condition and further being naturally changed to oil wet after a time period of aging of three weeks at reservoir temperature of 145°F. For the glass plate, wettability was measured by contact angle measurement techniques at the well temperature ranging from water-wet at the initial condition to oil wet after three weeks of aging process in the vessels at reservoir conditions as shown in FIG. 11 in the left side view, indicating a contact angle of 137.5° at the aged condition, as it should be expected in the reservoir, showing the oil spreading over the plate surface.

[0054] The plate was then placed in a beaker for a soaking time with a mixture of equal amount of the well fluids in a mean average of 20 % formation water and 80 % of the 12 °API extra

11-194-2

heavy oil at 145°F temperature, with the formulation of the present invention, which in this particular example comprised a solution of 0.5 % volume of ethoxylated nonyl phenol with 30 ethoxylated groups and 0.5% volume of ethanol, both admixed with 99% of production water from disposal tank of the Cabrutica field of the Junín Division of The Orinoco River Belt. A one (1) lb/bbl of potassium acetate was added for clay control to the formulation. The mixture and the plate were held for 24 hour exposure time at reservoir temperature of 145°F and contact angle measurement showed wettability reversal from oil wet of 137.5° to water wet with a contact angle of 45.1° as shown in FIG. 11 in the right side view. Note the bubbling up of the oil, and contact angle clearly indicative of the now water wet surface.

[0055] The above test was made to insure the wettability change in the well after application of the invention treatment in the porous media.

[0056] Similar results can be obtained by using various non-ionic and ionic surfactants. Suitable non-ionic surfactants include but are not limited to octilphenol having 9-16 EO, nonylphenol with an EO number from 4 to 80, preferably 20-55, fatty acids of 9-20 EO, n-tetradecanol of 9-20 EO, n-hexadecanol of 9-20 EO, laurate of sorbitan, and polyethoxilated fatty alcohols with EO number from 4 to 25, preferably 9 - 20.

[0057] Suitable ionic surfactants include but are not limited to n-alkyl sulfates of K or Na, n-alkyl trimethyl ammonium chloride and combinations thereof.

[0058] Suitable co-surfactants include but are not limited to any alcohol of the series of n-alcohols (C1 - C6), such as methanol, ethanol, propanol, butanol, pentanol, isopropanol and mixtures thereof.

[0059] The carrier fluid of the surfactant composition can be light oil, a light refinery cut, gasoil, diesel, diluent, brine,

11-194-2

produced water and water compatible with the formation fluids and the mineral in the rock. The most preferred carrier fluid is a the produced water and water compatible with the formation fluids and the mineral in the rock.

Example 3

[0060] A laboratory test was conducted for evaluating relative permeability with extraheavy crude oil and formation water and INTESURF™ 3PW0.5 solution prepared according to the invention with production water from the Cabrutica field of the Junín Division of the Orinoco River Belt Basin in Venezuela, and using a core of well E20P15 and the formation fluids of well DE 22 12 of the same field.

[0061] The core from a depth of 2212.2 feet from Cabrutica field was taken, and two samples were packed for use in a confined cell, one sample for return permeability test and the other sample for relative permeability test of extraheavy oil and formation water and extraheavy oil and INTESURF 3PW0.5 solution. The samples were cleaned, restored and aged for 16 days at the reservoir temperature of 120 F and pressure of 400 psi in a confined cell. An imbibition Amott test was performed to both samples to insure an oil wet condition of the sample before the tests. The core properties for two samples are shown in Table 1.

TABLE 1

11-194-2

COMPANY INTEVEP S.A
CORE FROM WELL E20P15 CABRUTICA FIELD VENEZUELA

Sample					Results Ø to Helio					PERMEABILITY	
	Confining pressure	Weight			Vol.	Vol	Density		Vol		
#	PSI	Total	Long	Diam	grain	Pore space	grain	Ø	Total	Air	Klink.
1A	1300	86.03	4.875	3.596	30.67	17.42	2.632	36.2	48.09	2697	2605
2B	1300	96.42	5.143	3.702	34.42	19.22	2.628	35.8	53.64	2596	2507

[0062] INTESURF 3PW0.5 solution is a mixture of 99% V/V production water from the Cabrutica field and a 0.5 V/V of nonylphenol ethoxilated with 30 ET groups, and 0.5 V/V % methanol. 1 lb/bbl of potassium acetate is added for clay control to the final admixture.

Return permeability test

[0063] Core sample 1A with an oil wet condition confirmed by the imbibition Amott test was placed in the confined cell at 1300 psi confining pressure. Thereafter extraheavy live crude oil from well DE 22 12 of Cabrutica field was displaced until a constant pressure drop was achieved. The permeability to oil (Ko) at the initial water saturation was measured and this value was taken as the reference base relative permeability to oil in the sample. Three cycles of returned permeability test were made, and previous to each cycle, 10% of the porous volume of the sample was squeezed with the INTESURF™ 3PW0.5 solution into the production end of the core sample, and the same volume allowed to be discharged from the opposite end of the core sample. A soaking time of 24 hours was allowed to each cycle before the displacement of live crude oil was restarted. The rate of flow and the pressure drop was monitored and the permeability to oil at several points of porous volume displaced

11-194-2

was measured. FIG. 9 exhibits the return permeability test results for each cycle and Table 2 the values from the test obtained.

TABLE 2

RETURN PERMEABILITY

Net confining presure 1300 psi

Reservoir temperature 120 °F

Company : INTEVEP

Well : E20 - P15

Field : Cabrutica

(Intesurf Plus)

Stimulation fluid: INTESURF 3PW 0.5

INTESURF Carrier fluid: Production water

Squeezed stimulation fluid: 10% porous volume

Sample No. 1A

Depth 2212,2 ft

Porosity 0,354 fraction

K Klinkenberg 2295 md

(Ko) K to oil 294 md

1er cycle Vol. Acum., cc	2do cycle Vol. Acum., cc	3er cycle Vol. Acum., cc.	1er cycle K to oil, md	2do cycle K to oil, md	3er cycle K to oil, md	Skin factor SF = 1-K.Ko
0,19	28,58	78,58	448	444	511	-0,737
0,35	29,61	79,08	436	437	442	-0,502
1,14	30,93	80,37	405	350	366	-0,243
2,30	32,28	81,51	369	328	318	-0,081
3,38	34,45	83,43	344	318	315	-0,069
4,93	36,48	85,30	334	317	315	-0,070
6,48	40,02	88,41	331	321	316	-0,074
9,68	44,38	92,16	322	318	318	-0,081
12,45	47,67	95,64	318	301	299	-0,017
15,60	50,97	98,39	316	292	293	0,004
16,50	54,22	101,42	311	290	278	0,054
19,50	57,39	104,21	314	287	271	0,080
22,39	60,42	106,78	306	260	276	0,063
25,36	69,24	115,14	307	254	274	0,069
28,13	77,50	123,55	304	255	252	0,143

[0064] A stimulation state was found in all cycles suggesting the cyclic stimulation of the sandstone - production end zone as a productivity improvement of the well by reducing the pressure drop and increasing the production of extraheavy oil from the well. No formation damage was observed even after a large amount relative to porous volume of live extraheavy oil was displaced on the coreplug and desorption of the surfactants of Intesurf™ , (a trade mark owned by INTEVEP S.A. used to identify the formulation of the present invention) in the porous media occurs. After restimulation with the solution of the present invention, a better condition of relative permeability to oil is achieved. It is believed that the relative permeability to oil

11-194-2

lost after a great volume of displacement of oil and after several cycles of squeezes is due to the new water saturation without Intesurf base surfactant increases in the porous media. However, it is observed that once the surfactant is available by restimulation in the porous media, a new improvement of the oil relative permeability is achieved and even reaches levels higher than earlier cycles.

[0065] A relative permeability test of extraheavy oil and formation water and extraheavy oil and INTESURF 3PW0.5 solution with production water was then conducted.

[0066] Core sample 2B was insured to have an oil wet condition by Amott imbibition test and thereafter was placed in a confined cell at confined pressure of 1300 psi. Temperature was that of the reservoir of 120° F. Extraheavy oil was displaced at a pressure of 1000 psi until a constant flow was achieved. The relative permeability effective to oil was measured at the initial water saturation. Thereafter, formation water was displaced at a constant rate of 1 cc/min and monitoring of the produced fluids and pressure drop was made until no flow of extraheavy oil is observed. The effective water permeability at the residual oil saturation is measured for each sample and the volume of extraheavy oil produced at room conditions is corrected to reservoir conditions using the viscosity and volumetric factor of the reservoir. The final saturation of the fluids is determined by material balance. The effective permeability of each phase is calculated using Darcy's Law. The relative permeability water - extraheavy oil and Intesurf solution - extraheavy oil ratios at non-stable state were calculated using the methods of Jones and Roszelle.

[0067] Once the formation water - extraheavy oil test was run, extraheavy crude was displaced for the core sample until a condition of initial water saturation and extraheavy oil saturation was achieved. In this state the permeability

11-194-2

effective to oil was measured again and displacement with the solution of INTESURF™ 3 PW0.5 took place with a rate 0.1 cc / min for 8 hours allowing a soaking time of 12 hours and so on until only solution of INTESURF™ 3 PW0.5 was collected as the production without any extraheavy oil. The final recovery of extraheavy oil was 10.02 cc which is a 52.13% of the total porous volume and 57.89% of the original extraheavy oil in place. FIG. 10 exhibits the behavior of $K_o K_w$ vs the water saturation for the two testing fluids

Example 3

[0068] Two highly deviated Orinoco River Belt wells from the Cerro Negro area were selected for pilot testing. Main characteristics of the wells are:

Well name	Reservoir name	Completion Date	Rock properties				Production Method	Original pressure psi	Actual pressure psi	Lithology
			Porosity %	K Darcy	Vsh	Thickness ft				
CD 36	OFIM CNX9	04/1992	33	2.3	5.3	194	Mechanical pump & Gravel pack	1100	1095	sandstone
CD 37	OFIM CNX9	02/1993	32	5	7.0	192	PCP Gravel pack	1350	1000	sandstone

[0069] An amount of 270 barrels of diluent, which is a light crude oil of 23 API gravity, was admixed with a previously homogenized mix of 1.3 barrels of tridecanol alcohol of 17 EO groups and 1.3 barrels of methanol in a tank of a pumping truck. The admixture was recirculated in the tank for homogenization and pumped to well CD 36 through the annular space between the tubing and the casing. The stimulation fluid of the present invention contacted the gravel pack downhole and passed to about two feet penetration in the formation. The well was closed for a soaking period of 24 hours. The well was restarted thereafter and showed an increased production of about 200 bpd that has been stable for a period of 60 days.

[0070] Another amount of 133 barrels of diluent, a light crude oil of 23 API gravity was admixed with a previously

11-194-2

homogenized mix of 0.7 barrels of tridecanol alcohol of 12 EO groups and 0.7 barrels of methanol in a tank of a pumping truck. The admixture was recirculated in the tank for homogenization and pumped to well CD 37 through the annular space between the tubing and the casing. The stimulation fluid of the present invention contacted the gravel pack downhole and passed to about two inches of penetration in the formation. The well was closed for a soaking period of 24 hours. The well was restarted thereafter and showed a production of 80 barrels net of oil per day and has been stable for a period of 60 days thereafter. The net oil production before the stimulation was 24 barrels of net oil.

EXAMPLE 4

[0071] The VB 19 well from the Petrocedeño joint venture of The Bolivarianan Republic of Venezuela PDVSA oil company in the Orinoco River Belt Junín Division was a candidate for a pump service. The well underwent a service job and INTESURF fluid according to the invention was used as a control and stimulation fluid, using the formulation and method of the present invention.

[0072] Crude oil and formation water from the VB 19 well have the following characteristics:

OIL:

Saturated % : 8 wt

Aromatics % : 44 wt

Resins %: 35 wt

Asphaltenes % : 13 wt

Acidity: 3.90 mg KOH/g

Viscosity CP 10,420 at 145 F

11-194-2

API: 9
% C wt 84.55
% H wt 11.12

Formation Water with 2,500 ppm NaCl

[0073] The service job in well VB 19 was prepared and the working control fluid was used to fill the annular space between the casing and the tubing, and the tubing. The well was closed at the wellhead and 80 barrels of the formulation was squeezed to the formation from the wellhead. Thereafter the rig worked taking out the tubing to surface and replaced the BCP pump for a new one, making another trip back to locate said pump downhole. Thereafter, the wellhead equipment and instrumentation of the well was replaced. The time elapsed for the whole service job was about 20 hours. This time was taken as the soaking time for the stimulation of the sand formation with the formulation of the present invention.

[0074] The total amount of fluid used during the whole job was 350 barrels and was prepared with clean, filtered potable water, 3.5 barrels of ethoxylated tridecanol of 17 ethoxylated oxide groups, 3.5 barrels of methanol and 343 barrels of water. Production increase was from a mean value before treatment of 183 bopd to a mean of 445 bopd after the treatment and the average intake pump pressure of the progressive cavity pump before treatment was around 5.74 bar (116 psi at 350 rpm) and after the treatment the average intake pump pressure of the progressive cavity pump increased to 13.74 bars (199 psi at 350 rpm).

[0075] Table 3 shows the VB 19 well reservoir and well parameters and FIG. 12 illustrates conditions before and after treatment monitored in the well as explained.

11-194-2

Table 3

WELL	VB-19
Geometry	HORIZONTAL
Field	Petrocedeno - Venezuela
Estación	San Diego
Sand / Reservoir	D2/D3/ OFII BSDZ0002
Slotted liner interval	2050'-6100'
Sand Thickness	30
Permeability, mD	16000
Porosity, %	28
Temperature, °F	120
Fecha completación original	09/02/2007
Actual reservoir pressure, psia	510

[0076] FIG. 13 illustrates the reported monitored downhole parameters in well VD 18 of Petrocedeno field in the San Diego de Cabrutica Principal Station Venezuela. In this well, of almost same characteristics of the VB19 well, the control working and stimulation fluid of the present invention was used, following the same procedure and composition as mentioned before for well VB19.

[0077] These pilot tests establish that the stimulation fluid, or formulation, of the present invention is highly effective at improving hydrocarbon flow and production through porous media treated with fluid. The fluid is made from readily available constituents, and the method can be carried out using known equipment already available for injecting other well stimulation fluids. Further, the method of the invention can be carried out during other well servicing, thereby gaining benefit of treatment according to the invention without substantial additional down time.

[0078] Based upon the foregoing, a beneficial change in permeability and production levels is demonstrated by using the formulation and method of the present invention.

11-194-2

[0079] It is to be understood that the invention is not limited to the illustrations described and shown herein, which are deemed to be merely illustrative of the best modes of carrying out the invention, and which are susceptible of modification of form, size, arrangement of parts and details of operation. The invention rather is intended to encompass all such modifications which are within its spirit and scope as defined by the claims.

11-194-2

We Claim:

1. A method for improving flow conditions in a porous media while servicing a well penetrating to the porous media, comprising the steps of:

stopping drilling or production activities on the well;

introducing a well control fluid into the well and the porous media, the well control fluid comprising a mixture of a surfactant, a co-surfactant and a carrier fluid;

holding the well control fluid in the well and the porous media in the presence of water while the well is being serviced, such that the fluid penetrates the porous media and forms a water film on surfaces of the porous media; and

when well servicing is finished, resuming drilling or production activities on the well.

2. The method of claim 1, wherein the surfaces of the porous media prior to treatment with the mixture have hydrocarbons adhered to them, and wherein the water film is formed over the surfaces and the hydrocarbon adhered to the surfaces.

3. The method of claim 1, wherein the porous media is a subterranean hydrocarbon bearing formation containing asphaltene and wherein the asphaltene is adhered to the surfaces of the porous media.

4. The method of claim 3, wherein the hydrocarbon has an API gravity of between 6 and 16.

5. The method of claim 3, wherein the hydrocarbon has an API gravity of between 6 and 12.

11-194+2

6. The method of claim 1, wherein the surfactant is selected from the group consisting of cationic surfactants, nonionic surfactants, amphoteric surfactants and combinations thereof.
7. The method of claim 1, wherein the co-surfactant is an alcohol co-surfactant.
8. The method of claim 7, wherein the alcohol co-surfactant is selected from the group consisting of methanol, ethanol, propanol, butanol, pentanol, isopropanol, and combinations thereof.
9. The method of claim 1, wherein the carrier fluid is selected from the group consisting of organic solvents, light hydrocarbons, diluents, light crude oil, and combinations thereof, water, production water and brine.
10. The method of claim 1, wherein the carrier fluid is a light crude oil with an API gravity between 20 to 25.
11. The method of claim 1, wherein the surfactant is an ethoxylated nonyl phenol having between 4 and 60 ethoxylated groups, and wherein the co-surfactant is ethanol.
12. The method of claim 11, wherein the mixture contains substantially equal amounts by volume of surfactant and co-surfactant.
13. The method of claim 11, wherein the mixture contains each of the surfactant and the co-surfactant at a concentration of between 0.5 and 5% wt.

11-194-2

14. The method of claim 11, wherein the mixture contains each of the surfactant and the co-surfactant at a concentration of between 1 and 4% wt.

15. The method of claim 1, wherein the surfaces of the porous media define pore space for the hydrocarbon, and wherein the surfaces are defined by a material selected from the group consisting of quartz, feldspar, siliceous mineral, carbonaceous mineral, clays, and combinations thereof.

11-194-2

ABSTRACT

A method for improving flow conditions in a porous media while servicing a well penetrating to the porous media includes the steps of: stopping drilling or production activities on the well; introducing a well control fluid into the well and the porous media, the well control fluid comprising a mixture of a surfactant, a co-surfactant and a carrier fluid; holding the well control fluid in the well and the porous media in the presence of water while the well is being serviced, such that the fluid penetrates the porous media and forms a water film on surfaces of the porous media; and when well servicing is finished, resuming drilling or production activities on the well.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS
---------------------------	--

As the below named inventor(s), I/we declare that:

This declaration is directed to: ☒ The attached application, or
☐ United States application or PCT international application number _____
filed on _____
☐ As amended on _____ (if applicable);

I/we believe that I/we am/are the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought;



I/we have reviewed and understand the contents of the above-identified application, including the claims, as amended by any amendment specifically referred to above;

I/we acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me/us to be material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT International filing date of the continuation-in-part application.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

All statements made herein of my/our own knowledge are true, all statements made herein on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME OF INVENTOR(S)	
Inventor one: <u>Pablo Manrique</u>	Date: <u>04-09-2012</u>
Signature: <u></u>	Citizen of: <u>VE</u>
Inventor two: <u>Franklin Archer</u>	Date: <u>04-13-2012</u>
Signature: <u></u>	Citizen of: <u>VE</u>
☐ Additional inventors or a legal representative are being named on _____ additional form(s) attached hereto.	

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.
If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS
---------------------------	--

As the below named inventor(s), I/we declare that:

This declaration is directed to: ☐ The attached application, or ☐ United States application or PCT international application number _____ filed on _____ ☐ As amended on _____ (if applicable);

I/we believe that I/we am/are the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought;

I/we have reviewed and understand the contents of the above-identified application, including the claims, as amended by any amendment specifically referred to above;

I/we acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me/us to be material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT International filing date of the continuation-in-part application.

WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

All statements made herein of my/our own knowledge are true, all statements made herein on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME OF INVENTOR(S)

Inventor one: Maria Gracia Araujo Date: 04-17-2012
Signature: *Maria Gracia Araujo* Citizen of: VE

Inventor two: Deivis Suarez Date: 04-03-2012
Signature: *Deivis Suarez* Citizen of: VE

☐ Additional inventors or a legal representative are being named on _____ additional form(s) attached hereto.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

FIG. 7

FIG. 8

FIG. 9

RETURN PERMEABILITY
Net confining pressure 1300 psi
Reservoir temperature 120 °F
Sample No. : 1A





FIG. 10

Relative permeability (Formation water & INTESURF™ 3PW0.5





Contact angle measurement before	Photograph	Contact angle measurement after INTESURF™	Photograph
137.5°		45.5°	

FIG. 11





FIG. 12



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194-2
		Application Number	
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	---

Applicant Information:

Applicant 1					Remove
Applicant Authority ☒ Inventor		☐ Legal Representative under 35 U.S.C. 117		☐ Party of Interest under 35 U.S.C. 118	
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Pablo		Manrique		
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service					
City	Caracas	Country Of Residence ⁱ	VE		
Citizenship under 37 CFR 1.41(b) ⁱ		VE			
Mailing Address of Applicant:					
Address 1		Edificio Caroata Apartamento 10C, Parque Central			
Address 2					
City	Caracas	State/Province			
Postal Code		Country ⁱ	VE		
Applicant 2					Remove
Applicant Authority ☒ Inventor		☐ Legal Representative under 35 U.S.C. 117		☐ Party of Interest under 35 U.S.C. 118	
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Franklin		Archer		
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service					
City	Caracas	Country Of Residence ⁱ	VE		
Citizenship under 37 CFR 1.41(b) ⁱ		VE			
Mailing Address of Applicant:					
Address 1		Edificio Lagunillas Apto. 9C2, El Valle			
Address 2					
City	Caracas	State/Province			
Postal Code	1090	Country ⁱ	VE		
Applicant 3					Remove
Applicant Authority ☒ Inventor		☐ Legal Representative under 35 U.S.C. 117		☐ Party of Interest under 35 U.S.C. 118	
Prefix	Given Name	Middle Name	Family Name	Suffix	
	Maria	Gracia	Araujo		
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service					
City	Barinas	Country Of Residence ⁱ	VE		

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194-2
		Application Number	
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		

Citizenship under 37 CFR 1.41(b) i		VE	
Mailing Address of Applicant:			
Address 1		Urb. Raul Leoni, Sector 5 Vereda 23, Casa Nro. 11	
Address 2			
City	Barinas	State/Province	
Postal Code	5201	Country	VE
Applicant 4			Remove
Applicant Authority ☒ Inventor		☐ Legal Representative under 35 U.S.C. 117	
		☐ Party of Interest under 35 U.S.C. 118	
Prefix	Given Name	Middle Name	Family Name
	Deivis		Suarez
Residence Information (Select One) ☐ US Residency ☒ Non US Residency ☐ Active US Military Service			
City		Country Of Residence i	VE
Citizenship under 37 CFR 1.41(b) i		VE	
Mailing Address of Applicant:			
Address 1		Sector San Isidro, Municipio Simon Rodriguez,	
Address 2		San Simon	
City	Estado Tachira	State/Province	
Postal Code	5038	Country	VE
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button.			Add

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).	
☐ An Address is being provided for the correspondence information of this application.	
Customer Number	34704
Email Address	docket@bachlap.com
Add Email Remove Email	

Application Information:

Title of the Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		
Attorney Docket Number	11-194-2	Small Entity Status Claimed ☐	
Application Type	Nonprovisional		
Subject Matter	Utility		
Suggested Class (if any)		Sub Class (if any)	
Suggested Technology Center (if any)			
Total Number of Drawing Sheets (if any)	9	Suggested Figure for Publication (if any)	

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194-2
		Application Number	
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		

Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)

☐ **Request Not to Publish.** I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application **has not and will not** be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Enter either Customer Number or complete the Representative Name section below. If both sections are completed the Customer Number will be used for the Representative Information during processing.

Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)
Customer Number	34704		

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78(a)(2) or CFR 1.78(a)(4), and need not otherwise be made part of the specification.

Prior Application Status	Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)
	Continuation in part of	12973022	2011-12-20
Prior Application Status	Expired	Remove	
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)
	non provisional of	61549534	2011-10-20

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the Add button.
 Add

Foreign Priority Information:

This section allows for the applicant to claim benefit of foreign priority and to identify any prior foreign application for which priority is not claimed. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55(a).

Remove			
Application Number	Country i	Parent Filing Date (YYYY-MM-DD)	Priority Claimed
			☐ Yes ☐ No

Additional Foreign Priority Data may be generated within this form by selecting the Add button.
 Add

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	11-194-2
		Application Number	
Title of Invention	WORKING/CONTROL FLUID FOR HEAVY AND EXTRA-HEAVY CRUDE WELLS		

Assignee Information:

Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office.			
Assignee 1			Remove
If the Assignee is an Organization check here. ☒			
Organization Name	Intevep, S.A.		
Mailing Address Information:			
Address 1	Apartado 76343		
Address 2			
City	Caracas	State/Province	
Country	VE	Postal Code	1070A
Phone Number		Fax Number	
Email Address			
Additional Assignee Data may be generated within this form by selecting the Add button. Add			

Signature:

A signature of the applicant or representative is required in accordance with 37 CFR 1.33 and 10.18. Please see 37 CFR 1.4(d) for the form of the signature.					
Signature	/George A. Coury/			Date (YYYY-MM-DD)	2012-06-21
First Name	George A.	Last Name	Coury	Registration Number	34309

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

91

TRADUCCIÓN DEL INGLÉS AL ESPAÑOL del documento de prioridad relacionado con la solicitud de Patente de los Estados Unidos No. 13/529,140 titulada:

FLUIDO DE TRABAJO/CONTROL PARA POZOS DE CRUDO PESADO Y EXTRA PESADO

ANEXOS. La solicitud de Patente de los Estados Unidos No. 13/529,140 arriba mencionada y Certificación del Comisionado de Patentes y Marcas de los Estados Unidos.

LOS ESTADOS UNIDOS DE AMÉRICA
A TODO AQUEL QUE PUEDA LLEGARLE LA PRESENTE:

DEPARTAMENTO DE COMERCIO DE ESTADOS UNIDOS
Oficina de Marcas y Patentes de Estados Unidos

16 de enero de 2013

LA PRESENTE CERTIFICA QUE EL ANEXO ES UNA COPIA VERDADERA TOMADA DE LOS ARCHIVOS DE LA OFICINA DE MARCAS Y PATENTES DE LOS ESTADOS UNIDOS DE LOS DOCUMENTOS DE LA SOLICITUD DE PATENTE IDENTIFICADA ABAJO LA CUAL CUMPLIÓ CON LOS REQUERIMIENTOS PARA OTORGÁRSELE UNA FECHA DE PRESENTACIÓN BAJO EL 35 USC 111.

SOLICITUD NÚMERO: 13/529,140
FECHA DE PRESENTACIÓN: *Junio 21, 2012*

EL CÓDIGO DEL PAÍS Y EL NÚMERO DE SU SOLICITUD PRIORITARIA A SER UTILIZADO PARA PRESENTACIÓN EN EL EXTRANJERO BAJO LA CONVENCION DE PARÍS ES *US13/529,140*.

Por autoridad del
Subsecretario de Comercio para la Propiedad Intelectual
y Director de la Oficina de Marcas y Patente de Estados Unidos

(firma)

N. WILLIAMS
Funcionario que Certifica

Hay un sello que dice:
OFICINA DE MARCAS Y PATENTE DE ESTADOS UNIDOS
DEPARTAMENTO DE COMERCIO

REIVINDICACIONES

1. Un método para mejorar las condiciones de flujo en un medio poroso mientras se rehabilita un pozo que penetra al medio poroso, que comprende las etapas de:

detener la perforación o actividades de producción del pozo;

introducir un fluido de control de pozo en el pozo y el medio poroso, el fluido de control de pozo comprende una mezcla de un tensoactivo, un co-tensoactivo y un fluido portador;

mantener el fluido de control de pozo en el pozo y el medio poroso en la presencia de agua aunque el pozo este siendo rehabilitado, de tal manera que el fluido penetra el medio poroso y forma una película de agua sobre las superficies del medio poroso; y

cuando la rehabilitación del pozo termina, se resumen el perforado o las actividades de producción en el pozo.

2. El método de la reivindicación 1, en donde las superficies del medio poroso antes del tratamiento con la mezcla tiene hidrocarburos adheridos a ellos, y en donde la película de agua se forma sobre las superficies y el hidrocarburo adherido a las superficies.

3. El método de la reivindicación 1, en donde el medio poroso es una formación que posee hidrocarburo subterráneo que contiene asfalto y en donde el asfalto se adhiere a la superficie del medio poroso.

4. El método de la reivindicación 3, en donde el hidrocarburo tiene una gravedad API de entre 6 y 16.

5. El método de la reivindicación 3 en donde el hidrocarburo tiene una gravedad API de entre 6 y 12.

6. El método de la reivindicación 1, en donde el tensoactivo se selecciona del grupo que consiste de tensoactivo catiónico, tensoactivos no iónicos, tensoactivos anfotéricos y combinaciones de los mismos.

7. El método de la reivindicación 1, en donde el co-tensoactivo es un co-tensoactivo de alcohol.

8. El método de la reivindicación 7, en donde el co-tensioactivo de alcohol se selecciona del grupo que consiste de metanol, etanol, propanol, butanol, pentanol, isopropanol, y combinaciones de los mismos.
9. El método de la reivindicación 1, en donde el fluido portador se selecciona del grupo que consiste de disolventes orgánicos, hidrocarburos ligeros, diluyentes, petróleo crudo ligero, y combinaciones de los mismos, agua, agua de producción, y solución salina.
10. El método de la reivindicación 1, en donde el fluido portador es un petróleo crudo ligero con una gravedad API entre 20 a 25.
11. El método de la reivindicación 1, en donde el tensioactivo es un nonil fenol etoxilado que tiene entre 4 y 60 grupos etoxilados, y en donde el co-tensioactivo es etanol.
12. El método de la reivindicación 11, en donde la mezcla contiene cantidades sustancialmente iguales en volumen del tensioactivo y el co-tensioactivo.
13. El método de la reivindicación 11, en donde la mezcla contiene cada uno del tensioactivo y el co-tensioactivo a una concentración de entre 0,5 y 5% en peso.
14. El método de la reivindicación 11, en donde la mezcla contiene cada uno del tensioactivo y el co-tensioactivo a una concentración de entre 1 al 4% en peso.
15. El método de la reivindicación 1, en donde las superficies del medio poroso definen el espacio de poro para el hidrocarburo, y en donde las superficies se definen mediante un material seleccionado del grupo que consiste de cuarzo, feldespato, mineral silíceo, mineral carbonáceo, arcilla, y combinaciones de los mismos.