

julian

Search history

Search 1: TAC=(dust and collector and housing and filter*) (Results 1369)

Search 2: TAC=(dust and collector and housing and filter* and door and clip*) (Results 5)

Title: Vacuum cleaner

Abstract: Source: US1763397A 1. At the opposite side of this casting may be formed a sunilar compartment or kit for containing ordinary tools or other supplies. Suppo/rtifn,g mul p1-apeZ .iiv,g means V One of the important objects of the invention is to provide means whereby the machine may be propelled over the **door** by the same motor which operates the pump, in order to li hten the work of the operator. To this end, I provide the shaft 113, at a point within the gear box 52-54, with a worm 112, and _arranged to mesh with this worm is a. worm wheel 113, secured to a short shaft 114. This is s journaled in suitable bearings 115, one on each side of the worm wheel 113, (see Fig. Qg. Each end of the shaft 114 projects into t e **housing** of a differential mechanism 116. Each of .these housin s is I formed of two halves or sections helm? to~ gether bly screws 116ss (see Fig. 15) and to the end of t e shaft 114 is secured a beveled gear 117. A similar beveled gear 118 is also mounted within the housin 116, and rigid with each gear 118, is a shag; 121, extending out through the side walls of the casting Planet gears 119 mesh with the two gears 117 and 118 and are carried on stub shafts 120, journaled in the **housing** 116. Secured' to one of the shafts 121 is a beveled"pinion 122, which meshes with the beveled gear 79, which rotates the **dust collector** or Hlter, as above described. ' Wvith the parts so far described, it is obvious that as the worm wheel 113 is driven, the two differential **housings** 116 will idly rotate and no power will be transmitted to the shafts 121. Means for locking the **housings** against rotation are, -however, provided. This comprises a sleeve 123, journaled on one of the shafts 121, and secured at its inner end to an arm 124. This is attached b means of a pin and slot connection to the gee end of an arm or lever 125, secured to a rock shaft 126, journaled in the side walls 54 of the gear box, and carrying a pair of short arms 127, spaced apart a distance corresponding with t at between the two differential **housings** 116. Pivotally connected with each arm 127 is a sliding bolt 128, the lower end of which is adapted to engage in notches 129, formed on the periphery of the differential **housings**. Secured to the outer endof the sleeve 123 is a lever arm 130, connected by a link 131, to the lower end of a control lever 132, pivotally mounted' at the rear end of the machine within easy reach of the operator. It is therefore obvious that by manipulating the lever 132, the differential **housings** 116 ma be locked against rotation when desiredi and that when so locked, power will be trans~ mitted' from the worm wheel 113 to the shafts 121. In other words, the mechanism just described serves the double function of a clutch and differential. ' _ Secured to the outer ends of each shaft 121 is a pinion 133, which meshes with a large gear 134, journaled on the hub 6ss of the wheel 6. The gear 134 is locked to the wheel 6 by means of set screws 135, carried by the wheel 6 and engaging lugs on the gear. These screws are, of course, in engagement with the lugs when the machine is being propelled by power, but they may be disengaged when it is desired to propel the machine by hand, as when transporting it from place to place. In this way, the operator is relieved from the frictional drag which would otherwise result from the engagement of the earing. To support the front end og the machine, I provide u. pair of relatively small wheels 136, and in order to adjust the ' height of the cleaning nozzle 80 relative to the carpet it' is necessary that these wheels be made adjustable. I accomplish this by mounting the wheels 16 on cranks 137 (see Fig. 8) caiftied at the ends of a crank shaft 138, extending under the machine. To one end of this crank shaft is secured a worm wheel 139, which meshes with a worm 140 (see Fig. 4) carried at the lower end of a vertical shaft 141, jour- ' naled in brackets 142, and rovided at its upper_end_With a hand wheel)1-43, by means 0 which it may be turned. Thrust collars 141ss are secured to the shaft 141 adjacent the bearings 142 to prevent endwise movement TB so an os lou no B5 ' 1,763,397 'Z' thereof, and when this shaft is turned, it will be obvious that the crank shaft 138- is correspondingly rocked in its bearings and that, owing to the cranks 137, the front end of the machine and the nozzle will be accordingly raised or lowered. ' In order to supply current to the motor, and at the same time permit the machine to operate at any desired distance from an electric receptacle or socket without danger of the cord becoming damaged or tangled, I equip the nmchxie with a reel for holding the conductor cord. The cord itself containing the usual two conductors is indicated at 144 and is provided at its end withthe usual plug 145. The cord is preferably led through a guide 146, so as to insure its winding properly on the reel. The reel itself preferably comprises e pair of spaced discs M 1, having ai central hub 1117ss (see Fig. 125) into the interior of which, throu _Ph an insulating bushing 1fl'i",, the inner end og the conductor cord is led. The reel is provided with si cntrail journal box or sleeve 149, which turns freely upon a spindle consisting of o bolt 14:23, set vevically into the top of the costing; 3, so that the reel itself is horizontal. 'll' he inner ends of the electrical conductors contained in the cord are soldered or other~ Wise secured to s, jpoir of concentric conduct-> ing sleeves or rings 150 and 151, insulated from the journal box 149 and from each other by insulating bushings 152, the inner sleeve 150 preferably being longer than the outer fini. These sleeves, of course, turn with the ree _ ' In order to establish electrical connection with the sleeves 150, 151,,1 provide e pair of brushes 154, 155, each in the nature of a split rin wda ted to embrace its res ective sleeve ga P _ _ _ ' P _> 'as shown in Fig. 17. These brushes or s lit rings are carried byslmnks 156, supportedby a block of insulation 157, mounted on a suitable bra,cke,t)159,a,nd az cover or **housing** 15Sof insulating material fits over and encloses all of the metallic current carrying parts above described, so as to avoid the possibility of shock or short circuit. ' From the shanks 156 of the contact brushes extend suitable conductors, (not shown) through a switch 160, and through the usual rheostat or starting box 161 to the motor 9. Upemtiow. It will, of course, be understood that when suction hose attached to the pipe 96, is being employed, the valve 83 at the cleaning nozzle is closed, so as to create a partial vacuum in the **dust collector** chamber. » Furthermore, since the cleaning nozzle 50 is held in position by lugs or screws 84 and 87, (see Figs. 1 and 41, it can he readily detached smd removed W en not in use, the nipples 82 and 89 slipping readily out of their respective pipe connections. When this cleaning nozzle is removed. a hose may be connected to the opening in the dirt pan in which thenipple 82 formerly stted. Thus, I have provided means for connectingahosctoeither the front or rear or both of the machines, as may be desired. Although the brushes 71 will effectively prevent undue accumulation of **dust** upon the porous walls of the **filter** or **dust collector**, as the latter is rotated, it may be sometimes desirable to blow air back through the **dust** collectorin a direction reverse to that of the normal flow, To accomplish this, it is only necessary to manipulate the hand Wheel so as to swing the disc 25 to the opposite side of the perpendicular hom that shown in Fig. 6. 'When this is done, air is delivered from the cylinders 520,-through the ports and 47, and conduit 60 into the interior of the **dust collector**, thus blowing through the porous walls and serving to clean and dis~ lddge the **dust** from 'theouter surface thereof _ ' It will be observed that the **dust** collector is rotated continuously so long as the machine is being propelled over the iioor, and that by disconnecting the screws 135 from the gear Wheels 134, the **dust collector** may be csused to rotate oven when the machine is standing still. , ' What ll claiin is :- 1. A vacuum cleaner comprising an elongated body, e motor ot one end of said body, il, suction nozzle at the other end thereof, e **dust collector** adjacent said nozzle, a. horizontal motor-driven shaft extending longitudinally of said body, pump mechanism located adjacent the motor and driven by said shaft, supporting wheels and gearing driven by said shaft for propelling the cleaner over the iioor, said gearing being located between said **dust collector** and pumping' mechanism. Q. lin a Vacuum cleaner, the combination with a casing having a closed chamber, a suction pr-odiicing means within said casing, 21. **dust collector** located between said chamber and said suction producing means, in suction nozzle communicating directly with said chamber and mounted at one end of the casing, and means ot the other end of said casing for connecting sz, suction hose iilso with said chamber. 3. In a vacuum cleaner, the combination with an elongated casing, of pumping means and a **dust** separator therein, a removable dirt pant arranged below said separator, a cleaning nozzle detachably connected with the forward end of said dirt pan to deliver into the same, in Valve in said nozzle, zinda suction hose adapted to be connected through the rear end portion of said casing with the spate shove said dirt an. ' In testimony whereoi} I afliic si nature

Classifications:

International (IPC 8-9): A47L5/14 A47L5/20 (Advanced/Invention);


A47L5/12 (Core/Invention)

International (IPC 1-7): A47L5/30

CPC: A47L5/14 A47L5/20

European: A47L5/14 A47L5/20

US: 15/323 15/334 15/346 15/352 15/383 55/290 92/12.2 92/172



Family:

Publication number	Publication date	Application number	Application date
US1763397 A	19300610	US19240717494	19240603

Priority:

US19240717494 19240603

Probable Assignee: JOB HUTCHINSON

Assignee(s): (std): JOB HUTCHINSON

Inventor(s): (std): JOB HUTCHINSON

Inventor(s): HUTCHINSON JOB

Title: Floor mounted **dust** mop cleaning device

Abstract: Source: US3122772A 1. A **dust** mop cleaning device comprising a **housing**, having side walls, a bottom and a top, and an interior wall dividing the interior of the **housing** into a suction section and an exhaust section, said interior wall having an opening through which air may be driven from said suction section to said exhaust section; a suction unit comprising an impeller, an impeller case, an electric motor and a mounting flange all positioned within the suction section of the **housing** and the mounting flange being secured to and mounted on said interior wall, and all being mounted on and secured to said interior wall by said mounting flange so that said flange surrounds said opening in the interior wall and so that air exhausted from ^0 said suction unit is driven through the opening in the interior wall; a **dust collector** bag unit positioned within the exhaust section consisting of a **dust collector** bag adapter surrounding the opening in the interior wall 2^ and provided with a groove, a **dust collector** bag made of air pervious material and having its open end embracing said **dust collector** bag adapter, and a rubber ring fitting over the **dust collector** bag and cooperating with the groove in the **dust collector** bag ^0 adapter to hold the **dust collector** bag in position to receive **dust** laden air through said opening from said suction unit; the portion of the **housing** top above the exhaust section being provided with a hinged **door** whereby the **door** can be opened on its hinges exposing the **dust collector** bag and permitting the same to be removed for cleaning, disposal and replacement; the portion of the **housing** top of the **dust** mop cleaning device above the suction section being formed ss degrees with slots which permit **dust** laden air to travel into the suction unit; the walls of the exhaust section being formed with venting holes through which **filtered** air escaping through the minute openings in the **dust collector** 4ss_gt; bag may escape from the exhaust section of the **housing**; a conically shaped disc fastened to the suction unit above the air inlet opening in the suction unit and just below the suction slots to protect the impeller 5" fan within the suction unit from damage in the event a solid object drops into the device; and means comprising top mounting **clips** and screws therefor for mounting the unit on the subfloor of a **house** in a properly shaped opening in the floor so 5^ that the entire mechanism contained in the **housing** is located below the floor surface and so that the upper surface of the top of said unit is substantially at the same level as the adjoining floor surface.

Classifications:


International (IPC 8-9): A47L13/502 (Advanced/Invention);
A47L13/10 (Core/Invention)

International (IPC 1-7): A47L13/502

CPC: A47L13/502

European: A47L13/502

US: 15/301 15/310



Family:

Publication number	Publication date	Application number	Application date
US3122772 A	19640303	US19610142163	19611002

Priority:

US19610142163 19611002

Probable Assignee: LIPSON SANFORD W

Assignee(s): (std): LIPSON SANFORD W

Inventor(s): (std): LIPSON SANFORD W

Title: HEAT ENERGY RECAPTURE AND RECYCLE AND ITS NEW APPLICATIONS

Abstract: Source: US2005120715A What has been created is a plurality and a variety of processes and a variety of devices correspondingly supportive to each process, wherein, a new partnership between; (1) a heat absorbing radiator compressed air pipes/tubes and (2) a gas turbine engine or a reciprocating piston engine,-is used to recapture and convert the, otherwise wasted, heat energies expelled by engines, by factories, by smelting plants, by distillation plants, by chillers/coolers/freezers, by cooking ovens, by lamps/stoves, by trash burners, and the heat energies created by the solar heat on the desert/ocean water,-into electric power and finally into hydrogen-deuterium fuel,-by having the engine's tailpipes submerged in cold compressed air inside the heat absorbing radiator pipes in reverse air flow, to further drive and re-drive the same engine; wherein, in order to capture fusion heat energy the hydrogen bomb is detonated in the deep ocean to catch the flames by the water and the hot water is used to energize the compressed air inside the heat absorbing radiator pipes; wherein, in order to produce fusion energy, an abundant electric arc is passed across liquid deuterium or across gaseous deuterium by the electro-plasma torch and sparkplug in the internal combustion engine, and by detonating a dynamite inside a liquid deuterium; wherein diamond is produced by placing carbon inside the hydrogen bomb; and wherein, deuterium fusion glass is used first in smelting glass to large sizes before running an engine.

Classifications:

International (IPC 8-9): B01D61/10 B63B1/10 B63B1/12 B63B35/00 B63B35/44 B63B39/06 B63B43/06 B63G1/00 B63G8/30 B63H19/02 B63H9/06 B63H9/10 B63J3/00 B64C31/04 B64C31/06 E02B3/06 F01K13/00 F01K23/10 F01K27/00 F02C1/00 F02C1/05 F02G5/00 F03B13/18 F03D11/04 F03D5/00 F03D5/04 F03G7/00 F24F5/00 F24F6/14 F28D5/00 (Advanced/Invention); B63B1/24 B63J1/00 F24F1/00 (Advanced/Non-invention); B01D61/02 B63B1/00 B63B35/00 B63B35/44 B63B43/00 B63H9/00 B63J3/00 E02B3/06 F01K23/10 F01K27/00 F02C1/00 F02G5/00 F03B13/00 F03D5/00 F03G7/00 (Core/Invention)

International (IPC 1-7): B01D61/10 B63B17/00 B63B35/00 B63B7/00 F01K23/10 F03D5/02 F03D5/04 F03G7/00 F04B35/00 F24F6/14 F28D5/00

CPG: F05B2210/18 B63H9/06 B63H9/1021 F05D2260/212 F01K27/00 F02C1/05 F03G7/00 Y02T50/672 Y02T50/676 B63B1/121 Y02W10/33 Y02W10/37 B63B1/107 B63B1/24 B63B39/06 B63B2039/067 B63G1/00 B63G8/30 B63H19/02 B63J1/00 C02F1/04 F05B2240/40 Y02T70/59 F03D11/04 B01D61/10 B63B35/00 B63B35/44 B63B43/06 B63B2035/446 B63B2035/4466 B63J3/00 B64C31/04 B64C31/06 E02B3/062 E02B2017/0091 F03B13/182 F03D5/00 F03D5/04 F05B2240/921 F05B2240/922 F24F5/0035 F24F6/14 F24F2001/0088 F28D5/00 Y02B10/30 Y02B10/50 Y02B30/545 Y02E10/38 Y02E10/70 Y02E10/728

European: B01D61/10 B63B1/10C B63B1/12B B63B35/00 B63B35/44 B63B39/06 B63B43/06 B63G1/00 B63G8/30 B63H19/02 B63H9/06 B63H9/10 B63H9/10C B63J3/00 B64C31/04 B64C31/06 E02B3/06B F01K27/00 F02C1/05 F03B13/18B2D F03D11/04 F03D5/00 F03D5/04 F03G7/00 F24F5/00C7 F24F6/14 F28D5/00 L63B1/24 L63B35/44 L63B35/44E9 L63B39/06R L63B43/06 L63H9/10 L63J1/00 L63J3/00 M02F1/04 P02B17/00M R05B210/18 R05B240/40 R05B240/921 R05B240/922 R05B240/931 R05B260/212 R24F1/00G1 Y02B10/30 Y02B10/50 Y02B30/14 Y02B30/54D Y02E10/38 Y02E10/70 Y02E10/72L Y02E10/72N Y02E20/18 Y02T50/67B2 Y02T50/67F2 Y02T70/59

US: 114/267 114/382 114/39.1 114/39.2 114/39.26 114/39.29 114/39.31 210/136 210/170 210/259 210/321.87 244/153.00R 244/153R 244/24 405/76 415/5 416/8 417/330 417/332 60/39.01 60/506 60/618 60/618P 60/676 60/698 60/698P 60/772 62/304 62/310 62/314 62/340

Family:

Publication number	Publication date	Application number	Application date
AP200704109 A0	20070831	AP20070004109	20050727
AU2005325208 AA	20060727	AU20050325208	20050727
AU2005325208 BB	20120329	AU20050325208	20050727
CA2397847 AA	20040212	CA20022397847	20020812
CA2404410 AA	20040320	CA20022404410	20020920
CA2599414 AA	20070823	CA20052599414	20050727
CN101146981 A	20080319	CN200580049207	20050727
EA200701538 A1	20081030	EA20070001538	20050727
EP1851418 A1	20071107	EP20050779535	20050727
EP1851418 A4	20090513	EP20050779535	20050727
IN05612DN2007 A	20070831	IN2007DN05612	20070719
US2005120715 AA	20050609	US20050039624	20050120
US2008155985 AA	20080703	US20050795835	20050727
US4756666 A	19880712	US19840631321	19840719
US4859146 A	19890822	US19880177599	19880405
US5027735 A	19910702	US19900472753	19900131
US5052902 A	19911001	US19860820082	19860121
US5056447 A	19911015	US19880255657	19881013
US5094595 A	19920310	US19890376002	19890815
US5435259 A	19950725	US19930097655	19930727
US5507943 A	19960416	US19910811470	19911218
US6293121 BA	20010925	US19980137499	19980820
US6327994 BA	20011211	US19970999729	19971223
US8051637 BB	20111108	US20050795835	20050727
WO06078315 A1	20060727	WO2005US26793	20050727
WO06078315 C1	20061102	WO2005US26793	20050727

Priority:

US19840631321 19840719	US19840631322 19840719	US19860820082 19860121
US19880255719 19881013	US19900472753 19900131	US19880177599 19880405
US19880255657 19881013	US19890376002 19890815	US19910773680 19911008
US20050795835 20050727	US19970058062P 19970905	CA20022404410 20020920
US19930097655 19930727	CA20022397847 20020812	US19950506335 19950725
US19910811470 19911218	US20050039624 20050120	WO2005US26793 20050727
US19970999729 19971223	US19980137499 19980820	PH20040000148 20040325

Probable Assignee: CHRISTION SCHOOL OF TECHNOLOGY

Assignee(s): (std): CHRISTIAN SCHOOL OF TECHNOLOGY CHARITABLE FOUNDATION TRUST ; CHRISTION SCHOOL OF TECHNOLOGY ; GAUDENCIO LABRADOR ; LABRADOR GAUDENCIO A ; LABRADOR GAUDENCIO AQUINO ; LABRADOR GAUDENCIO ; CHRISTIAN SCHOOL OF TECHNOLOGY


Assignee(s): CHRISTIAN SCHOOL OF TECHNOLOGY CHARITABLE FOUNDATI ; CHRISTION SCHOOL OF TECHNOLOGY CHARITABLE FOUNDATI ; CHRISTION SCHOOL OF TECHNOLOGY CHARITABLE FOUNDATION TRUST

Inventor(s): (std): LABRADOR GAUDENCIO A ; LABRADOR GAUDENCIO AQUINO ; CHRISTIAN SCHOOL OF TECHNOLOGY

Inventor(s): GAUDENCIO AQUINO LABRADOR ; CHRISTIAN SCHOOL OF TECHNOLOGY CHARITABLE ; LABRADOR GAUDENCIO

Agent(s): GAUDENCIO AQUINO LABRADOR

Designated states: AE AG AL AM AT AU AZ BA BB BE BF BG BJ BR BW BY BZ CA CF CG CH CI CM CN CO CR CU CY CZ DE DK DM DZ EC EE EG ES FI FR GA GB GD GE GH GM GN GQ GR GW HR HU IE IL IN IS IT JP KE KG KM KP KZ LC LI LK LR LS LT LU LV MA MC MD MG MK ML MN MR MW MX MZ NA NE NG NI NL NO NZ OM PG PH PL PT RO RU SC SD SE SG SI SK SL SM SN SY SZ TD TG TJ TM TN TR TT TZ UA UG US UZ VC VN YU ZA ZM ZW



Title: REAR-VIEW MIRROR WITH MULTIPLE INTERCHANGEABLE SIGNALS FOR VEHICLES WITH TWO, THREE, FOUR OR MORE WHEELS

Abstract: Source: US2003169160A The invention relates to a rear-view mirror for vehicles, which consists of compatible, combinable and exchangeable modules such as: (A) and (B), or integrated (A+B), functional, signal, lighting and sensor modules; and structural (C), (D) and (E) modules; cover-**housing**, body-**housing** and support which may include functional modules. (A), (B) and (A+B) fulfill their function even if the rear-view mirror is folded. They use a multifocal light source of LED's inserted into a flexible and orientable circuit and/or a mixed rigid-flexible circuit combining LED's+bulbs and other lighting elements, with variable optical and reflective means enabling more than one signal from one same transparent surface with direct light output, indirect-reflected light output and/or through intermediate optical light guides depending on the directions required in the front, the side, the back and the lateral ground for different commands, applications and safety signals.

Classifications:

International (IPC 8-9): B60Q1/00 B60Q1/26 B60R1/12 F21V9/00 G06M7/00 (Advanced/Invention)

International (IPC 1-7): B60Q1/26 B60R1/12 B60R25/10 G06M7/00

CPC: Y10S362/80 B60Q1/2665 B60R1/1207 B60R2001/1215 B60R2001/1223


B60R2001/123 B60R2001/1253

European: B60Q1/26J B60Q1/26J2 B60R1/12A L60R1/12A L60R1/12B L60R1/12C L60R1/12D L60R1/12G

US: 340/426.1 340/426.100P 362/494 362/494P 362/511 362/540 362/545 362/800

PatBase - US2003169160_RR

First Application Publication Sep. 11, 2003 Sheet 1 of 57 US 2003/0169160 A1

**Family:**

Publication number	Publication date	Application number	Application date
AT324291 E	20060515	AT20010943552T	20010622
AU2001266099 AA	20020205	AU20010266099	20010622
AU200166099 A5	20020205	AU20010066099	20010622
DE60119122 D1	20060601	DE20016019122	20010622
DE60119122 T2	20061207	DE20016019122T	20010622
EP1304260 A1	20030423	EP20010943552	20010622
EP1304260 B1	20060426	EP20010943552	20010622
EP1690736 A2	20060816	EP20060008486	20010622
EP1690736 A3	20090805	EP20060008486	20010622
EP1690737 A2	20060816	EP20060008489	20010622
EP1690737 A3	20090930	EP20060008489	20010622
EP1690738 A2	20060816	EP20060008490	20010622
EP1690738 A3	20090819	EP20060008490	20010622
EP1698515 A2	20060906	EP20060008488	20010622
EP1698515 A3	20070606	EP20060008488	20010622
EP2154023 A2	20100217	EP20090075387	20010622
EP2154023 A3	20100331	EP20090075387	20010622
EP2174835 A1	20100414	EP20090075388	20010622
ES2168071 AA	20020516	ES20000001834	20000712
ES2168071 BA	20030716	ES20000001834	20000712
ES2264695 T3	20070116	ES20010943552T	20010622
US2003169160 AA	20030911	US20030340360	20030109
US2005225994 AA	20051013	US20050156912	20050620
US2005243568 AA	20051103	US20050157079	20050620
US2005243569 AA	20051103	US20050157195	20050620
US2005276059 AA	20051215	US20050157075	20050620
US2007279923 AA	20071206	US20070829506	20070727
US6926432 BB	20050809	US20030340360	20030109
US7188981 BB	20070313	US20050156912	20050620
US7192171 BB	20070320	US20050157075	20050620
US7255464 BB	20070814	US20050157195	20050620
US7258471 BB	20070821	US20050157079	20050620
US7524092 BB	20090428	US20070829506	20070727
WO0208015 A1	20020131	WO2001ES00251	20010622

Priority:

ES20000001834 20000712	EP20060008489 20010622	EP20010943552 20010622
US20050157075 20050620	US20030340360 20030109	WO2001ES00251 20010622
US20050157195 20050620	US20050156912 20050620	US20070829506 20070727
US20050157079 20050620		

Probable Assignee: RODRIGUES JOSE MANUEL RODRIGUEZ

Assignee(s): (std): RODRIGUES JOSE MANUEL RODRIGUEZ ; RODRIGUEZ BARROS ALEJANDRO ; RODRIGUEZ FERNANDEZ JOSE MANUE ; BARROS GARCIA ALEX R ; RODRIGUEZ FERNANDEZ JOSE M ; BARROS ALEJANDRO RODRIGUEZ ; RODRIGUEZ FERNANDEZ JOSE MANUEL

Assignee(s): ALEJANDRO RODRIGUEZ BARROS ; JOSE MANUEL RODRIGUEZ FERNANDEZ


Inventor(s): (std): BARROS ALEJANDRO RODRIGUEZ ; BARROS GARCIA ALEX R ; FERNANDEZ JOSE MANUEL RODRIGUE ; RODRIGUEZ BARROS ALEJANDRO ; RODRIGUEZ FERNANDEZ JOSE M ; RODRIGUEZ FERNANDEZ JOSE MANUE ; RODRIGUEZ FERNANDEZ JOSE MANUEL

Inventor(s): JOSE MANUEL RODRIGUEZ FERNANDEZ ; ALEJANDRO RODRIGUEZ BARROS
Agent(s): GISLON GABRIELE; STEPHEN D SCANLON; DAVID M MAIORANA JONES DAY REAVIS AND POGUE; JONES DAY
Designated states: AE AT AU BE BG BR CA CH CN CY DE DK DZ ES FI FR GB GR IE IN IT JP KP KR LI LU MC MX NL NZ PT RU SE TM TR US ZA

Title: Scavenger energy converter system its new applications and its control systems

Abstract: Source: AU2002302091A What has been invented is a series of scientific applications of the wideface energy converter device, be it in the form of a wideface solar heat receiver or a wideface fluid impeder device. The wider is the solar heat receiver, the more solar power is available for conversion. The wider is the sail of the boat, the more wind is available to push the boat. Wherefore, the wideface solar trap made up of multi-layer transparent roofs covering a heat insulated box is used to heat up a radiator tubings that contain water. The multilayer transparent roof, having spaces in between sheets, prevents solar heat from backing out hence the trap becomes hotter and hotter because the inner sheet is not in contact with the cold wind. This solar trap is now used to heat up radiator pipes of compressed air coming from a gas turbine engine and then returned back to the exhaust turbine of same engine. Applying the principle of the wind sail, the turbine blades of the compressor and the turbine blades of the exhaust turbine are made wideface as much as possible to produce maximum impedance against the expanding exhaust hot air and to produce maximum push upon the fresh air being compressed. This wideface fluid impeder is now expanded into an underwater platform from One Acre or much more and attached to floating hotels, large/small boats, and floating sea walls, to prevent oscillation by the surfs. 36 9 Fig.1 104 Fig.I

Classifications:
International (IPC 8-9): F03D9/00 F03G6/00 (Advanced/Invention); F03D9/00 F03G6/00 (Core/Invention)
International (IPC 1-7): F03D9/00 F03G6/00
CPC: Y02B10/22 Y02B10/30 Y02B10/70 Y02E10/46 Y02E10/725
European: Y02B10/22 Y02B10/30 Y02B10/70 Y02E10/46 Y02E10/72H



Family:

Publication number	Publication date	Application number	Application date
AU2002302091 AA	20040610	AU20020302091	20021122

Priority:
AU20020302091 20021122

Probable Assignee: GAUDENCIO LABRADOR
Assignee(s): (std): GAUDENCIO LABRADOR
Assignee(s): LABRADOR GAUDENCIO A
Inventor(s): (std): LABRADOR GAUDENCIO A
Inventor(s): GAUDENCIO A LABRADOR