



No. 11-067280- -00004-0000

Fecha: 2011-08-31 10:11:43 Dep. 2020 DIR.NUEVASCR  
Tra. 2 PATENTES Eve: 1 REGDEPOSITO  
Act. 329 CTOINFORMACION Folios: 83  
Act. 329 CTOINFORMACION Folios: 73

Señores

SUPERINTENDENCIA DE INDUSTRIA Y CO.  
DIVISIÓN DE NUEVAS CREACIONES

E.

S.

D.

Ref.: Expediente No. 11 067280

Solicitud de Patente PCT SISTEMA DE RESISTENCIA DE FLUJO  
VARIABLE CON ESTRUCTURA QUE INDUCE LA CIRCULACIÓN  
EN LA MISMA PARA RESISTIR VARIABLEMENTE EL FLUJO EN  
UN POZO SUBTERRÁNEO

Solicitante: HALLIBURTON ENERGY SERVICES, INC

Luz Helena Adarve Gómez, identificada como aparece al pie de mi firma y obrando en mi condición de apoderada de la sociedad HALLIBURTON ENERGY SERVICES, INC mencionada en la referencia, me permito adjuntar:

1. Memoriales de presentación de Poder, documento existencia y representación legal y documento de cesión.
2. Copia certificada de la prioridad invocada junto traducción simple del capítulo reivindicatorio.

En virtud de lo anterior, solicito a ese Despacho proceder a ordenar la publicación del diseño en referencia.

Atentamente,

Luz Helena Adarve Gómez  
c.c. 41575435 de Bogotá  
t.p. 14.884 C.S.J.

Fol P-571  
JAG/amg

## REIVINDICACIONES

1. Un sistema de resistencia de flujo variable para usar en un pozo subterráneo, el sistema comprende:

5 una cámara de flujo a través de la cual fluye una composición fluida, la cámara tiene al menos una entrada, una salida, y al menos una estructura que impide un cambio del flujo circular de la composición fluida alrededor de la salida a flujo radial hacia la salida.

10

2. El sistema de la reivindicación 1, en donde la composición fluida fluye a través de la cámara de flujo en el pozo.

3. El sistema de la reivindicación 1, en donde la estructura  
15 impide, cada vez más, el cambio de flujo circular de la composición fluida alrededor de la salida a flujo radial hacia la salida en respuesta a al menos uno de a) aumento de la velocidad de la composición fluida, b) disminución de la viscosidad de la composición fluida, c) reducción de la relación de fluido deseado  
20 al fluido indeseado en la composición fluida, d) disminución del ángulo de entrada de la composición fluida en la cámara de flujo, y e) un incremento del choque de la composición fluida con la estructura.

25 4. El sistema de la reivindicación 1, en donde la al menos una entrada comprende sólo una sola entrada.

5. El sistema de la reivindicación 1, en donde la estructura comprende al menos uno de un aspa y un agujero.

30

6. El sistema de la reivindicación 1, en donde la estructura se proyecta al menos una interiormente y exteriormente con relación a una pared de la cámara.

35 7. El sistema de la reivindicación 1, en donde composición fluida sale de la cámara a través de la salida a un ángulo que cambia en base a una relación del fluido deseado al fluido indeseado en la composición fluida.

8. El sistema de la reivindicación 1, en donde la composición fluida fluye más directamente desde la entrada a la salida según aumenta la viscosidad de la composición fluida.

5 9. El sistema de la reivindicación 1, en donde la composición fluida fluye más directamente desde la entrada a la salida según disminuye la velocidad de la composición fluida.

10 10. El sistema de la reivindicación 1, en donde la composición fluida fluye más directamente desde la entrada a la salida según aumente el ángulo de entrada de la composición fluida.

15 11. El sistema de la reivindicación 1, en donde la composición fluida fluye más directamente desde la entrada a la salida según aumente la relación del fluido deseado al fluido indeseado en la composición fluida.

20 12. El sistema de la reivindicación 1, en donde la estructura incrementa la velocidad de la composición fluida según ésta fluya de la entrada a la salida.

13. Un sistema de resistencia de flujo variable para el uso en un pozo subterráneo, el sistema comprende:

25 una cámara de flujo a través de la cual fluye una composición fluida en el pozo. la cámara tiene al menos una entrada, una salida y al menos una estructura que impide el flujo circular de la composición fluida alrededor de la salida.

30 14. El sistema de la reivindicación 13, en donde la composición fluida fluye a través de la cámara de flujo en el pozo.

35 15. El sistema de la reivindicación 13, en donde la estructura impide, cada vez más, el flujo circular de la composición fluida alrededor de la salida en respuesta a al menos uno de, a) disminución de la velocidad de la composición fluida, b) aumento de la viscosidad de la composición fluida, c) incremento de la relación del fluido deseado con relación al fluido indeseado en la composición fluida, d) disminución del ángulo de entrada de la composición fluida en la cámara de flujo, y e) incremento del choque de la composición fluida con la estructura.

40

16. El sistema de la reivindicación 13, en donde la estructura tiene una abertura que permite que la composición fluida cambie la dirección y el flujo más directamente de la entrada a la salida.

17. El sistema de la reivindicación 13, en donde al menos una entrada comprende al menos entradas primarias y secundarias, en donde la entrada primaria dirige la composición fluida a fluir más directamente hacia la salida de la cámara comparado con la entrada secundaria.

18. El sistema de la reivindicación 13, en donde la al menos una entrada comprende una sola entrada.

19. El sistema de la reivindicación 13, en donde la estructura comprende al menos uno de un aspa y un agujero.

20. El sistema de la reivindicación 13, en donde la estructura se proyecta al menos interiormente y exteriormente con relación a una pared de la cámara.

21. El sistema de la reivindicación 13, en donde la composición fluida sale de la cámara a través de la salida a un ángulo que cambia en base a una relación de fluido deseado al fluido indeseado en la composición fluida.

22. El sistema de la reivindicación 13, en donde la composición fluida fluye más directamente desde la entrada a la salida según aumenta la viscosidad de la composición fluida.

23. El sistema de la reivindicación 13, en donde la composición fluida fluye más directamente desde la entrada a la salida según disminuye la velocidad de la composición fluida.

24. El sistema de la reivindicación 13, en donde la composición fluida fluye más directamente desde la entrada a la salida según aumenta el ángulo de entrada de la composición fluida.

25. El sistema de la reivindicación 13, en donde la composición fluida fluye más directamente desde la entrada a la salida según aumenta la relación del fluido deseado al fluido indeseado.

5

26. El sistema de la reivindicación 13, en donde la estructura reduce una velocidad de la composición fluida mientras fluye desde la entrada a la salida.

10

27. Un sistema de resistencia de flujo variable para el uso en un pozo subterráneo, el sistema comprende:

una cámara de flujo que incluye una salida y al menos una estructura que resiste el cambio en la dirección de flujo de la composición fluida hacia la salida, y

15

en donde la composición fluida entra a la cámara en la dirección del flujo que cambia en base a una relación del fluido deseado con relación al fluido indeseado en la composición fluida.

20

28. El sistema de la reivindicación 27, en donde la estructura impide un cambio del flujo circular de la composición fluida alrededor de la salida a flujo radial hacia salida.

25

29. El sistema de la reivindicación 27, en donde la estructura tiene una abertura la cual permite un cambio del flujo circular de la composición fluida alrededor de la salida a flujo radial hacia la salida.

30

30. El sistema de la reivindicación 29, en donde la abertura en la estructura permite el flujo más directo de la composición fluida desde una entrada a la salida.

31. El sistema de la reivindicación 30, en donde la composición fluida fluye en la cámara sólo a través de la entrada.

35

32. El sistema de la reivindicación 27, en donde la estructura comprende al menos uno de un aspa y un agujero

40

33. El sistema de la reivindicación 27, en donde la estructura se proyecta al menos interiormente y exteriormente con relación a una pared de la cámara.

34. El sistema de la reivindicación 27, en donde la composición fluida fluye más directamente desde una entrada de la cámara a la salida según aumenta la viscosidad de la composición fluida.

35. El sistema de la reivindicación 27, en donde la composición fluida fluye más directamente desde una entrada de la cámara a la salida según disminuye la velocidad de la composición fluida.

36. El sistema de la reivindicación 27, en donde la composición fluida fluye más directamente desde una entrada de la cámara a la salida según aumenta el ángulo de entrada de la composición fluida.

37. El sistema de la reivindicación 27, en donde la composición fluida fluye más directamente desde una entrada de la cámara a la salida según aumenta la relación de fluido deseado al fluido indeseado en la composición fluida.

38. El sistema de la reivindicación 27, en donde la estructura impide, cada vez más, un cambio del flujo circular en la dirección de la composición fluida alrededor de la salida a flujo radial hacia la salida según aumenta la velocidad de la composición fluida, una viscosidad de la composición fluida disminuye, un ángulo de entrada de la composición fluida disminuye, una relación del fluido deseado al fluido indeseado disminuye, y el choque de la composición fluida con la estructura aumenta.

39. El sistema de la reivindicación 27, en donde la estructura, cada vez más, causa un cambio en la dirección de la composición fluida del flujo circular de la composición fluida alrededor de la salida a flujo radial hacia la salida según disminuya la velocidad de la composición fluida, la viscosidad de la composición fluida aumente, el ángulo de entrada de la composición fluida aumente y la relación de fluido deseado al fluido indeseado aumente.

40. El sistema de la reivindicación 27, en donde la estructura incrementa la velocidad de la composición fluida mientras fluye de una entrada a la salida.

5        41. El sistema de la reivindicación 27, en donde la estructura reduce la velocidad de la composición fluida mientras fluye de una entrada a la salida.

42. Un sistema de resistencia de flujo variable para el uso en un pozo subterráneo, el sistema comprende:

10        un dispositivo de selección de la vía de flujo que selecciona a través de cuál de las múltiples vías de flujo fluirá una mayor parte del fluido desde el dispositivo en base a una relación del fluido deseado al fluido indeseado en una composición fluida; y

15        una cámara de flujo que tiene una salida, una primera entrada conectada a la primera de las vía de flujo, una segunda entrada conectada a la segunda de las vía de flujo y al menos una estructura que impide el flujo radial de la composición fluida desde la segunda entrada a la salida más que e flujo radial de la composición fluida de la primera entrada a la salida.

20

43. El sistema de la reivindicación 42, en donde la estructura tiene al menos una abertura que permite a la composición fluida cambiar la dirección y el flujo más directamente desde la primera entrada a la salida.

25

44. El sistema de la reivindicación 42, en donde la primera entrada direcciona la composición fluida a fluir más directamente hacia la salida en comparación con la segunda entrada.

30        45. El sistema de la reivindicación 42, en donde la estructura comprende al menos uno de un aspa y un agujero.

35        46. El sistema de la reivindicación 42, en donde la estructura se proyecta al menos interiormente y exteriormente con relación a una pared de la cámara.

47. El sistema de la reivindicación 42, en donde la estructura induce porciones de la composición fluida las cuales fluyen circularmente alrededor de la salida a continuar fluyendo circularmente alrededor de la salida.


40

48. El sistema de la reivindicación 42, en donde la estructura impide, cada vez más, un cambio del flujo circular de la composición fluida alrededor de la salida a flujo radial hacia la salida en respuesta a al menos uno de a) aumento de la velocidad de la composición fluida, b) disminución de la viscosidad de la composición fluida, c) una relación reducida del fluido deseado con relación al fluido indeseado en la composición fluida, d) disminución del ángulo de entrada de la composición fluida, y e) aumento del choque de la composición fluida con la estructura.

49. El sistema de la reivindicación 42, en donde una estructura en la cámara incrementa la velocidad de la composición fluida mientras fluye a la salida.

15

PA 1840894



# THE UNITED STATES OF AMERICA

**TO ALL TO WHOM THESE PRESENTS SHALL COME:**

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office

May 04, 2011

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM  
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK  
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT  
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A  
FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 12/792,146

FILING DATE: June 02, 2010

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY  
APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS  
CONVENTION, IS US12/792,146

By Authority of the  
Under Secretary of Commerce for Intellectual Property  
and Director of the United States Patent and Trademark Office



*W. Montgomery*  
W. MONTGOMERY  
Certifying Officer

## Electronic Acknowledgement Receipt

|                                             |                                                                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>EFS ID:</b>                              | 7729459                                                                                                                    |
| <b>Application Number:</b>                  | 12792146                                                                                                                   |
| <b>International Application Number:</b>    |                                                                                                                            |
| <b>Confirmation Number:</b>                 | 4135                                                                                                                       |
| <b>Title of Invention:</b>                  | VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION INDUCING STRUCTURE THEREIN TO VARIABLY RESIST FLOW IN A SUBTERRANEAN WELL |
| <b>First Named Inventor/Applicant Name:</b> | Jason D. DYKSTRA                                                                                                           |
| <b>Customer Number:</b>                     | 49431                                                                                                                      |
| <b>Filer:</b>                               | Marlin Ray Smith/Sally Ann Smith                                                                                           |
| <b>Filer Authorized By:</b>                 | Marlin Ray Smith                                                                                                           |
| <b>Attorney Docket Number:</b>              | 2010-IP-033103 U1 US                                                                                                       |
| <b>Receipt Date:</b>                        | 02-JUN-2010                                                                                                                |
| <b>Filing Date:</b>                         |                                                                                                                            |
| <b>Time Stamp:</b>                          | 14:35:58                                                                                                                   |
| <b>Application Type:</b>                    | Utility under 35 USC 111(a)                                                                                                |

### Payment information:

|                        |    |
|------------------------|----|
| Submitted with Payment | no |
|------------------------|----|

### File Listing:

| Document Number | Document Description | File Name             | File Size(Bytes)/<br>Message Digest               | Multi Part /.zip | Pages (if appl.) |
|-----------------|----------------------|-----------------------|---------------------------------------------------|------------------|------------------|
| 1               |                      | PatentApplication.pdf | 136626<br>fb7462a44fec5821a14150708a13fe17cd15646 | yes              | 51               |

|                              |                                                    |                          |                                          |     |    |
|------------------------------|----------------------------------------------------|--------------------------|------------------------------------------|-----|----|
|                              | Multipart Description/PDF files in zip description |                          |                                          |     |    |
|                              | Document Description                               |                          | Start                                    | End |    |
|                              | Specification                                      |                          | 1                                        | 38  |    |
|                              | Claims                                             |                          | 39                                       | 50  |    |
|                              | Abstract                                           |                          | 51                                       | 51  |    |
| Warnings:                    |                                                    |                          |                                          |     |    |
| Information:                 |                                                    |                          |                                          |     |    |
| 2                            | Drawings-only black and white line drawings        | Drawings.pdf             | 1791799                                  | no  | 12 |
|                              |                                                    |                          | 69e9342a0764666c9d425ea78b880781852b6619 |     |    |
| Warnings:                    |                                                    |                          |                                          |     |    |
| Information:                 |                                                    |                          |                                          |     |    |
| 3                            | Oath or Declaration filed                          | Declaration.pdf          | 542836                                   | no  | 2  |
|                              |                                                    |                          | 8526d00dbf3d8220ad24dcb0422e675a794596dd |     |    |
| Warnings:                    |                                                    |                          |                                          |     |    |
| Information:                 |                                                    |                          |                                          |     |    |
| 4                            | Application Data Sheet                             | ApplicationDataSheet.pdf | 1104392                                  | no  | 4  |
|                              |                                                    |                          | 897c82dfc98fc072ac70aee2ca812fac8964c6bb |     |    |
| Warnings:                    |                                                    |                          |                                          |     |    |
| Information:                 |                                                    |                          |                                          |     |    |
| 5                            | Transmittal of New Application                     | Transmittal.pdf          | 253390                                   | no  | 2  |
|                              |                                                    |                          | 5a0c937a77bc07725ae656988ac873bc634c1cfc |     |    |
| Warnings:                    |                                                    |                          |                                          |     |    |
| Information:                 |                                                    |                          |                                          |     |    |
| Total Files Size (in bytes): |                                                    |                          | 3829043                                  |     |    |

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

**New Applications Under 35 U.S.C. 111**

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

**National Stage of an International Application under 35 U.S.C. 371**

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

**New International Application Filed with the USPTO as a Receiving Office**

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY  
PATENT APPLICATION  
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

2010-IP-033103 U1 US

First Inventor

Jason D. DYKSTRA

Title

VARIABLE FLOW RESISTANCE SYSTEM..

Express Mail Label No.

**APPLICATION ELEMENTS**

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ **Fee Transmittal Form** (e.g., PTO/SB/17)
2. ☐ **Applicant claims small entity status.**  
See 37 CFR 1.27.
3. ☒ **Specification** [Total Pages 51]  
Both the claims and abstract must start on a new page  
(For information on the preferred arrangement, see MPEP 608.01(a))
4. ☒ **Drawing(s)** (35 U.S.C. 113) [Total Sheets 12]
5. **Oath or Declaration** [Total Sheets 2]  
  - a. ☒ Newly executed (original or copy)
  - b. ☐ A copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 18 completed)
    - i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s)  
name in the prior application, see 37 CFR  
1.63(d)(2) and 1.33(b).
6. ☒ **Application Data Sheet.** See 37 CFR 1.76
7. ☐ **CD-ROM or CD-R** in duplicate, large table or  
Computer Program (Appendix)  
☐ Landscape Table on CD
8. **Nucleotide and/or Amino Acid Sequence Submission**  
(if applicable, items a. - c. are required)
  - a. ☐ Computer Readable Form (CRF)
  - b. **Specification Sequence Listing on:**
    - i. ☐ CD-ROM or CD-R (2 copies); or
    - ii. ☐ Paper
  - c. ☐ Statements verifying identity of above copies

ADDRESS TO:

Commissioner for Patents  
P.O. Box 1450  
Alexandria VA 22313-1450**ACCOMPANYING APPLICATION PARTS**

9. ☐ **Assignment Papers** (cover sheet & document(s))  
Name of Assignee \_\_\_\_\_
10. ☐ **37 CFR 3.73(b) Statement** ☐ **Power of Attorney**  
(when there is an assignee)
11. ☐ **English Translation Document** (if applicable)
12. ☐ **Information Disclosure Statement** (PTO/SB/08 or PTO-1449)  
☐ Copies of citations attached
13. ☐ **Preliminary Amendment**
14. ☐ **Return Receipt Postcard** (MPEP 503)  
(Should be specifically itemized)
15. ☐ **Certified Copy of Priority Document(s)**  
(if foreign priority is claimed)
16. ☐ **Nonpublication Request** under 35 U.S.C. 122(b)(2)(B)(i).  
Applicant must attach form PTO/SB/35 or equivalent.
17. ☐ Other: \_\_\_\_\_

18. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in the first sentence of the specification following the title, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation    ☐ Divisional    ☐ Continuation-in-part (CIP)    of prior application No.: \_\_\_\_\_

Prior application information:    Examiner: \_\_\_\_\_    Art Unit: \_\_\_\_\_

**19. CORRESPONDENCE ADDRESS**
☒ The address associated with Customer Number: 49431    OR    ☐ Correspondence address below

Name

Address

City

State

Zip Code

Country

Telephone

Email

Signature

/Marlin R. Smith/

Date

June 2, 2010

Name

(Print/Type)

Marlin R. Smith

Registration No.

(Attorney/Agent)

38310

This collection of information is required by 37 CFR 1.53(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

## Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

5

**VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION  
INDUCING STRUCTURE THEREIN TO VARIABLY RESIST FLOW  
10 IN A SUBTERRANEAN WELL**

Inventors: Jason D. Dykstra and Michael L. Fripp

15

**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is related to prior application  
serial no. 12/700685 filed on 4 February 2010, which is a  
continuation-in-part of application serial no. 12/542695  
20 filed on 18 August 2009. The entire disclosures of these  
prior applications are incorporated herein by this  
reference for all purposes.

### BACKGROUND

This disclosure relates generally to equipment utilized and operations performed in conjunction with a subterranean well and, in an example described below, more particularly provides for variably resisting flow in a subterranean well.

In a hydrocarbon production well, it is many times beneficial to be able to regulate flow of fluids from an earth formation into a wellbore. A variety of purposes may be served by such regulation, including prevention of water or gas coning, minimizing sand production, minimizing water and/or gas production, maximizing oil and/or gas production, balancing production among zones, etc.

In an injection well, it is typically desirable to evenly inject water, steam, gas, etc., into multiple zones, so that hydrocarbons are displaced evenly through an earth formation, without the injected fluid prematurely breaking through to a production wellbore. Thus, the ability to regulate flow of fluids from a wellbore into an earth formation can also be beneficial for injection wells.

Therefore, it will be appreciated that advancements in the art of variably restricting fluid flow in a well would be desirable in the circumstances mentioned above, and such advancements would also be beneficial in a wide variety of other circumstances.

**SUMMARY**

In the disclosure below, a variable flow resistance system is provided which brings improvements to the art of regulating fluid flow in a well. One example is described below in which flow of a fluid composition resisted more if the fluid composition has a threshold level of an undesirable characteristic. Another example is described below in which a resistance to flow through the system increases as a ratio of desired fluid to undesired fluid in the fluid composition decreases.

In one aspect, this disclosure provides to the art a variable flow resistance system for use in a subterranean well. The system can include a flow chamber through which a fluid composition flows. The chamber has at least one inlet, an outlet, and at least one structure which impedes a change from circular flow of the fluid composition about the outlet to radial flow toward the outlet.

In another aspect, a variable flow resistance system for use in a subterranean well can include a flow chamber through which a fluid composition flows. The chamber has at least one inlet, an outlet, and at least one structure which impedes circular flow of the fluid composition about the outlet.

In yet another aspect, a variable flow resistance system for use in a subterranean well is provided. The system can include a flow chamber through which a fluid composition flows in the well, the chamber having at least one inlet, an outlet, and at least one structure which

impedes a change from circular flow of the fluid composition about the outlet to radial flow toward the outlet.

5 In another aspect, a variable flow resistance system described below can include a flow chamber with an outlet and at least one structure which resists a change in a direction of flow of a fluid composition toward the outlet. The fluid composition enters the chamber in a direction of flow which changes based on a ratio of desired fluid to  
10 undesired fluid in the fluid composition.

In yet another aspect, this disclosure provides a variable flow resistance system which can include a flow path selection device that selects which of multiple flow paths a majority of fluid flows through from the device,  
15 based on a ratio of desired fluid to undesired fluid in a fluid composition. The system also includes a flow chamber having an outlet, a first inlet connected to a first one of the flow paths, a second inlet connected to a second one of the flow paths, and at least one structure which impedes  
20 radial flow of the fluid composition from the second inlet to the outlet more than it impedes radial flow of the fluid composition from the first inlet to the outlet.

These and other features, advantages and benefits will become apparent to one of ordinary skill in the art upon  
25 careful consideration of the detailed description of representative examples below and the accompanying drawings, in which similar elements are indicated in the various figures using the same reference numbers.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a schematic partially cross-sectional view of a well system which can embody principles of the present disclosure.

FIG. 2 is an enlarged scale schematic cross-sectional view of a well screen and a variable flow resistance system which may be used in the well system of FIG. 1.

FIG. 3 is a schematic "unrolled" plan view of one configuration of the variable flow resistance system, taken along line 3-3 of FIG. 2.

FIGS. 4A & B are schematic plan views of another configuration of a flow chamber of the variable flow resistance system.

FIG. 5 is a schematic plan view of yet another configuration of the flow chamber.

FIGS. 6A & B are schematic plan views of yet another configuration of the variable flow resistance system.

FIGS. 7A-H are schematic cross-sectional views of various configurations of the flow chamber, with FIGS. 7A-G being taken along line 7-7 of FIG. 4B, and FIG. 7H being taken along line 7H-7H of FIG. 7G.

FIGS. 7I & J are schematic perspective views of configurations of structures which may be used in the flow chamber of the variable flow resistance system.

FIGS. 8A-11 are schematic plan views of additional configurations of the flow chamber.

#### DETAILED DESCRIPTION

5       Representatively illustrated in FIG. 1 is a well system 10 which can embody principles of this disclosure. As depicted in FIG. 1, a wellbore 12 has a generally vertical uncased section 14 extending downwardly from casing 16, as well as a generally horizontal uncased  
10   section 18 extending through an earth formation 20.

A tubular string 22 (such as a production tubing string) is installed in the wellbore 12. Interconnected in the tubular string 22 are multiple well screens 24, variable flow resistance systems 25 and packers 26.

15       The packers 26 seal off an annulus 28 formed radially between the tubular string 22 and the wellbore section 18. In this manner, fluids 30 may be produced from multiple intervals or zones of the formation 20 via isolated portions of the annulus 28 between adjacent pairs of the  
20   packers 26.

Positioned between each adjacent pair of the packers 26, a well screen 24 and a variable flow resistance system 25 are interconnected in the tubular string 22. The well screen 24 filters the fluids 30 flowing into the tubular  
25   string 22 from the annulus 28. The variable flow resistance system 25 variably restricts flow of the fluids

30 into the tubular string 22, based on certain characteristics of the fluids.

At this point, it should be noted that the well system 10 is illustrated in the drawings and is described herein as merely one example of a wide variety of well systems in which the principles of this disclosure can be utilized. It should be clearly understood that the principles of this disclosure are not limited at all to any of the details of the well system 10, or components thereof, depicted in the drawings or described herein.

For example, it is not necessary in keeping with the principles of this disclosure for the wellbore 12 to include a generally vertical wellbore section 14 or a generally horizontal wellbore section 18. It is not necessary for fluids 30 to be only produced from the formation 20 since, in other examples, fluids could be injected into a formation, fluids could be both injected into and produced from a formation, etc.

It is not necessary for one each of the well screen 24 and variable flow resistance system 25 to be positioned between each adjacent pair of the packers 26. It is not necessary for a single variable flow resistance system 25 to be used in conjunction with a single well screen 24. Any number, arrangement and/or combination of these components may be used.

It is not necessary for any variable flow resistance system 25 to be used with a well screen 24. For example, in injection operations, the injected fluid could be flowed

through a variable flow resistance system 25, without also flowing through a well screen 24.

It is not necessary for the well screens 24, variable flow resistance systems 25, packers 26 or any other  
5 components of the tubular string 22 to be positioned in uncased sections 14, 18 of the wellbore 12. Any section of the wellbore 12 may be cased or uncased, and any portion of the tubular string 22 may be positioned in an uncased or cased section of the wellbore, in keeping with the  
10 principles of this disclosure.

It should be clearly understood, therefore, that this disclosure describes how to make and use certain examples, but the principles of the disclosure are not limited to any details of those examples. Instead, those principles can  
15 be applied to a variety of other examples using the knowledge obtained from this disclosure.

It will be appreciated by those skilled in the art that it would be beneficial to be able to regulate flow of the fluids 30 into the tubular string 22 from each zone of  
20 the formation 20, for example, to prevent water coning 32 or gas coning 34 in the formation. Other uses for flow regulation in a well include, but are not limited to, balancing production from (or injection into) multiple zones, minimizing production or injection of undesired  
25 fluids, maximizing production or injection of desired fluids, etc.

Examples of the variable flow resistance systems 25 described more fully below can provide these benefits by

increasing resistance to flow if a fluid velocity increases beyond a selected level (e.g., to thereby balance flow among zones, prevent water or gas coning, etc.), increasing resistance to flow if a fluid viscosity or density decreases below a selected level (e.g., to thereby restrict flow of an undesired fluid, such as water or gas, in an oil producing well), and/or increasing resistance to flow if a fluid viscosity or density increases above a selected level (e.g., to thereby minimize injection of water in a steam injection well).

Whether a fluid is a desired or an undesired fluid depends on the purpose of the production or injection operation being conducted. For example, if it is desired to produce oil from a well, but not to produce water or gas, then oil is a desired fluid and water and gas are undesired fluids. If it is desired to produce gas from a well, but not to produce water or oil, the gas is a desired fluid, and water and oil are undesired fluids. If it is desired to inject steam into a formation, but not to inject water, then steam is a desired fluid and water is an undesired fluid.

Note that, at downhole temperatures and pressures, hydrocarbon gas can actually be completely or partially in liquid phase. Thus, it should be understood that when the term "gas" is used herein, supercritical, liquid and/or gaseous phases are included within the scope of that term.

Referring additionally now to FIG. 2, an enlarged scale cross-sectional view of one of the variable flow

resistance systems 25 and a portion of one of the well screens 24 is representatively illustrated. In this example, a fluid composition 36 (which can include one or more fluids, such as oil and water, liquid water and steam,  
5 oil and gas, gas and water, oil, water and gas, etc.) flows into the well screen 24, is thereby filtered, and then flows into an inlet 38 of the variable flow resistance system 25.

A fluid composition can include one or more undesired  
10 or desired fluids. Both steam and water can be combined in a fluid composition. As another example, oil, water and/or gas can be combined in a fluid composition.

Flow of the fluid composition 36 through the variable flow resistance system 25 is resisted based on one or more  
15 characteristics (such as density, viscosity, velocity, etc.) of the fluid composition. The fluid composition 36 is then discharged from the variable flow resistance system 25 to an interior of the tubular string 22 via an outlet 40.

In other examples, the well screen 24 may not be used  
20 in conjunction with the variable flow resistance system 25 (e.g., in injection operations), the fluid composition 36 could flow in an opposite direction through the various elements of the well system 10 (e.g., in injection  
25 operations), a single variable flow resistance system could be used in conjunction with multiple well screens, multiple variable flow resistance systems could be used with one or more well screens, the fluid composition could be received

from or discharged into regions of a well other than an annulus or a tubular string, the fluid composition could flow through the variable flow resistance system prior to flowing through the well screen, any other components could  
5 be interconnected upstream or downstream of the well screen and/or variable flow resistance system, etc. Thus, it will be appreciated that the principles of this disclosure are not limited at all to the details of the example depicted in FIG. 2 and described herein.

10 Although the well screen 24 depicted in FIG. 2 is of the type known to those skilled in the art as a wire-wrapped well screen, any other types or combinations of well screens (such as sintered, expanded, pre-packed, wire mesh, etc.) may be used in other examples. Additional  
15 components (such as shrouds, shunt tubes, lines, instrumentation, sensors, inflow control devices, etc.) may also be used, if desired.

The variable flow resistance system 25 is depicted in simplified form in FIG. 2, but in a preferred example, the  
20 system can include various passages and devices for performing various functions, as described more fully below. In addition, the system 25 preferably at least partially extends circumferentially about the tubular string 22, or the system may be formed in a wall of a  
25 tubular structure interconnected as part of the tubular string.

In other examples, the system 25 may not extend circumferentially about a tubular string or be formed in a

wall of a tubular structure. For example, the system 25 could be formed in a flat structure, etc. The system 25 could be in a separate housing that is attached to the tubular string 22, or it could be oriented so that the axis of the outlet 40 is parallel to the axis of the tubular string. The system 25 could be on a logging string or attached to a device that is not tubular in shape. Any orientation or configuration of the system 25 may be used in keeping with the principles of this disclosure.

Referring additionally now to FIG. 3, a more detailed cross-sectional view of one example of the system 25 is representatively illustrated. The system 25 is depicted in FIG. 3 as if it is "unrolled" from its circumferentially extending configuration to a generally planar configuration.

As described above, the fluid composition 36 enters the system 25 via the inlet 38, and exits the system via the outlet 40. A resistance to flow of the fluid composition 36 through the system 25 varies based on one or more characteristics of the fluid composition. The system 25 depicted in FIG. 3 is similar in most respects to that illustrated in FIG. 23 of the prior application serial no. 12/700685 incorporated herein by reference above.

In the example of FIG. 3, the fluid composition 36 initially flows into multiple flow passages 42, 44, 46, 48. The flow passages 42, 44, 46, 48 direct the fluid composition 36 to two flow path selection devices 50, 52. The device 50 selects which of two flow paths 54, 56 a

majority of the flow from the passages 44, 46, 48 will enter, and the other device 52 selects which of two flow paths 58, 60 a majority of the flow from the passages 42, 44, 46, 48 will enter.

5       The flow passage 44 is configured to be more restrictive to flow of fluids having higher viscosity. Flow of increased viscosity fluids will be increasingly restricted through the flow passage 44.

10       As used herein, the term "viscosity" is used to indicate any of the related rheological properties including kinematic viscosity, yield strength, viscoplasticity, surface tension, wettability, etc.

15       For example, the flow passage 44 may have a relatively small flow area, the flow passage may require the fluid flowing therethrough to follow a tortuous path, surface roughness or flow impeding structures may be used to provide an increased resistance to flow of higher viscosity fluid, etc. Relatively low viscosity fluid, however, can flow through the flow passage 44 with relatively low  
20       resistance to such flow.

25       A control passage 64 of the flow path selection device 50 receives the fluid which flows through the flow passage 44. A control port 66 at an end of the control passage 64 has a reduced flow area to thereby increase a velocity of the fluid exiting the control passage.

      The flow passage 48 is configured to have a flow resistance which is relatively insensitive to viscosity of

fluids flowing therethrough, but which may be increasingly resistant to flow of higher velocity and/or density fluids. Flow of increased viscosity fluids may be increasingly resisted through the flow passage 48, but not to as great an extent as flow of such fluids would be resisted through the flow passage 44.

In the example depicted in FIG. 3, fluid flowing through the flow passage 48 must flow through a "vortex" chamber 62 prior to being discharged into a control passage 68 of the flow path selection device 50. Since the chamber 62 in this example has a cylindrical shape with a central outlet, and the fluid composition 36 spirals about the chamber, increasing in velocity as it nears the outlet, driven by a pressure differential from the inlet to the outlet, the chamber is referred to as a "vortex" chamber. In other examples, one or more orifices, venturis, nozzles, etc. may be used.

The control passage 68 terminates at a control port 70. The control port 70 has a reduced flow area, in order to increase the velocity of the fluid exiting the control passage 68.

It will be appreciated that, as a viscosity of the fluid composition 36 increases, a greater proportion of the fluid composition will flow through the flow passage 48, control passage 68 and control port 70 (due to the flow passage 44 resisting flow of higher viscosity fluid more than the flow passage 48 and vortex chamber 62), and as a viscosity of the fluid composition decreases, a greater

proportion of the fluid composition will flow through the flow passage 44, control passage 64 and control port 66.

Fluid which flows through the flow passage 46 also flows through a vortex chamber 72, which may be similar to the vortex chamber 62 (although the vortex chamber 72 in a preferred example provides less resistance to flow therethrough than the vortex chamber 62), and is discharged into a central passage 74. The vortex chamber 72 is used for "impedance matching" to achieve a desired balance of flows through the flow passages 44, 46, 48.

Note that dimensions and other characteristics of the various components of the system 25 will need to be selected appropriately, so that desired outcomes are achieved. In the example of FIG. 3, one desired outcome of the flow path selection device 50 is that flow of a majority of the fluid composition 36 which flows through the flow passages 44, 46, 48 is directed into the flow path 54 when the fluid composition has a sufficiently high ratio of desired fluid to undesired fluid therein.

In this case, the desired fluid is oil, which has a higher viscosity than water or gas, and so when a sufficiently high proportion of the fluid composition 36 is oil, a majority of the fluid composition 36 which enters the flow path selection device 50 will be directed to flow into the flow path 54, instead of into the flow path 56. This result is achieved due to the fluid exiting the control port 70 at a greater rate or at a higher velocity than fluid exiting the other control port 66, thereby

influencing the fluid flowing from the passages 64, 68, 74 to flow more toward the flow path 54.

If the viscosity of the fluid composition 36 is not sufficiently high (and thus a ratio of desired fluid to undesired fluid is below a selected level), a majority of the fluid composition which enters the flow path selection device 50 will be directed to flow into the flow path 56, instead of into the flow path 54. This will be due to the fluid exiting the control port 66 at a greater rate or at a higher velocity than fluid exiting the other control port 70, thereby influencing the fluid flowing from the passages 64, 68, 74 to flow more toward the flow path 56.

It will be appreciated that, by appropriately configuring the flow passages 44, 46, 48, control passages 64, 68, control ports 66, 70, vortex chambers 62, 72, etc., the ratio of desired to undesired fluid in the fluid composition 36 at which the device 50 selects either the flow passage 54 or 56 for flow of a majority of fluid from the device can be set to various different levels.

The flow paths 54, 56 direct fluid to respective control passages 76, 78 of the other flow path selection device 52. The control passages 76, 78 terminate at respective control ports 80, 82. A central passage 75 receives fluid from the flow passage 42.

The flow path selection device 52 operates similar to the flow path selection device 50, in that fluid which flows into the device 52 via the passages 75, 76, 78 is directed toward one of the flow paths 58, 60, and the flow

path selection depends on a ratio of fluid discharged from the control ports 80, 82. If fluid flows through the control port 80 at a greater rate or velocity as compared to fluid flowing through the control port 82, then a majority of the fluid composition 36 will be directed to flow through the flow path 60. If fluid flows through the control port 82 at a greater rate or velocity as compared to fluid flowing through the control port 80, then a majority of the fluid composition 36 will be directed to flow through the flow path 58.

Although two of the flow path selection devices 50, 52 are depicted in the example of the system 25 in FIG. 3, it will be appreciated that any number (including one) of flow path selection devices may be used in keeping with the principles of this disclosure. The devices 50, 52 illustrated in FIG. 3 are of the type known to those skilled in the art as jet-type fluid ratio amplifiers, but other types of flow path selection devices (e.g., pressure-type fluid ratio amplifiers, bi-stable fluid switches, proportional fluid ratio amplifiers, etc.) may be used in keeping with the principles of this disclosure.

Fluid which flows through the flow path 58 enters a flow chamber 84 via an inlet 86 which directs the fluid to enter the chamber generally tangentially (e.g., the chamber 84 is shaped similar to a cylinder, and the inlet 86 is aligned with a tangent to a circumference of the cylinder). As a result, the fluid will spiral about the chamber 84,

until it eventually exits via the outlet 40, as indicated schematically by arrow 90 in FIG. 3.

Fluid which flows through the flow path 60 enters the flow chamber 84 via an inlet 88 which directs the fluid to flow more directly toward the outlet 40 (e.g., in a radial direction, as indicated schematically by arrow 92 in FIG. 3). As will be readily appreciated, much less energy is consumed at the same flow rate when the fluid flows more directly toward the outlet 40 as compared to when the fluid flows less directly toward the outlet.

Thus, less resistance to flow is experienced when the fluid composition 36 flows more directly toward the outlet 40 and, conversely, more resistance to flow is experienced when the fluid composition flows less directly toward the outlet. Accordingly, working upstream from the outlet 40, less resistance to flow is experienced when a majority of the fluid composition 36 flows into the chamber 84 from the inlet 88, and through the flow path 60.

A majority of the fluid composition 36 flows through the flow path 60 when fluid exits the control port 80 at a greater rate or velocity as compared to fluid exiting the control port 82. More fluid exits the control port 80 when a majority of the fluid flowing from the passages 64, 68, 74 flows through the flow path 54.

A majority of the fluid flowing from the passages 64, 68, 74 flows through the flow path 54 when fluid exits the control port 70 at a greater rate or velocity as compared to fluid exiting the control port 66. More fluid exits the

control port 70 when a viscosity of the fluid composition 36 is above a selected level.

Thus, flow through the system 25 is resisted less when the fluid composition 36 has an increased viscosity (and a greater ratio of desired to undesired fluid therein). Flow through the system 25 is resisted more when the fluid composition 36 has a decreased viscosity.

More resistance to flow is experienced when the fluid composition 36 flows less directly toward the outlet 40 (e.g., as indicated by arrow 90). Thus, more resistance to flow is experienced when a majority of the fluid composition 36 flows into the chamber 84 from the inlet 86, and through the flow path 58.

A majority of the fluid composition 36 flows through the flow path 58 when fluid exits the control port 82 at a greater rate or velocity as compared to fluid exiting the control port 80. More fluid exits the control port 82 when a majority of the fluid flowing from the passages 64, 68, 74 flows through the flow path 56, instead of through the flow path 54.

A majority of the fluid flowing from the passages 64, 68, 74 flows through the flow path 56 when fluid exits the control port 66 at a greater rate or velocity as compared to fluid exiting the control port 70. More fluid exits the control port 66 when a viscosity of the fluid composition 36 is below a selected level.

As described above, the system 25 is configured to provide less resistance to flow when the fluid composition 36 has an increased viscosity, and more resistance to flow when the fluid composition has a decreased viscosity. This is beneficial when it is desired to flow more of a higher viscosity fluid, and less of a lower viscosity fluid (e.g., in order to produce more oil and less water or gas).

If it is desired to flow more of a lower viscosity fluid, and less of a higher viscosity fluid (e.g., in order to produce more gas and less water, or to inject more steam and less water), then the system 25 may be readily reconfigured for this purpose. For example, the inlets 86, 88 could conveniently be reversed, so that fluid which flows through the flow path 58 is directed to the inlet 88, and fluid which flows through the flow path 60 is directed to the inlet 86.

Referring additionally now to FIGS. 4A & B, another configuration of the flow chamber 84 is representatively illustrated, apart from the remainder of the variable flow resistance system 25. The flow chamber 84 of FIGS. 4A & B is similar in most respects to the flow chamber of FIG. 3, but differs at least in that one or more structures 94 are included in the chamber. As depicted in FIGS. 4A & B, the structure 94 may be considered as a single structure having one or more breaks or openings 96 therein, or as multiple structures separated by the breaks or openings.

The structure 94 induces any portion of the fluid composition 36 which flows circularly about the chamber 84,

and has a relatively high velocity, high density or low viscosity, to continue to flow circularly about the chamber, but at least one of the openings 96 permits more direct flow of the fluid composition from the inlet 88 to the outlet 40. Thus, when the fluid composition 36 enters the other inlet 86, it initially flows circularly in the chamber 84 about the outlet 40, and the structure 94 increasingly resists or impedes a change in direction of the flow of the fluid composition toward the outlet, as the velocity and/or density of the fluid composition increases, and/or as a viscosity of the fluid composition decreases. The openings 96, however, permit the fluid composition 36 to gradually flow spirally inward to the outlet 40.

In FIG. 4A, a relatively high velocity, low viscosity and/or high density fluid composition 36 enters the chamber 84 via the inlet 86. Some of the fluid composition 36 may also enter the chamber 84 via the inlet 88, but in this example, a substantial majority of the fluid composition enters via the inlet 86, thereby flowing tangential to the flow chamber 84 initially (i.e., at an angle of 0 degrees relative to a tangent to the outer circumference of the flow chamber).

Upon entering the chamber 84, the fluid composition 36 initially flows circularly about the outlet 40. For most of its path about the outlet 40, the fluid composition 36 is prevented, or at least impeded, from changing direction and flowing radially toward the outlet by the structure 94. The openings 96 do, however, gradually allow portions of

the fluid composition 36 to spiral radially inward toward the outlet 40.

In FIG. 4B, a relatively low velocity, high viscosity and/or low density fluid composition 36 enters the chamber 84 via the inlet 88. Some of the fluid composition 36 may also enter the chamber 84 via the inlet 86, but in this example, a substantial majority of the fluid composition enters via the inlet 88, thereby flowing radially through the flow chamber 84 (i.e., at an angle of 90 degrees relative to a tangent to the outer circumference of the flow chamber).

One of the openings 96 allows the fluid composition 36 to flow more directly from the inlet 88 to the outlet 40. Thus, radial flow of the fluid composition 36 toward the outlet 40 in this example is not resisted or impeded significantly by the structure 94.

If a portion of the relatively low velocity, high viscosity and/or low density fluid composition 36 should flow circularly about the outlet 40 in FIG. 4B, the openings 96 will allow the fluid composition to readily change direction and flow more directly toward the outlet. Indeed, as a viscosity of the fluid composition 36 increases, or as a density or velocity of the fluid composition decreases, the structures 94 in this situation will increasingly impede the circular flow of the fluid composition 36 about the chamber 84, enabling the fluid composition to more readily change direction and flow through the openings 96.

Note that it is not necessary for multiple openings 96 to be provided in the structure 94, since the fluid composition 36 could flow more directly from the inlet 88 to the outlet 40 via a single opening, and a single opening could also allow flow from the inlet 86 to gradually spiral inwardly toward the outlet. Any number of openings 96 (or other areas of low resistance to radial flow) could be provided in keeping with the principles of this disclosure.

Furthermore, it is not necessary for one of the openings 96 to be positioned directly between the inlet 88 and the outlet 40. The openings 96 in the structure 94 can provide for more direct flow of the fluid composition 36 from the inlet 88 to the outlet 40, even if some circular flow of the fluid composition about the structure is needed for the fluid composition to flow inward through one of the openings.

It will be appreciated that the more circuitous flow of the fluid composition 36 in the FIG. 4A example results in more energy being consumed at the same flow rate and, therefore, more resistance to flow of the fluid composition as compared to the example of FIG. 4B. If oil is a desired fluid, and water and/or gas are undesired fluids, then it will be appreciated that the variable flow resistance system 25 of FIGS. 4A & B will provide less resistance to flow of the fluid composition 36 when it has an increased ratio of desired to undesired fluid therein, and will provide greater resistance to flow when the fluid

composition has a decreased ratio of desired to undesired fluid therein.

Referring additionally now to FIG. 5, another configuration of the chamber 84 is representatively  
5 illustrated. In this configuration, the chamber 84 includes four of the structures 94, which are equally spaced apart by four openings 96. The structures 94 may be equally or unequally spaced apart, depending on the desired operational parameters of the system 25.

10 Referring additionally now to FIGS. 6A & B, another configuration of the variable flow resistance system 25 is representatively illustrated. The variable flow resistance system 25 of FIGS. 6A & B differs substantially from that of FIG. 3, at least in that it is much less complex and has  
15 many fewer components. Indeed, in the configuration of FIGS. 6A & B, only the chamber 84 is interposed between the inlet 38 and the outlet 40 of the system 25.

The chamber 84 in the configuration of FIGS. 6A & B has only a single inlet 86. The chamber 84 also includes  
20 the structures 94 therein.

In FIG. 6A, a relatively high velocity, low viscosity and/or high density fluid composition 36 enters the chamber 84 via the inlet 86 and is influenced by the structure 94 to continue to flow about the chamber. The fluid  
25 composition 36, thus, flows circuitously through the chamber 84, eventually spiraling inward to the outlet 40 as it gradually bypasses the structure 94 via the openings 96.

In FIG. 6B, however, the fluid composition 36 has a lower velocity, increased viscosity and/or decreased density. The fluid composition 36 in this example is able to change direction more readily as it flows into the chamber 84 via the inlet 86, allowing it to flow more directly from the inlet to the outlet 40 via the openings 96.

It will be appreciated that the much more circuitous flow path taken by the fluid composition 36 in the example of FIG. 6A consumes more of the fluid composition's energy at the same flow rate and, thus, results in more resistance to flow, as compared to the much more direct flow path taken by the fluid composition in the example of FIG. 6B. If oil is a desired fluid, and water and/or gas are undesired fluids, then it will be appreciated that the variable flow resistance system 25 of FIGS. 6A & B will provide less resistance to flow of the fluid composition 36 when it has an increased ratio of desired to undesired fluid therein, and will provide greater resistance to flow when the fluid composition has a decreased ratio of desired to undesired fluid therein.

Although in the configuration of FIGS. 6A & B, only a single inlet 86 is used for admitting the fluid composition 36 into the chamber 84, in other examples multiple inlets could be provided, if desired. The fluid composition 36 could flow into the chamber 84 via multiple inlets simultaneously or separately. For example, different inlets could be used for when the fluid composition 36 has

corresponding different characteristics (such as different velocities, viscosities, densities, etc.).

The structure 94 may be in the form of one or more circumferentially extending vanes having one or more of the openings 96 between the vane(s). Alternatively, or in addition, the structure 94 could be in the form of one or more circumferentially extending recesses in one or more walls of the chamber 84. The structure 94 could project inwardly and/or outwardly relative to one or more walls of the chamber 84. Thus, it will be appreciated that any type of structure which functions to increasingly influence the fluid composition 36 to continue to flow circuitously about the chamber 84 as the velocity or density of the fluid composition increases, or as a viscosity of the fluid decreases, and/or which functions to increasingly impede circular flow of the fluid composition about the chamber as the velocity or density of the fluid composition decreases, or as a viscosity of the fluid increases, may be used in keeping with the principles of this disclosure.

Several illustrative schematic examples of the structure 94 are depicted in FIGS. 7A-J, with the cross-sectional views of FIGS. 7A-G being taken along line 7-7 of FIG. 4B. These various examples demonstrate that a great variety of possibilities exist for constructing the structure 94, and so it should be appreciated that the principles of this disclosure are not limited to use of any particular structure configuration in the chamber 84.

In FIG. 7A, the structure 94 comprises a wall or vane which extends between upper and lower (as viewed in the drawings) walls 98, 100 of the chamber 84. The structure 94 in this example precludes radially inward flow of the fluid composition 36 from an outer portion of the chamber 84, except at the opening 96.

In FIG. 7B, the structure 94 comprises a wall or vane which extends only partially between the walls 98, 100 of the chamber 84. The structure 94 in this example does not preclude radially inward flow of the fluid composition 36, but does resist a change in direction from circular to radial flow in the outer portion of the chamber 84.

One inlet (such as inlet 88) could be positioned at a height relative to the chamber walls 98, 100 so that the fluid composition 36 entering the chamber 84 via that inlet does not impinge substantially on the structure 94 (e.g., flowing over or under the structure). Another inlet (such as the inlet 86) could be positioned at a different height, so that the fluid composition 36 entering the chamber 84 via that inlet does impinge substantially on the structure 94. More resistance to flow would be experienced by the fluid composition 36 impinging on the structure.

In FIG. 7C, the structure 94 comprises whiskers, bristles or stiff wires which resist radially inward flow of the fluid composition 36 from the outer portion of the chamber 84. The structure 94 in this example may extend completely or partially between the walls 98, 100 of the chamber 84, and may extend inwardly from both walls.

In FIG. 7D, the structure 94 comprises multiple circumferentially extending recesses and projections which resist radially inward flow of the fluid composition 36. Either or both of the recesses and projections may be provided in the chamber 84. If only the recesses are provided, then the structure 94 may not protrude into the chamber 84 at all.

In FIG. 7E, the structure 94 comprises multiple circumferentially extending undulations formed on the walls 98, 100 of the chamber 84. Similar to the configuration of FIG. 7D, the undulations include recesses and projections, but in other examples either or both of the recesses and projections may be provided. If only the recesses are provided, then the structure 94 may not protrude into the chamber 84 at all.

In FIG. 7F, the structure 94 comprises circumferentially extending but radially offset walls or vanes extending inwardly from the walls 98, 100 of the chamber 84. Any number, arrangement and/or configuration of the walls or vanes may be used, in keeping with the principles of this disclosure.

In FIGS. 7G & H, the structure 94 comprises a wall or vane extending inwardly from the chamber wall 100, with another vane 102 which influences the fluid composition 36 to change direction axially relative to the outlet 40. For example, the vane 102 could be configured so that it directs the fluid composition 36 to flow axially away from, or toward, the outlet 40.

The vane 102 could be configured so that it accomplishes mixing of the fluid composition 36 received from multiple inlets, increases resistance to flow of fluid circularly in the chamber 84, and/or provides resistance to flow of fluid at different axial levels of the chamber, etc. Any number, arrangement, configuration, etc. of the vane 102 may be used, in keeping with the principles of this disclosure.

The vane 102 can provide greater resistance to circular flow of increased viscosity fluids, so that such fluids are more readily diverted toward the outlet 40. Thus, while the structure 94 increasingly impedes a fluid composition 36 having increased velocity, increased density or reduced viscosity from flowing radially inward toward the outlet 40, the vane 102 can increasingly resist circular flow of an increased viscosity fluid composition.

One inlet (such as inlet 88) could be positioned at a height relative to the chamber walls 98, 100 so that the fluid composition 36 entering the chamber 84 via that inlet does not impinge substantially on the structure 94 (e.g., flowing over or under the structure). Another inlet (such as the inlet 86) could be positioned at a different height, so that the fluid composition 36 entering the chamber 84 via that inlet does impinge substantially on the structure 94.

In FIG. 7I, the structure 94 comprises a one-piece cylindrical-shaped wall with the openings 96 being distributed about the wall, at alternating upper and lower

ends of the wall. The structure 94 would be positioned between the end walls 98, 100 of the chamber 84.

In FIG. 7J, the structure 94 comprises a one-piece cylindrical-shaped wall, similar to that depicted in FIG. 7J, except that the openings 96 are distributed about the wall midway between its upper and lower ends.

Additional configurations of the flow chamber 84 and structures 94 therein are representatively illustrated in FIGS. 8A-11. These additional configurations demonstrate that a wide variety of different configurations are possible without departing from the principles of this disclosure, and those principles are not limited at all to the specific examples described herein and depicted in the drawings.

In FIG. 8A, the chamber 84 is similar in most respects to that of FIGS. 4A-5, with two inlets 86, 88. A majority of the fluid composition 36 having a relatively high velocity, low viscosity and/or high density flows into the chamber 84 via the inlet 86 and flows circularly about the outlet 40. The structures 94 impede radially inward flow of the fluid composition 36 toward the outlet 40.

In FIG. 8B, a majority of the fluid composition 36 having a relatively low velocity, high viscosity and/or low density flows into the chamber 84 via the inlet 88. One of the structures 94 prevents direct flow of the fluid composition 36 from the inlet 88 to the outlet 40, but the fluid composition can readily change direction to flow

around each of the structures. Thus, a flow resistance of the system 25 of FIG. 8B is less than that of FIG. 8A.

In FIG. 9A, the chamber 84 is similar in most respects to that of FIGS. 6A & B, with a single inlet 86. The fluid composition 36 having a relatively high velocity, low viscosity and/or high density flows into the chamber 84 via the inlet 86 and flows circularly about the outlet 40. The structure 94 impedes radially inward flow of the fluid composition 36 toward the outlet 40.

In FIG. 9B, the fluid composition 36 having a relatively low velocity, high viscosity and/or low density flows into the chamber 84 via the inlet 86. The structure 94 prevents direct flow of the fluid composition 36 from the inlet 88 to the outlet 40, but the fluid composition can readily change direction to flow around the structure and through the opening 96 toward the outlet. Thus, a flow resistance of the system 25 of FIG. 9B is less than that of FIG. 9A.

It is postulated that, by preventing flow of the relatively low velocity, high viscosity and/or low density fluid composition 36 directly to the outlet 40 from the inlet 88 in FIG. 8B, or from the inlet 86 in FIG. 9B, the radial velocity of the fluid composition toward the outlet can be desirably decreased, without significantly increasing the flow resistance of the system 25.

In FIGS. 10 & 11, the chamber 84 is similar in most respects to the configuration of FIGS. 4A-5, with two inlets 86, 88. Fluid composition 36 which flows into the

chamber 84 via the inlet 86 will, at least initially, flow circularly about the outlet 40, whereas fluid composition which flows into the chamber via the inlet 88 will flow more directly toward the outlet.

5 Multiple cup-like structures 94 are distributed about the chamber 84 in the FIG. 10 configuration, and multiple structures are located in the chamber in the FIG. 11 configuration. These structures 94 can increasingly impede circular flow of the fluid composition 36 about the outlet  
10 40 when the fluid composition has a decreased velocity, increased viscosity and/or decreased density. In this manner, the structures 94 can function to stabilize the flow of relatively low velocity, high viscosity and/or low density fluid in the chamber 84, even though the structures  
15 do not significantly impede circular flow of relatively high velocity, low viscosity and/or high density fluid about the outlet 40.

Many other possibilities exist for the placement, configuration, number, etc. of the structures 94 in the  
20 chamber 84. For example, the structures 94 could be aerofoil-shaped or cylinder-shaped, the structures could comprise grooves oriented radially relative to the outlet 40, etc. Any arrangement, position and/or combination of structures 94 may be used in keeping with the principles of  
25 this disclosure.

It may now be fully appreciated that this disclosure provides several advancements to the art of regulating fluid flow in a subterranean well. The various

configurations of the variable flow resistance system 25 described above enable control of desired and undesired fluids in a well, without use of complex, expensive or failure-prone mechanisms. Instead, the system 25 is  
5 relatively straightforward and inexpensive to produce, operate and maintain, and is reliable in operation.

The above disclosure provides to the art a variable flow resistance system 25 for use in a subterranean well. The system 25 includes a flow chamber 84 through which a  
10 fluid composition 36 flows. The chamber 84 has at least one inlet 86, 88, an outlet 40, and at least one structure 94 which impedes a change from circular flow of the fluid composition 36 about the outlet 40 to radial flow toward the outlet 40.

15 The fluid composition 36 can flow through the flow chamber 84 in the well.

The structure 94 can increasingly impede a change from circular flow of the fluid composition 36 about the outlet 40 to radial flow toward the outlet 40 in response to at  
20 least one of a) increased velocity of the fluid composition 36, b) decreased viscosity of the fluid composition 36, c) increased density of the fluid composition 36, d) a reduced ratio of desired fluid to undesired fluid in the fluid composition 36, e) decreased angle of entry of the fluid  
25 composition 36 into the chamber 84, and f) more substantial impingement of the fluid composition 36 on the structure 94.

The structure 94 may have at least one opening 96 which permits the fluid composition 36 to change direction and flow more directly from the inlet 86, 88 to the outlet 40.

5       The at least one inlet can comprise at least first and second inlets, wherein the first inlet 88 directs the fluid composition 36 to flow more directly toward the outlet 40 of the chamber 84 as compared to the second inlet 86.

10       The at least one inlet can comprises only a single inlet 86.

The structure 94 may comprise at least one of a vane and a recess.

The structure 94 may project at least one of inwardly and outwardly relative to a wall 98, 100 of the chamber 84.

15       The fluid composition 36 may exit the chamber 84 via the outlet 40 in a direction which changes based on a ratio of desired fluid to undesired fluid in the fluid composition 36.

20       The fluid composition 36 may flow more directly from the inlet 86, 88 to the outlet 40 as the viscosity of the fluid composition 36 increases, as the velocity of the fluid composition 36 decreases, as the density of the fluid composition 36 decreases, as the ratio of desired fluid to undesired fluid in the fluid composition 36 increases,  
25       and/or as an angle of entry of the fluid composition 36 increases.

The structure 94 may reduce or increase the velocity of the fluid composition 36 as it flows from the inlet 86 to the outlet 40.

The above disclosure also provides to the art a  
5 variable flow resistance system 25 which comprises a flow chamber 84 through which a fluid composition 36 flows. The chamber 84 has at least one inlet 86, 88, an outlet 40, and at least one structure 94 which impedes circular flow of the fluid composition 36 about the outlet 40.

10 Also described above is a variable flow resistance system 25 for use in a subterranean well, with the system comprising a flow chamber 84 including an outlet 40 and at least one structure 94 which resists a change in a direction of flow of a fluid composition 36 toward the  
15 outlet 40. The fluid composition 36 enters the chamber 84 in a direction of flow which changes based on a ratio of desired fluid to undesired fluid in the fluid composition 36.

20 The fluid composition 36 may exit the chamber via the outlet 40 in a direction which changes based on a ratio of desired fluid to undesired fluid in the fluid composition 36.

25 The structure 94 can impede a change from circular flow of the fluid composition 36 about the outlet 40 to radial flow toward the outlet 40.

The structure 94 may have at least one opening 96 which permits the fluid composition 36 to flow directly

from a first inlet 88 of the chamber 84 to the outlet 40. The first inlet 88 can direct the fluid composition 36 to flow more directly toward the outlet 40 of the chamber 84 as compared to a second inlet 86.

5       The opening 96 in the structure 94 may permit direct flow of the fluid composition 36 from the first inlet 88 to the outlet 40. In one example described above, the chamber 84 includes only one inlet 86.

10       The structure 94 may comprise a vane or a recess. The structure 94 can project inwardly or outwardly relative to one or more walls 98, 100 of the chamber 84.

15       The fluid composition 36 may flow more directly from an inlet 86 of the chamber 84 to the outlet 40 as a viscosity of the fluid composition 36 increases, as a velocity of the fluid composition 36 decreases, as a density of the fluid composition 36 increases, as a ratio of desired fluid to undesired fluid in the fluid composition 36 increases, as an angle of entry of the fluid composition 36 increases, and/or as the fluid composition 20 36 impingement on the structure 94 decreases.

25       The structure 94 may induce portions of the fluid composition 36 which flow circularly about the outlet 40 to continue to flow circularly about the outlet 40. The structure 94 preferably impedes a change from circular flow of the fluid composition 36 about the outlet 40 to radial flow toward the outlet 40.

Also described by the above disclosure is a variable flow resistance system 25 which includes a flow chamber 84 through which a fluid composition 36 flows. The chamber 84 has at least one inlet 86, 88, an outlet 40, and at least one structure 94 which impedes a change from circular flow of the fluid composition 36 about the outlet 40 to radial flow toward the outlet 40.

The above disclosure also describes a variable flow resistance system 25 which includes a flow path selection device 52 that selects which of multiple flow paths 58, 60 a majority of fluid flows through from the device 52, based on a ratio of desired fluid to undesired fluid in a fluid composition 36. A flow chamber 84 of the system 25 includes an outlet 40, a first inlet 88 connected to a first one of the flow paths 60, a second inlet 86 connected to a second one of the flow paths 58, and at least one structure 94 which impedes radial flow of the fluid composition 36 from the second inlet 86 to the outlet 40 more than it impedes radial flow of the fluid composition 36 from the first inlet 88 to the outlet 40.

It is to be understood that the various examples described above may be utilized in various orientations, such as inclined, inverted, horizontal, vertical, etc., and in various configurations, without departing from the principles of the present disclosure. The embodiments illustrated in the drawings are depicted and described merely as examples of useful applications of the principles

of the disclosure, which are not limited to any specific details of these embodiments.

Of course, a person skilled in the art would, upon a careful consideration of the above description of  
5 representative embodiments, readily appreciate that many modifications, additions, substitutions, deletions, and other changes may be made to these specific embodiments, and such changes are within the scope of the principles of the present disclosure. Accordingly, the foregoing  
10 detailed description is to be clearly understood as being given by way of illustration and example only, the spirit and scope of the present invention being limited solely by the appended claims and their equivalents.

**WHAT IS CLAIMED IS:**

1. A variable flow resistance system for use in a subterranean well, the system comprising:

5 a flow chamber through which a fluid composition flows, the chamber having at least one inlet, an outlet, and at least one structure which impedes a change from circular flow of the fluid composition about the outlet to radial flow toward the outlet.

10

2. The system of claim 1, wherein the fluid composition flows through the flow chamber in the well.

3. The system of claim 1, wherein the structure  
15 increasingly impedes the change from circular flow of the fluid composition about the outlet to radial flow toward the outlet in response to at least one of a) increased velocity of the fluid composition, b) decreased viscosity of the fluid composition, c) a reduced ratio of desired  
20 fluid to undesired fluid in the fluid composition, d) a decreased angle of entry of the fluid composition into the flow chamber, and e) an increased impingement of the fluid composition on the structure.

25 4. The system of claim 1, wherein the at least one inlet comprises only a single inlet.

5. The system of claim 1, wherein the structure comprises at least one of a vane and a recess.

5 6. The system of claim 1, wherein the structure projects at least one of inwardly and outwardly relative to a wall of the chamber.

7. The system of claim 1, wherein the fluid  
10 composition exits the chamber via the outlet at an angle which changes based on a ratio of desired fluid to undesired fluid in the fluid composition.

8. The system of claim 1, wherein the fluid  
15 composition flows more directly from the inlet to the outlet as a viscosity of the fluid composition increases.

9. The system of claim 1, wherein the fluid  
composition flows more directly from the inlet to the  
20 outlet as a velocity of the fluid composition decreases.

10. The system of claim 1, wherein the fluid  
composition flows more directly from the inlet to the  
outlet as an angle of entry of the fluid composition  
25 increases.

11. The system of claim 1, wherein the fluid  
composition flows more directly from the inlet to the  
outlet as a ratio of desired fluid to undesired fluid in  
5 the fluid composition increases.

12. The system of claim 1, wherein the structure  
increases a velocity of the fluid composition as it flows  
from the inlet to the outlet.

10

13. A variable flow resistance system for use in a subterranean well, the system comprising:

5 a flow chamber through which a fluid composition flows in the well, the chamber having at least one inlet, an outlet, and at least one structure which impedes circular flow of the fluid composition about the outlet.

10 14. The system of claim 13, wherein the fluid composition flows through the flow chamber in the well.

15 15. The system of claim 13, wherein the structure increasingly impedes the circular flow of the fluid composition about the outlet in response to at least one of a) decreased velocity of the fluid composition, b) increased viscosity of the fluid composition, c) an increased ratio of desired fluid to undesired fluid in the fluid composition, d) a decreased angle of entry of the fluid composition into the flow chamber, and e) an  
20 increased impingement of the fluid composition on the structure.

25 16. The system of claim 13, wherein the structure has at least one opening which permits the fluid composition to change direction and flow more directly from the inlet to the outlet.

17. The system of claim 13, wherein the at least one inlet comprises at least first and second inlets, wherein the first inlet directs the fluid composition to flow more directly toward the outlet of the chamber as compared to  
5 the second inlet.

18. The system of claim 13, wherein the at least one inlet comprises a single inlet.

10 19. The system of claim 13, wherein the structure comprises at least one of a vane and a recess.

20. The system of claim 13, wherein the structure projects at least one of inwardly and outwardly relative to  
15 a wall of the chamber.

21. The system of claim 13, wherein the fluid composition exits the chamber via the outlet at an angle which changes based on a ratio of desired fluid to  
20 undesired fluid in the fluid composition.

22. The system of claim 13, wherein the fluid composition flows more directly from the inlet to the outlet as the viscosity of the fluid composition increases.

25

23. The system of claim 13, wherein the fluid composition flows more directly from the inlet to the outlet as a velocity of the fluid composition decreases.

5        24. The system of claim 13, wherein the fluid composition flows more directly from the inlet to the outlet as an angle of entry of the fluid composition increases.

10       25. The system of claim 13, wherein the fluid composition flows more directly from the inlet to the outlet as a ratio of desired fluid to undesired fluid in the fluid composition increases.

15       26. The system of claim 13, wherein the structure reduces a velocity of the fluid composition as it flows from the inlet to the outlet.

27. A variable flow resistance system for use in a subterranean well, the system comprising:

5 a flow chamber including an outlet and at least one structure which resists a change in a direction of flow of a fluid composition toward the outlet, and

wherein the fluid composition enters the chamber in the direction of flow which changes based on a ratio of desired fluid to undesired fluid in the fluid composition.

10

28. The system of claim 27, wherein the structure impedes a change from circular flow of the fluid composition about the outlet to radial flow toward the outlet.

15

29. The system of claim 27, wherein the structure has at least one opening which permits a change from circular flow of the fluid composition about the outlet to radial flow toward the outlet.

20

30. The system of claim 29, wherein the opening in the structure permits more direct flow of the fluid composition from an inlet to the outlet.

25

31. The system of claim 30, wherein the fluid composition flows into the chamber only via the inlet.

32. The system of claim 27, wherein the structure comprises at least one of a vane and a recess.

5        33. The system of claim 27, wherein the structure projects at least one of inwardly and outwardly relative to a wall of the chamber.

10       34. The system of claim 27, wherein the fluid composition flows more directly from an inlet of the chamber to the outlet as a viscosity of the fluid composition increases.

15       35. The system of claim 27, wherein the fluid composition flows more directly from an inlet of the chamber to the outlet as a velocity of the fluid composition decreases.

20       36. The system of claim 27, wherein the fluid composition flows more directly from an inlet of the chamber to the outlet as an angle of entry of the fluid composition increases.

25       37. The system of claim 27, wherein the fluid composition flows more directly from an inlet of the

chamber to the outlet as a ratio of desired fluid to undesired fluid in the fluid composition increases.

38. The system of claim 27, wherein the structure  
5 increasingly impedes a change in direction of the fluid  
composition from circular flow of the fluid composition  
about the outlet to radial flow toward the outlet as a  
velocity of the fluid composition increases, a viscosity of  
the fluid composition decreases, an angle of entry of the  
10 fluid composition decreases, a ratio of desired fluid to  
undesired fluid decreases, and impingement of the fluid  
composition on the structure increases.

39. The system of claim 27, wherein the structure  
15 increasingly causes a change in direction of the fluid  
composition from circular flow of the fluid composition  
about the outlet to radial flow toward the outlet as a  
velocity of the fluid composition decreases, a viscosity of  
the fluid composition increases, an angle of entry of the  
20 fluid composition increases and a ratio of desired fluid to  
undesired fluid increases.

40. The system of claim 27, wherein the structure  
increases a velocity of the fluid composition as it flows  
25 from an inlet to the outlet.

41. The system of claim 27, wherein the structure reduces a velocity of the fluid composition as it flows from an inlet to the outlet.

42. A variable flow resistance system for use in a subterranean well, the system comprising:

a flow path selection device that selects which of multiple flow paths a majority of fluid flows through from the device, based on a ratio of desired fluid to undesired fluid in a fluid composition; and

a flow chamber having an outlet, a first inlet connected to a first one of the flow paths, a second inlet connected to a second one of the flow paths, and at least one structure which impedes radial flow of the fluid composition from the second inlet to the outlet more than it impedes radial flow of the fluid composition from the first inlet to the outlet.

43. The system of claim 42, wherein the structure has at least one opening which permits the fluid composition to change direction and flow more directly from the first inlet to the outlet.

44. The system of claim 42, wherein the first inlet directs the fluid composition to flow more directly toward the outlet of the chamber as compared to the second inlet.

45. The system of claim 42, wherein the structure comprises at least one of a vane and a recess.

46. The system of claim 42, wherein the structure projects at least one of inwardly and outwardly relative to a wall of the chamber.

5           47. The system of claim 42, wherein the structure induces portions of the fluid composition which flow circularly about the outlet to continue to flow circularly about the outlet.

10           48. The system of claim 42, wherein the structure increasingly impedes a change from circular flow of the fluid composition about the outlet to radial flow toward the outlet in response to at least one of a) increased velocity of the fluid composition, b) decreased viscosity  
15 of the fluid composition, c) a reduced ratio of desired fluid to undesired fluid in the fluid composition, d) decreased angle of entry of the fluid composition, and e) increased impingement of the fluid composition on the structure.

20           49. The system of claim 42, wherein a structure in the chamber increases a velocity of the fluid composition as it flows to the outlet.

**ABSTRACT OF THE DISCLOSURE**

A variable flow resistance system for use in a  
5 subterranean well can include a flow chamber having an  
outlet and at least one structure which resists a change in  
a direction of flow of a fluid composition toward the  
outlet. The fluid composition may enter the chamber in the  
direction of flow which changes based on a ratio of desired  
10 fluid to undesired fluid in the fluid composition. Another  
variable flow resistance system can include a flow chamber  
through which a fluid composition flows, the chamber having  
an inlet, an outlet, and a structure which impedes a change  
from circular flow about the outlet to radial flow toward  
15 the outlet.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN  
APPLICATION DATA SHEET (37 CFR 1.76)**

|                               |                                                                                                                                           |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Title of<br/>Invention</b> | <b>VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION INDUCING<br/>STRUCTURE THEREIN TO VARIABLY RESIST FLOW IN A SUBTERRANEAN<br/>WELL</b> |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|

As the below named inventor(s), I/we declare that:

This declaration is directed to:

- ☒ The attached application, or
- ☐ Application No. \_\_\_\_\_ filed on \_\_\_\_\_
- ☐ As amended on \_\_\_\_\_ (if applicable);

I/we believe that I/we am/are the original and first inventor(s) of the subject matter which is claimed and for which a patent is sought;

I/we have reviewed and understand the contents of the above-identified application, including the claims, as amended by any amendment specifically referred to above;

I/we acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me/us to be material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT International filing date of the continuation-in-part application.

**WARNING:**

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

All statements made herein of my/our own knowledge are true, all statements made herein on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and may jeopardize the validity of the application or any patent issuing thereon.

**FULL NAME OF INVENTOR(S)**Inventor one: Jason D. DYKSTRA Date: \_\_\_\_\_Signature: \_\_\_\_\_ Citizen of: USInventor two: Michael L. FRIPP Date: \_\_\_\_\_Signature: \_\_\_\_\_ Citizen of: US☐ Additional inventors or a legal representative are being named on \_\_\_\_\_ additional form(s) attached hereto.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.


If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

## Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.







FIG. 2



+




FIG. 4B






FIG. 4A

+

+



+

+

6/7




FIG. 6B




FIG. 6A

+




FIG. 7D




FIG. 7E




FIG. 7F




FIG. 7G




FIG. 7H




FIG. 7I






FIG. 7J






FIG. 9B




FIG. 9A




FIG. 10




FIG. 11

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                            |                        |                      |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------|
| <b>Application Data Sheet 37 CFR 1.76</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                            | Attorney Docket Number | 2010-IP-033103 U1 US |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                            | Application Number     |                      |
| Title of Invention                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION INDUCING STRUCTURE THEREIN TO VARIABLY RESIST FLOW IN A SUBTERRANEAN WELL |                        |                      |
| <p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p> |                                                                                                                            |                        |                      |

**Secrecy Order 37 CFR 5.2**

|                          |                                                                                                                                                                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> | Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.) |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Applicant Information:**

|                                                                                                                                                                                 |                   |                                           |                    |                                                                |                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------|--------------------|----------------------------------------------------------------|-------------------------------------------------------------|
| <b>Applicant 1</b>                                                                                                                                                              |                   |                                           |                    |                                                                | <b>Remove</b>                                               |
| <b>Applicant Authority</b>                                                                                                                                                      |                   | <input checked="" type="radio"/> Inventor |                    | <input type="radio"/> Legal Representative under 35 U.S.C. 117 | <input type="radio"/> Party of Interest under 35 U.S.C. 118 |
| <b>Prefix</b>                                                                                                                                                                   | <b>Given Name</b> | <b>Middle Name</b>                        | <b>Family Name</b> | <b>Suffix</b>                                                  |                                                             |
|                                                                                                                                                                                 | Jason             | D.                                        | DYKSTRA            |                                                                |                                                             |
| <b>Residence Information (Select One)</b> <input checked="" type="radio"/> US Residency <input type="radio"/> Non US Residency <input type="radio"/> Active US Military Service |                   |                                           |                    |                                                                |                                                             |
| <b>City</b>                                                                                                                                                                     | Carrollton        | <b>State/Province</b>                     | TX                 | <b>Country of Residence i</b>                                  | US                                                          |
| <b>Citizenship under 37 CFR 1.41(b) i</b>                                                                                                                                       |                   | US                                        |                    |                                                                |                                                             |
| <b>Mailing Address of Applicant:</b>                                                                                                                                            |                   |                                           |                    |                                                                |                                                             |
| <b>Address 1</b>                                                                                                                                                                |                   | 2601 Belt Line Road                       |                    |                                                                |                                                             |
| <b>Address 2</b>                                                                                                                                                                |                   |                                           |                    |                                                                |                                                             |
| <b>City</b>                                                                                                                                                                     | Carrollton        | <b>State/Province</b>                     | TX                 |                                                                |                                                             |
| <b>Postal Code</b>                                                                                                                                                              | 75006             | <b>Country i</b>                          | US                 |                                                                |                                                             |
| <b>Applicant 2</b>                                                                                                                                                              |                   |                                           |                    |                                                                | <b>Remove</b>                                               |
| <b>Applicant Authority</b>                                                                                                                                                      |                   | <input checked="" type="radio"/> Inventor |                    | <input type="radio"/> Legal Representative under 35 U.S.C. 117 | <input type="radio"/> Party of Interest under 35 U.S.C. 118 |
| <b>Prefix</b>                                                                                                                                                                   | <b>Given Name</b> | <b>Middle Name</b>                        | <b>Family Name</b> | <b>Suffix</b>                                                  |                                                             |
|                                                                                                                                                                                 | Michael           | L.                                        | FRIPP              |                                                                |                                                             |
| <b>Residence Information (Select One)</b> <input checked="" type="radio"/> US Residency <input type="radio"/> Non US Residency <input type="radio"/> Active US Military Service |                   |                                           |                    |                                                                |                                                             |
| <b>City</b>                                                                                                                                                                     | Carrollton        | <b>State/Province</b>                     | TX                 | <b>Country of Residence i</b>                                  | US                                                          |
| <b>Citizenship under 37 CFR 1.41(b) i</b>                                                                                                                                       |                   | US                                        |                    |                                                                |                                                             |
| <b>Mailing Address of Applicant:</b>                                                                                                                                            |                   |                                           |                    |                                                                |                                                             |
| <b>Address 1</b>                                                                                                                                                                |                   | 2601 Belt Line Road                       |                    |                                                                |                                                             |
| <b>Address 2</b>                                                                                                                                                                |                   |                                           |                    |                                                                |                                                             |
| <b>City</b>                                                                                                                                                                     | Carrollton        | <b>State/Province</b>                     | TX                 |                                                                |                                                             |
| <b>Postal Code</b>                                                                                                                                                              | 75006             | <b>Country i</b>                          | US                 |                                                                |                                                             |
| All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button.                                            |                   |                                           |                    |                                                                |                                                             |
|                                                                                                                                                                                 |                   |                                           |                    |                                                                | <b>Add</b>                                                  |

**Correspondence Information:**

|                                                                                                                                       |                                                                                      |
|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Enter either Customer Number or complete the Correspondence Information section below.<br>For further information see 37 CFR 1.33(a). |                                                                                      |
| <input type="checkbox"/>                                                                                                              | An Address is being provided for the correspondence Information of this application. |

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

|                                           |                                                                                                                            |                        |                                          |                                             |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------------------------|---------------------------------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                                                                                                                            | Attorney Docket Number | 2010-IP-033103 U1 US                     |                                             |
|                                           |                                                                                                                            | Application Number     |                                          |                                             |
| Title of Invention                        | VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION INDUCING STRUCTURE THEREIN TO VARIABLY RESIST FLOW IN A SUBTERRANEAN WELL |                        |                                          |                                             |
| Customer Number                           | 49431                                                                                                                      |                        |                                          |                                             |
| Email Address                             | mail@smithipservices.com                                                                                                   |                        | <input type="button" value="Add Email"/> | <input type="button" value="Remove Email"/> |

**Application Information:**

|                                         |                                                                                                                            |                                           |                          |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|--------------------------|
| Title of the Invention                  | VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION INDUCING STRUCTURE THEREIN TO VARIABLY RESIST FLOW IN A SUBTERRANEAN WELL |                                           |                          |
| Attorney Docket Number                  | 2010-IP-033103 U1 US                                                                                                       | Small Entity Status Claimed               | <input type="checkbox"/> |
| Application Type                        | Nonprovisional                                                                                                             |                                           |                          |
| Subject Matter                          | Utility                                                                                                                    |                                           |                          |
| Suggested Class (if any)                | 166                                                                                                                        | Sub Class (if any)                        | 25015                    |
| Suggested Technology Center (if any)    |                                                                                                                            |                                           |                          |
| Total Number of Drawing Sheets (if any) | 12                                                                                                                         | Suggested Figure for Publication (if any) |                          |

**Publication Information:**

|                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> Request Early Publication (Fee required at time of Request 37 CFR 1.219)                                                                                                                                                                                                                                                                                                               |
| <input type="checkbox"/> <b>Request Not to Publish.</b> I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing. |

**Representative Information:**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                  |                                              |                                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------|---------------------------------------------------------|
| Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Enter either Customer Number or complete the Representative Name section below. If both sections are completed the Customer Number will be used for the Representative Information during processing. |                                                  |                                              |                                                         |
| Please Select One:                                                                                                                                                                                                                                                                                                                                                                                                                                              | <input checked="" type="radio"/> Customer Number | <input type="radio"/> US Patent Practitioner | <input type="radio"/> Limited Recognition (37 CFR 11.9) |
| Customer Number                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 49431                                            |                                              |                                                         |

**Domestic Benefit/National Stage Information:**

|                                                                                                                                                                                                                                                                                                                                                                                                        |                         |                                       |                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------------------------------------|------------------------------------|
| This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78(a)(2) or CFR 1.78(a)(4), and need not otherwise be made part of the specification. |                         |                                       |                                    |
| Prior Application Status                                                                                                                                                                                                                                                                                                                                                                               | Pending                 | <input type="button" value="Remove"/> |                                    |
| Application Number                                                                                                                                                                                                                                                                                                                                                                                     | Continuity Type         | Prior Application Number              | Filing Date (YYYY-MM-DD)           |
|                                                                                                                                                                                                                                                                                                                                                                                                        | Continuation in part of |                                       |                                    |
| Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the Add button.                                                                                                                                                                                                                                                                                         |                         |                                       | <input type="button" value="Add"/> |

**Foreign Priority Information:**

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

|                                           |                                                                                                                            |                        |                      |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                                                                                                                            | Attorney Docket Number | 2010-IP-033103 U1 US |
|                                           |                                                                                                                            | Application Number     |                      |
| Title of Invention                        | VARIABLE FLOW RESISTANCE SYSTEM WITH CIRCULATION INDUCING STRUCTURE THEREIN TO VARIABLY RESIST FLOW IN A SUBTERRANEAN WELL |                        |                      |

This section allows for the applicant to claim benefit of foreign priority and to identify any prior foreign application for which priority is not claimed. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55(a).

|                                                                                                        |                      |                                 |                                                               |
|--------------------------------------------------------------------------------------------------------|----------------------|---------------------------------|---------------------------------------------------------------|
|                                                                                                        |                      |                                 | <b>Remove</b>                                                 |
| Application Number                                                                                     | Country <sup>i</sup> | Parent Filing Date (YYYY-MM-DD) | Priority Claimed                                              |
|                                                                                                        |                      |                                 | <input checked="" type="radio"/> Yes <input type="radio"/> No |
| Additional Foreign Priority Data may be generated within this form by selecting the <b>Add</b> button. |                      |                                 | <b>Add</b>                                                    |

## Assignee Information:

Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office.

|                                                                                                |                                   |                |            |
|------------------------------------------------------------------------------------------------|-----------------------------------|----------------|------------|
| <b>Assignee 1</b>                                                                              |                                   | <b>Remove</b>  |            |
| If the Assignee is an Organization check here. <input checked="" type="checkbox"/>             |                                   |                |            |
| Organization Name                                                                              | HALLIBURTON ENERGY SERVICES, INC. |                |            |
| <b>Mailing Address Information:</b>                                                            |                                   |                |            |
| Address 1                                                                                      | 10200 Bellaire Boulevard          |                |            |
| Address 2                                                                                      |                                   |                |            |
| City                                                                                           | Houston                           | State/Province | TX         |
| Country <sup>i</sup>                                                                           | US                                | Postal Code    | 77072      |
| Phone Number                                                                                   |                                   | Fax Number     |            |
| Email Address                                                                                  |                                   |                |            |
| Additional Assignee Data may be generated within this form by selecting the <b>Add</b> button. |                                   |                | <b>Add</b> |

## Signature:

A signature of the applicant or representative is required in accordance with 37 CFR 1.33 and 10.18. Please see 37 CFR 1.4(d) for the form of the signature.

|                   |                   |                  |                          |                            |       |
|-------------------|-------------------|------------------|--------------------------|----------------------------|-------|
| <b>Signature</b>  | /Marlin R. Smith/ |                  | <b>Date (YYYY-MM-DD)</b> | 2010-06-02                 |       |
| <b>First Name</b> | Marlin R.         | <b>Last Name</b> | Smith                    | <b>Registration Number</b> | 38310 |

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

## Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.