



New connection on: : 14-07-2017 : 19:16:11 - Last disconnection on: : 14-07-2017 : 19:15:39

V 4.0.0.43847(LP,U,linux) (Rev:41675 2016-01-15 13:33:59 +0100#(D201706)) (RPM D201706)

Welcome to EPOQUE Rebuild under the Production Environment

[EPODOC: SS 1] **water 1w saving**

Results in EPODOC **26.047**

[SS 2] **shower and tank and coupling**

Results in EPODOC **194**

[SS 3] **1 and 2**

Results in EPODOC **2**

[SS 4] **..li**



1/2 © EPODOC / EPO

PN - [CN205946791U](#) U 20170215

PR - CN20162971537U 20160829

AP - CN20162971537U 20160829

DT - I

PA - SUZHOU RENHE LANDSCAPE CO LTD

TI - Can **water -saving** afforestation device

AB - The utility model discloses a can **water -saving** afforestation device, include control panel, manometer, flow meter, insect repelling device and drip irrigation the **shower** nozzle, the outside of water storage **tank** is inlayed and is had control panel, the immersible pump sets up the inner chamber at the water storage **tank**, and is electric connection between immersible pump and the control panel, the outside difference fixedly connected with manometer and the flow meter of delivery pipe, drip irrigation the union **coupling** in one side of delivery pipe, and drip irrigation and be connected through three way connection between pipe and the delivery pipe, insect repelling device inlays the one side at three way connection, the outside of driping irrigation the pipe is equipped with drips irrigation the **shower** nozzle, and the end -to -end connection of just driping irrigation the pipe has the end cap. This can **water -saving** afforestation device is equipped with the ultrasonic insect device, the improvement insect pest of ideal, and the inner chamber of driping irrigation the pipe is equipped with the filter screen, can prevent that drip irrigation hole from blocking up, is

connected with manometer and flow meter, and drips irrigation the pipe and for the loop configuration, can practice thrift the watering water, is connected with three way connection, can enlarge greening area.

2/2 © EPODOC / EPO

PN - [CN204940455U](#) U 20160106

PR - CN20152551436U 20150727

AP - CN20152551436U 20150727

DT - I

PA - SHENZHEN POLYTECHNIC

TI - **Water -saving** closetool

AB - The utility model discloses a **water -saving** closetool, including toilet **tank**, the toilet **tank** bottom is equipped with the water inlet and washes away the bath mouth of closetool, and the mouth of a river leads to pipe and water inlet intercommunication from the beginning, still include: additional water **tank**, joint, check valve, additional water **tank** bottom is equipped with two at least supports, and additional water **tank** passes through the support to be fixed on toilet **tank** upper portion, connecting and fixing the delivery port department that offers in additional water **tank** bottom, connect the one end switch -on of leading to pipe and check valve, the other end of check valve is through tee pipe **coupling** and the cross current between the mouth of a river and the water inlet from the beginning, and be equipped with the water pipe switch between the mouth of a river and the tee pipe **coupling** from the beginning. The utility model discloses it is fixed to toilet **tank** upper portion only to need to add the water **tank**, the other end of check valve receive on toilet **tank**'s the water pipe can, changes very for a short time, install fairly simply, only need operate the water pipe switch during use, the utilization ratio is more convenient, and can make full use of the have a **shower** cold water of preceding emission, it is effectual to economize on water.

[SS 4] ..v

[EPODOC: SS 4]