



(51) International Patent Classification:

C04B 28/00 (2006.01) C04B 28/04 (2006.01)

(21) International Application Number:

PCT/EP2016/063302

(22) International Filing Date:

10 June 2016 (10.06.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

PCT/EP2015/063045 11 June 2015 (11.06.2015) EP

(71) Applicant: CEMEX RESEARCH GROUP AG
[CH/CH]; Römerstrasse 13, 2555 Brugg bei Biel (CH).

(72) Inventors: ESSER, Jeremy; Radiusweg, 4, 2503 Biel/Bienne (CH). ZAMPINI, Davide; Birkenweg 18, 3250 Lyss (CH). GUERINI, Alexandre; Chemin des Ratenets 14, 2088 Cressier NE (CH). VOLPATTI, Giovanni; Salismatte 2, 2555 Aegerten (CH).

(74) Agents: CARVAJAL Y URQUIJO, Isabel et al.; Suero de Quiñones 34-36, 28002 Madrid (ES).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: CONCRETE MIX DESIGNS USING A PLURALITY OF REINFORCEMENT FIBERS SYSTEMS



(57) Abstract: A concrete mix comprising sand, fine aggregates, binder, fibers, and various admixtures, having a consistency from S2 to SF3, a compressive strength in the range of 30-80 MPa and a ductility represented by f_c , f_{fl} , f_{R1} and f_{R3} values, wherein the concrete mix contains at least 390 Kg of binder, the concrete mix comprises a paste volume of 300- 600 liters, the concrete mix contains at least two systems of metallic fibers and a general admixture system that is composed of at least 2 sub-admixture systems.

Fig. 1

Published:

— with international search report (Art. 21(3))