

Institutional Sign In

Browse

My Settings

Get Help

Subscribe

Advertisement

Need Full-Text

access to IEEE *Xplore* for your organization?

REQUEST A FREE TRIAL >

Browse Conferences > World Automation Congress (WA...

< Previous | Back to Results | Next >

Experimental research on the tumble dryer of fly ash

Sign In or Purchase
to View Full Text

33
Full
Text Views

Related Articles

SafetyNet: improving the availability of shared memory multiprocessors with glob...

Fuzzy biasless simulated evolution for multiobjective VLSI placement

View All

3
Author(s)

Tai Lv ; Sheng Che ; Ting-ting Zhou

View All Authors

Abstract	Authors	Figures	References	Citations	Keywords	Metrics	Media
----------	---------	---------	------------	-----------	----------	---------	-------

Abstract:

The applications of the tumble dryer and the feasibility of drying fly ash have been analyzed. Wind speed, temperature, rotational speed and the feeding rate which are the main parameters affecting the tumble dryer have been researched by using the mutual affecting test. The effects of parameters on the tumble dryer have been found out which can provide references for the design of large dryers.

Published in:

World Automation Congress (WAC), 2012

Date of Conference:

24-28 June 2012

Publisher:

IEEE

Date Added to IEEE *Xplore*:

04 October 2012

Conference Location:

Puerto Vallarta, Mexico, Mexico

ISBN Information:

ISSN Information:

Advertisement

IEEE *Xplore*

Want to know when an article is cited?

Activate Citation Alerts today.

Contents

Download PDF	I. Introduction In the electrical industry of china, generating capacity of thermal power is about 75% of the total generating capacity. Annual fly ash discharge volume is above 160 million tons. For the past many years, the amount of unutilized fly ash has reached 500 million tons and covering 200 thousand Mu which poses a great threat to the environment. In china, the utilization technology and equipments of fly ash are backward, the development comprehensive utilization is unbalanced. No matter the storage and transportation of dry fly ash are liable in the process of fly ash comprehensive utilization. Moreover, the technological requirements of some projects need to use dry ash. So the quantity demand of dry ash is much more than wet ash. The burning question of fly ash utilization is how to change the fly ash which contains a certain amount of water stored in the ash yard into dry ash which is more valuable.	
Download Citation	Read document	Full Text
View References	Authors	Authors
Email	References	References
Print	Keywords	Keywords
Request Permissions	Related Articles	Related Articles
Export to Collabratec	Disclaimer	Back to Top
Alerts		

IEEE Account » Change Username/Password » Update Address	Purchase Details » Payment Options » Order History » View Purchased Documents	Profile Information » Communications Preferences » Profession and Education » Technical Interests	Need Help? » US & Canada: +1 800 678 4333 » Worldwide: +1 732 981 0060 » Contact & Support
---	---	---	--

About IEEE *Xplore* | Contact Us | Help | Accessibility | Terms of Use | Nondiscrimination Policy | Sitemap | Privacy & Opting Out of Cookies

A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.
© Copyright 2018 IEEE - All rights reserved. Use of this web site signifies your agreement to the terms and conditions.