







2 results for (cement+ and pellet+ and drying and cellulose and chitosan and collagen and polyacrylamide)/TI/AB/IW/CLMS/DESC/ODES/OBJ/ADB/ICLM/KEYW/TX AND (C04B-018/02)/IPC - Collection: FAMPAT






#	 Title	Publication number	1st app. date	Applicant/Assignee	1st publ. date	Publ. date
1.	Method to produce aggregates from unsettled cementitious mixtures	WO2016198384	2015-06-08	CEMEX RESEARCH*	2016-12-15	2016-12-15

Method to produce aggregates from unsettled **ce**mentitious mixtures, comprising the steps of (a) adding at least one **pe**lletizing agent to an unsettled **ce**mentitious mixture, (b) mixing constantly the mixture of step (a) in a mixer to produce **pe**llets, (c) discharging the **pe**llets obtained in step (b) and (d) **dr**yding the **pe**llets formed in step (c). The **pe**lletizing agent is selected from the group consisting of **ce**llulose, **ch**itosan, **co**llagen, **po**lyacrylamide and co-polymers of **po**lyacrylamide and polyacrylics, polyamines, polyvinylalcohols, polysaccharides, lactic acid, methacrylic acid, methacrylate, hydroxyethyl, ethylene glycol, ethylene oxide, acrylic acid, inorganic flocculants and inorganic coagulants.



2.	Method to artificially agglomerate finely divided materials	WO2016188559	2015-05-26	CEMEX RESEARCH*	2016-12-01	2016-12-01
----	---	--------------	------------	-----------------	------------	------------

Method to artificially agglomerate finely divided materials. A method to agglomerate finely divided material into aggregates, the aggregates being larger than the finely divided material, comprising the steps of (a) mixing finely divided material, binder and water in a mixer, (b) adding an agglomerating agent to the mix formed in step (a) and mixing constantly. Finely divided material is selected from the group consisting of **ce**ment, sand, clay, glass, slag, fly ash, stone powder, bypass dust, limestone, silica fume, crushed brick, brick powder and crushed stone or a combination thereof.



$$F M_{50} = 4.54 q_{50} \left(\frac{PV}{d} \right)^{100}$$

eq. 1

$$F M_{50} = 1.815 \cdot 10 q_{50} \left(\frac{PV}{d} \right)^{100}$$

eq. 2

$$F M_{50} = 0.336 \cdot 10 q_{50} \left(\frac{PV}{d} \right)^{100}$$

eq. 3

$$d = F M_{50} \times \left(\frac{d_{50}}{PV} \right)^{100}$$

eq. 4

$$d = F M_{50} \times \left(\frac{d_{50}}{PV} \right)^{100}$$

eq. 5