



(51) International Patent Classification:
E21B 33/127 (2006.01)

(21) International Application Number:
PCT/US2018/061412

(22) International Filing Date:
16 November 2018 (16.11.2018)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
15/831,659 05 December 2017 (05.12.2017) US

(71) Applicant: **WEATHERFORD TECHNOLOGY HOLDINGS, LLC** [US/US]; 2000 St. James Place, Houston, TX 77056 (US).

(72) Inventor: **SCRUGGS, Justin, R.**; 11909 Spencer Road, Houston, TX 77041 (US).

(74) Agent: **SMITH, Marlin, R.**; Smith IP Services, P.C., P.O. Box 997, Rockwall, TX 75087 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

— *with international search report (Art. 21(3))*

(54) Title: MULTIPLE SETTING AND UNSETTING OF INFLATABLE WELL PACKER

(57) Abstract: An inflatable packer assembly can include an inflatable seal element having an internal inflation chamber, a flow passage extending longitudinally through the inflatable packer assembly, a flow restrictor between sections of the flow passage, and a flow controller that selectively permits and prevents fluid communication between the inflation chamber and each of the flow passage sections. The flow controller changes from a deflate configuration to an inflate configuration in response to an increase in flow rate through the flow passage. A method can include connecting an inflatable packer assembly in a tubular string, so that a longitudinal flow passage of the tubular string extends through the inflatable packer assembly, and a flow restrictor restricts flow between sections of the flow passage, and inflating an inflatable seal element of the inflatable packer assembly while fluid flows between the flow passage sections via the flow restrictor.

