



(51) International Patent Classification:

B62J 7/04 (2006.01) *B62K 19/40* (2006.01)
B62J 9/00 (2020.01)

(21) International Application Number:

PCT/IB2020/051009

(22) International Filing Date:

10 February 2020 (10.02.2020)

(25) Filing Language:

Italian

(26) Publication Language:

English

(30) Priority Data:

102019000002225 15 February 2019 (15.02.2019) IT

(71) Applicant: **GIVI S.P.A.** [IT/IT]; Via Ungaretti, 48, 25020 Flero (BS) (IT).

(72) Inventor: **VISENZI, Giuseppe**; Viale della Bornata 117, 25123 Brescia (IT).


(74) Agent: **BRANCA, Emanuela**; c/o BARZANO' & ZANARDO MILANO S.p.A., Via Borgonuovo, 10, 20121 Milano (IT).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

(54) Title: LATERAL CASE FOR MOTORCYCLES WITH IMPROVED COUPLING DEVICE TO THE VEHICLE FRAME

Fig. 3



(57) Abstract: The present invention relates to a lateral case for motorcycles provided with an improved coupling/release device for the coupling and release of the case itself to/from the vehicle frame. The lateral case for motorcycles according to the present invention is configured to allow the user to perform the coupling and release operations with a single and simple vertical movement of the bag with respect to the motorcycle frame, so that the coupling/release operation is simpler and more convenient for the user. Furthermore, the coupling/release device of the lateral case according to the present invention is easy for the user to activate and has a high degree of security towards accidental or fraudulent openings.

EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *in black and white; the international application as filed
contained color or greyscale and is available for download
from PATENTSCOPE*

LATERAL CASE FOR MOTORCYCLES WITH IMPROVED COUPLING
DEVICE TO THE VEHICLE FRAME

FIELD OF THE INVENTION

The present invention relates to a lateral case or bag
5 for motorcycles comprising an improved coupling device
for the coupling and release of the case itself to/from
the vehicle frame.

More in particular, the present invention relates to a
lateral case for motorcycles appropriately configured
10 to allow the user to perform the coupling and release
operations with a single and simple vertical movement
of the bag with respect to the motorcycle frame, so
that the coupling/release operation is simpler and more
convenient for the user.

15 The present invention further relates to a lateral case
for motorcycles provided with an improved
coupling/release and locking/unlocking system that can
be easily activated by the user and having a high
degree of security against accidental or fraudulent
20 openings.

STATE OF THE ART

The use of lateral bags or cases adapted to house
luggage, helmets or other accessories is known in the
motor vehicle sector, which can be coupled and released
25 to/from the motorcycle frame, in particular at the rear
area of the vehicle frame.

Even more in particular with specific reference to
lateral cases or bags for motorcycles, lateral cases
are known in the sector which in order to be coupled to
30 the motorcycle frame oblige the user to perform a
horizontal or oblique translation movement of the bag
with respect to the vehicle frame during the

coupling/release operations.

The fact that the user has to couple the bag to the frame and then move the bag with respect to the frame with a horizontal or oblique movement is perceived by the user as inconvenient, particularly uncomfortable when the bag to be coupled is full and therefore heavy, and in any case complicated to the point of making the correct outcome of the coupling/release operations uncertain.

10 Likewise, such movement is perceived as inconvenient in the case of the operation of releasing the bag.

According to the state of the art, once the bag is coupled to the frame by means of appropriate coupling/release means, such coupling/release means must also be locked in a stable coupled bag position. In the same way, to allow the release of the bag the coupling/release means must be unlocked in advance passing into a configuration in which the bag can be released from the frame.

20 Known embodiments do not offer simple and at the same time reliable solutions for the coupling/release and locking/unlocking of the bag to/from the vehicle frame, and also generally require that an actual support frame be present on the motorcycle, generally made of metal tubular material, for the coupling and support of the bag.

SUMMARY OF THE INVENTION

The aim of the present invention is therefore that of providing a lateral case or bag for motorcycles comprising a coupling device of the improved type for the coupling and release of the case itself to/from the vehicle frame which allows the user, in the coupling

30

operations, to perform a simple vertical movement of the bag with respect to the frame, so as to "hang" the bag itself on the support frame. A similar concept applies to the release operations.

5 Within this aim, the object of the present invention is that of providing a lateral case for motorcycles comprising a coupling/release device the activation of which is easy and intuitive for the user and, at the same time, strong, secure and reliable.

10 Again, it is an object of the present invention to provide a lateral case for motorcycles comprising a coupling/release device that allows the bag to be directly coupled to the motorcycle frame regardless of the presence of a support frame or however a dedicated
15 tubular support structure.

These objects according to the present invention are achieved by a lateral case for motorcycles comprising a coupling device of the improved type, according to what is set out in claim 1.

20 LIST OF FIGURES

The characteristics and advantages of the lateral case according to the present invention will become more apparent from the following detailed description, provided by way of non-limiting example, with reference
25 to the schematic attached drawings, wherein:

- figure 1 shows a side view of the rear area of a motorcycle on whose frame seats are provided for housing the coupling/release device of the lateral bag according to the present invention;
- 30 - figure 2 shows an overall perspective view of the lateral case according to the present invention;
- figure 3 shows a detailed view of the main

- components of the coupling/release device that equips the lateral case according to the present invention, in a closed device configuration and therefore with the bag firmly coupled to the vehicle frame;
- 5 frame;
- figure 4 shows the same view as figure 3 in an open device configuration and therefore with the case that can be released from the vehicle frame;
 - figure 5 shows a schematic perspective view of a step of coupling the lateral case to the motorcycle frame;
 - 10 frame;
 - figure 6 shows a view from below of the coupled condition of the case to the vehicle wherein the hooks of the case are inserted into the housing seats provided in the frame and the sliders are in the released position, i.e. they are close to one another at the inner stroke end position which allows the coupling and release of the case from the frame;
 - 15 frame;
 - 20 - figure 7 shows the same view from below as figure 6 wherein the hooks of the case are inserted into the housing seats provided in the frame and the sliders are in the locked position, i.e. they are distanced from one another at the outer stroke end position wherein said sliders are engaged at corresponding abutment grooves provided on said frame below the hook housing seats, a position that does not allow the release of the case from the frame;
 - 25 frame;
 - figures 8A and 8B each show a partial sectional view of the case closing means, in a closed case hook closing condition, and an open case hook closing condition, respectively.
 - 30 frame;

DETAILED DESCRIPTION OF THE INVENTION

In the appended figures overall views and views of details of the lateral case 10 for motorcycles according to the present invention, and of the related
5 coupling/release device of the case 10 to/from the frame 50 of a vehicle are shown.

As it will become clearer from the detailed description provided below by way of example, the case 10 according to the present invention allows the lateral case 10 to
10 be directly hooked to the frame 50 of the vehicle with the provision of relevant hooks 23, 24 on the case 10 and corresponding coupling seats 100, 200 directly on the frame.

Advantageously said coupling seats 100, 200 are
15 provided in an area of the frame that is accessible from above, so that the bag 10 can be coupled to the frame 50 with a substantially vertical movement by the user.

More advantageously, to protect the aesthetics of the back end of the motorcycle, the coupling seats 100, 200
20 shall be provided in a position that is accessible from above for the insertion of said hooks 23, 24 of the case, preferably on the side of the vehicle below the seat and/or the rear luggage compartment, so as not to
25 ruin the aesthetics of the vehicle.

Therefore, the subject matter of the present invention is not only the case 10 provided with the coupling/release device that will be better described herein below, but also the coupling system comprising
30 the frame 50 appropriately provided to cooperate with the coupling/release device of the case 10.

As mentioned, the hooks 23, 24, of which there are

preferably two, are inserted into the coupling seats 100, 200 provided on the frame 50, so that the case 10 hangs from the frame of the vehicle.

In order to lock the movements of the case also in a transverse direction with respect to the longitudinal axis of the vehicle, the case 10 according to the present invention is advantageously provided with a housing seat 14 obtained at the lower area of the case and configured to accommodate, when the case is coupled to the motorcycle, lower coupling means 300 integral with the vehicle frame 50 and preferably at the area of the frame supporting the passenger footrest.

Thanks to this configuration of the coupling system on the vehicle, metal frames are not provided for the fixing of the bag and therefore, once the case has been removed, the aesthetic line of the motorcycle is unaltered as required by users.

Advantageously, the case 10 according to the present invention comprises two shells hinged to one another, the bottom 11 and the cover 12, and a coupling/release device that is housed within the case itself, preferably fixed to the bottom 11.

Preferably, the case 10 according to the present invention comprises only one lock 20 that can be activated by the user. Such lock advantageously controls both the opening and the closing of the case and the possibility to couple and release it to/from the motorcycle.

Now, passing onto the detailed description of the lateral case 10 according to the present invention, it comprises, as mentioned, preferably at least one pair of hooks 23, 24 which project from the surface of the

case 10 intended to face towards said frame 50, and whose loops 23a, 24a face downwards, and which are configured to engage special coupling seats 100, 200 obtained on the frame 50 of the vehicle.

5 Said hooks 23, 24 are part of the coupling/release device of the case 10 according to the present invention, which device further comprises a pair of sliders 25, 26 movable along a substantially horizontal direction and each configured to be selectively
10 positioned in correspondence with one of said hooks 23, 24, below it, so as to match special grooves 400, 500 formed on the frame 50 below said coupling seats 100, 200.

The presence of the movable sliders 25, 26, as can be
15 seen better below, allows the movements in the vertical direction of the case 10 to be blocked once it is coupled to the frame 50 thus preventing the hooks 23, 24 from coming out of the coupling seats 100, 200.

In fact, the movable sliders 25, 26 are configured to
20 be selectively engaged with the respective grooves 400, 500 obtained on the frame below the coupling seats 100, 200 so that when the sliders 25, 26 are engaged within said grooves, the lifting of the case with respect to the frame and therefore the removal of the bag from the
25 vehicle is actually prevented.

The movement of said movable sliders 25, 26 is performed by the user through said coupling/release device, which for the purpose comprises a pair of sliding rod-shaped elements 43, 46, each of which in
30 turn comprises at least one rack portion 44, 47.

A first 43 of said rod-shaped elements is in turn kinematically connected to a locking/unlocking lever 41

which can be activated by the user.

With particular reference to the appended figures 3 and 4, the activation of said locking/unlocking lever 41 causes the translation of said first rod-shaped element 43 and of the relative slider 25.

Advantageously, the two rack portions 44, 47 of the two rod-shaped elements 43, 46 result facing each other so that an idle toothed wheel 45, free to turn about its own central axis, can be interposed between them so as to transfer the translational motion of the first rod-shaped element 43 to the second rod-shaped element 46.

In this way the translation of the first rod-shaped element 43 caused by the activation of the locking/unlocking lever 41 causes an equal translation in the opposite direction of the second 46 of said rod-shaped elements and, therefore, of the relative slider 26.

The sliders 25, 26 are therefore movable between a first released position in which the coupling and release of the case 10 to/from the frame 50 of the vehicle is possible, and a second locked position in which they abut the relevant grooves 400, 500 made below said frame 50 thus retaining the case coupled to the frame itself.

According to the preferred embodiment of the present invention illustrated herein by way of non-limiting example, the locking/unlocking lever 41 is movable between a first closed position in which said sliders 25, 26 are in the locked position, and a second opening position in which said sliders 25, 26 are in said unlocked position.

For example, in the first unlocked position, said

sliders 25, 26 will be close to one another, so as to allow the coupling and release of the case 10 to/from the frame 50 of the vehicle, whereas in the second unlocked position said sliders 25, 26 are spaced out
5 from one another and inserted inside said grooves 400, 500 obtained on the frame keeping the case coupled to the frame 50 itself.

To move said sliders 25, 26, the locking/unlocking lever 41 is advantageously assembled on a rotating
10 shaft 42 in turn connected to a crank 42a which engages, preferably through a pin 42b, with said first rod-shaped element 43. As mentioned, and with particular reference to the detail of figures 3 and 4, the user by activating in rotation the
15 locking/unlocking lever 41 about the axis of the rotating shaft 42 moves in translation the first rod-shaped element 43 and, thanks to the presence of the idle toothed wheel 45, free to rotate about its own axis, a single and opposite translation of said second
20 rod-shaped element 46.

By rotating the locking/unlocking lever 41 in one direction, the mutual nearing of the two sliders 25, 26 will be obtained; by rotating said locking/unlocking lever 41 in the opposite direction the mutual
25 distancing of the two sliders 25, 26 will be obtained.

In order to guarantee the security of the coupling of the case to the vehicle and prevent accidental or fraudulent activations of the locking/unlocking lever 41, advantageously, according to the preferred
30 embodiment of the present invention shown in the appended figures, the case 10 further comprises closing means 21, 30, 31 of the case configured for selectively

allowing or preventing the user from accessing said locking/unlocking lever 41.

More in particular, said closing means 21, 30, 31 of the case 10 are operatively connected to a lock block 20 advantageously provided on the case itself, so that by acting on the lock 20 it is possible to lock or unlock the closing means 21, 30, 31 of the case, preventing or allowing the user to access to said locking/unlocking lever 41.

Even more in detail, said closing means 21, 30, 31 of the case preferably comprise an under-lock element 30 operatively connected to said lock block 20, a locking slider 31 operatively connected to said under-lock element 30, and a handle 21 configured to selectively cooperate with said locking slider 31 so that operating said lock block 20 through said under-lock element 30 and said locking slider 31 the opening of said handle 21 is selectively allowed or prevented, which in turn allows or prevents the access to said locking/unlocking lever 41.

Furthermore, the closing means of the case will also comprise, on said bottom 11, a case closure hook 22 which allows the case to be closed and/or opened according to the prior art.

More specifically, and with particular reference to figures 8A and 8B, the means that allow the opening and closing of the case advantageously comprise a hooking tooth 15 provided on the cover 12, and the case closure hook 22, which is in a known way coupled to a rod 27 that allows the movement thereof with respect to the cover 12.

When the case is closed the case closure hook 22 is

engaged with the tooth 15 of the cover.

When the lock 20 is closed, it is not possible to make the case closure hook 22 rotate since the rod 27, which is directly connected to the case closure hook 22, is
5 locked by the action of the locking slider 31.

Therefore the case cannot be opened.

When the lock 20 is open, the rod 27 is disengaged from the action of the locking slider 31 and the movement of the case closure hook 22 is therefore allowed, the
10 coupling between the case closure hook 22 and the cover tooth 15 is disengaged and therefore the case is opened.

The locking of the case closure hook 22 is operated by the presence on said locking slider 31 of locking teeth
15 32 that find corresponding abutments on said case closure hook 22 and on the handle 21.

Thanks to this configuration, and as it can be seen in the drawings, on the case according to the present invention there is only one lock both for opening and
20 closing the case itself, through the movement of said case closure hook 22, and to allow the coupling/release thereof to/from the motorcycle, allowing the lifting of the handle 21 in order to be able to access the lever 41 and be able to activate it.

25 When the key is in the closing position, the user cannot move either the handle 21 or the case closure hook 22 and therefore it is not possible either to open the case or couple/release it to/from the motorcycle.

By rotating the key in the opening position the
30 disengagement of the teeth 32 of the slidable slider 31 from those of the handle 21 and from those of the case closure hook 22 is obtained.

Once the lock 20 is open, the handle 21 and the case closure hook 22 can be moved by the user independently from one another.

In other words, when the key is in the opening position
5 the user can selectively decide whether to open the case, by acting on the case closure hook 22, or to couple/release the case to/from the motorcycle by lifting the handle 21 and acting on the lever 41 as described.

10 Advantageously, as shown in the appended figures, the preferred embodiment of the present invention provides that the locking/unlocking lever 41 is placed below said handle 21.

With the handle 21 closed, the locking/unlocking lever
15 41 is in the closing, horizontal, position and the sliders 25, 26 are positioned at the outer stroke end position of the grooves 400, 500 obtained on said frame 50 below the hooks 23, 24.

In this configuration it is not possible to couple the
20 case to the motorcycle as the position of the coupling sliders 25, 26 does not allow the vertical insertion of the hooks 23, 24 in the relevant coupling seats 100, 200 obtained on the frame 50.

To couple the case to the motorcycle it is necessary to
25 lift the handle 21 and therefore rotate the lever 41 in the vertical position; in this way the system of kinematic mechanisms described above makes the coupling sliders 25, 26 move towards the inside bringing them to their stroke end outside the profile of the hooks 23,
30 24.

In this way it is possible to insert from above the hooks 23, 24 into the relevant coupling seats 100, 200

obtained on the side of the frame 50, and at the same time it is also possible to couple the housing seat 14 obtained at the lower region of the case with the lower coupling means 300 provided on the vehicle frame, preferably at the connection to the passenger footrest. By bringing the lever 41 into the horizontal position, the coupling sliders 25, 26 are moved again up to the outer stroke end, engaging them in said grooves 400, 500 obtained below the coupling seats 100, 200 of the hooks 23, 24.

In this configuration it is no longer possible to remove the case as the locking sliders interfere directly with the motorcycle side in which the grooves 400, 500 are obtained and do not allow the vertical movement of the case and therefore the disengagement of the hooks 23, 24 from their seats 100, 200.

To make the system secure it is therefore necessary to close the handle 21 again and bring the key back into the closing position.

The repositioning of the handle 21 in the closed position also signals to the user that the case is correctly coupled to the motorcycle. In fact, if the coupling is not completed correctly, the lever 41 will not be in the horizontal position and will not allow the closing of the handle 21 and, therefore, the complete rotation of the key of the lock 20.

To detach the case from the motorcycle it is necessary to perform the same procedure and therefore to bring the key of the lock 20 into the opening position, lift the handle 21, rotate the lever 41 thus causing the movement of the coupling sliders 25, 26 until such sliders are engaged on the inner stroke end and

therefore the sliders are disengaged from said grooves 400, 500 and the hooks 23, 24 from their seats 100, 200 lifting the case upwards.

From the description provided, the characteristics of
5 the lateral case for motorcycles comprising the coupling/release device for allowing the coupling and release of the case 10 itself to/from the frame 50 of the vehicle according to the present invention are clear.

10 The advantages of the coupling system for the coupling of such case to the frame of a motorcycle are also clear, where said frame is appropriately configured to allow the operation of the specific coupling/release device.

15 It is further to be understood that the coupling/release device of the lateral case for motorcycles according to the present invention is susceptible to modifications and variants, all falling within the scope of protection identified by the
20 appended claims, which form an integral part of the descriptive text.

Furthermore, the details provided by way of example can be replaced by technically equivalent elements falling within the scope of protection of the invention.

25

CLAIMS

1. Lateral case (10) for motorcycles comprising a coupling/release device configured to allow the coupling and the release of said case (10) to/from the vehicle frame (50), said coupling/release device comprising at least one pair of hooks (23, 24) which protrude from the surface of the case (10) intended to face said frame (50) with the loops (23a, 24a) facing downwards and configured to engage special coupling seats (100, 200) formed on said vehicle frame (50), said device further comprising a pair of sliders (25, 26) movable along a substantially horizontal direction and each configured to be able to selectively positioning in correspondence with one of said hooks (23, 24), below it, so as to match special grooves (400, 500) formed on said frame (50) below said coupling seats (100, 200), further characterized in that each of said sliders (25, 26) is connected to a respective sliding rod-shaped element (43, 46) comprising at least one rack portion (44, 47), a first (43) of said sliding rod-shaped elements being in turn kinematically connected to a locking/unlocking lever (41) which can be activated by the user, the actuation of said lever (41) causing the translation of said first rod-shaped element (43) and of the relative slider (25), the two rack portions (44, 47) resulting facing each other and an idle toothed wheel (45) being interposed between them so that the translation of said first rod-shaped element (43) caused by the actuation of said lever (41) causes an equal translation in the opposite direction of the

second (46) of said rod-shaped elements (43, 46) and of the relative slider (26).

2. Lateral case (10) for motorcycles according to the previous claim, characterized in that said sliders
5 (25, 26) are movable between a first release position in which they are close to each other and allow the coupling and uncoupling of the case (10) to the frame (50) of the vehicle, and a second locking position in which they are spaced from each
10 other and match said grooves (400, 500) formed on said frame (50) retaining the case hooked to the frame (50) of the vehicle with said hooks (23, 24) inserted into said coupling seats (100, 200).
3. Lateral case (10) for motorcycles according to the
15 previous claim, characterized in that said locking/unlocking lever (41) is movable between a first closing position in which said sliders (25, 26) are in said locking position, and a second opening position in which said sliders (25, 26) are
20 in said release position.
4. Lateral case (10) for motorcycles according to the previous claim, characterized in that said locking/unlocking lever (41) is assembled on a rotating shaft (42) in turn connected to a crank
25 (42a) configured to engage through a pin (42b) with said first rod-shaped element (43), so that the rotation of said locking/unlocking lever (41) around the axis of the rotating shaft (42) causes a translation of said first rod-shaped element (43)
30 and, consequently, an equal and opposite translation of said second rod-like element (46).

5. Lateral case (10) for motorcycles according to one or more of the preceding claims, characterized in that it further comprises closing means (21, 30, 31) of the case configured for selectively allowing or preventing the user from accessing said locking/unlocking lever (41).
6. Lateral case (10) for motorcycles according to the previous claim, characterized in that it further comprises a lock block (20) and in that said case closing means (21, 30, 31) are operatively connected to said lock block (20) so that by acting on the lock (20) it is possible to lock or unlock said case closing means (21, 30, 31) preventing or allowing the user to access said locking/unlocking lever (41).
7. Lateral case (10) for motorcycles according to the previous claim, characterized in that said case closing means (21, 30, 31) comprise an under-lock element (30) operatively connected to said lock block (20), a locking slider (31) operatively connected to said under-lock element (30), and a handle (21) configured to selectively cooperate with said locking slider (31) so that by operating said lock block (20) through said under-lock element (30) and said locking slider (31) the opening of said handle (21) is selectively allowed or prevented, said handle (21) in turn allowing or preventing the access to said locking/unlocking lever (41).
8. Lateral case (10) for motorcycles according to the previous claim, characterized in that said case closure means further comprise a case closure hook (22) which allows to close and/or open the case,

operatively connected through said under-lock element (30) and said locking slider (31) to said lock block (20) so that when the key is in the open position both said suitcase closure hook (22) and
5 said handle (21) can be moved by the user, so as to allow the access to said lever (41).

9. Lateral case (10) for motorcycles according to one or more of the preceding claims, characterized in that it further comprises a housing seat (14)
10 obtained at the lower area of the case and configured to receive, when the case is coupled to the motorcycle, lower coupling means (300) integral with the vehicle frame (50), preferably integral with the area of the frame supporting the passenger
15 footrest.

10. Coupling system for a lateral case (10) for motorcycles, characterized in that it comprises a case (10) according to one or more of the preceding claims, a motorcycle frame (50) equipped, in the
20 area of the back end of the vehicle, with coupling seats (100, 200) configured to accommodate said hooks (23, 24) of said case (10) facing upwards, said frame (50) being further provided with grooves (400, 500) formed at the bottom to said coupling
25 seats (100, 200) and configured to match with said sliders (25, 26) preventing, when said sliders (25, 26) are in their locking position in which they are spaced apart, movements in the vertical direction of the case (10) with respect to the frame (50) and,
30 consequently, the exit of the hooks (23, 24) from the corresponding coupling seats (100, 200).




Fig. 1




Fig. 2




Fig. 3




Fig. 4

Fig. 5





Fig. 6






Fig. 8A





Fig. 8B



INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2020/051009

A. CLASSIFICATION OF SUBJECT MATTER

INV. B62J7/04 B62J9/00 B62K19/40
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B62J B62K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2007/045371 A1 (GI VI SRL [IT]; VISENZI GIUSEPPE [IT]) 26 April 2007 (2007-04-26) page 3, line 4 - page 4, line 3; figures 1-6	1-10
A	----- WO 2011/098897 A1 (GIVI S R L UNIPERSONALE [IT]; VISENZI GIUSEPPE [IT]) 18 August 2011 (2011-08-18) page 6, line 23 - page 7, line 25; figure 1	1-10
A	----- EP 1 921 001 A1 (LIM SAU LEONG [SG]) 14 May 2008 (2008-05-14) paragraphs [0017], [0018], [0021]; figure 1 ----- -/--	1-10



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

28 February 2020

Date of mailing of the international search report

11/03/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Afanasiev, Andrey

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2020/051009

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2005/104380 A1 (CHO JOUNG-HWAN [KR]) 19 May 2005 (2005-05-19) paragraphs [0025] - [0036], [0045] - [0052] -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2020/051009

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2007045371 A1	26-04-2007	EP 1937540 A1 ES 2548094 T3 JP 5087546 B2 JP 2009511355 A US 2010181356 A1 WO 2007045371 A1	02-07-2008 13-10-2015 05-12-2012 19-03-2009 22-07-2010 26-04-2007
WO 2011098897 A1	18-08-2011	BR 112012020123 A2 CN 102803057 A EP 2534033 A1 ES 2555405 T3 IT 1398164 B1 MY 167515 A US 2013043289 A1 WO 2011098897 A1	23-08-2016 28-11-2012 19-12-2012 30-12-2015 14-02-2013 04-09-2018 21-02-2013 18-08-2011
EP 1921001 A1	14-05-2008	AT 451294 T CN 101311058 A EP 1921001 A1 ES 2338036 T3 HK 1126173 A1 JP 5325787 B2 JP 2010509123 A MY 150870 A SG 143110 A1 TW 200902371 A US 2010065596 A1 WO 2008060245 A1	15-12-2009 26-11-2008 14-05-2008 03-05-2010 01-03-2013 23-10-2013 25-03-2010 14-03-2014 27-06-2008 16-01-2009 18-03-2010 22-05-2008
US 2005104380 A1	19-05-2005	KR 20050048378 A US 2005104380 A1	24-05-2005 19-05-2005