

kardemir
Çelik Sanayi A.S.
Aşıyeşme Mah. Meşelerez Bulv. No:77 Gebzel / Türkiye
Tel: +90 262 625 22 22 Fax: +90 262 625 19 85

MILL TEST CERTIFICATE
EN 10204:2004 / 3.1

EN 10025-1:2004 Hot Rolled Products of structural steel- Part 1 General technical delivery conditions

CE 2195-CPR-1405603

Certificate No: / No Du Certificat: 20221024
Date : 24.10.2022
Page : / 1

Your Order No: / Commande No:
Our Order No: / Notre Commande: GYXBAQ 22-1204

Description of Goods: PRIME QUALITY HOT ROLLED STEEL IPE IN 6,000 METERS LENGTH (00 MM / +50 MM) AND 12,000 METERS LENGTH (-00 MM / +100 MM) IN QUALITY ASTM A572 GR50 T2 ACC TO EN 10025

Standard : ASTM
Tolerance :

Purchaser : / Commettant: GYJ FERRETERIAS S.A.
NIT:800.130.426-3. CARRERA 65B NO12-93 BOGOTA / COLOMBIA
TEL: +5712 60078 3

Material: Matière:	Size-Dimension:	Quality / Qualité Hot Rolled Structural Steel	Heat No ! No Coulée :	CHEMICAL COMPOSITION - COMPOSITION CHEMIQUE - CEV = C + Mn/6 + (Cr + Mo + V)/5 + (Cu + Ni)/15																		Mechanical Properties - Properties Mechaniques ASTM A370-19e1				Quantity Shipped / Quantité expédiée (MTON)	No Of Bundles Nbs Of Pieces Per Bundles
				C %	Si %	Mn %	P %	S %	Cr %	Ni %	Mo %	Cu %	Ti %	Co %	N %	Nb %	Al %	V %	Cb %	B %	Cev %	Yield Point-Limite el. N/mm²	Tensile Strength- Rupture (N/mm²)	Elongation-Allong.(%) (age Length L0 = 2)	Hardness - Dureté		
IPE	80 MM	ASTM A572 GR50 T2	213410	0,20	0,19	1,14	0,012	0,014	0,130	0,110	0,016	0,31	0,000	0,000	0,008	0,014	0,001	0,017	0,000	0,0000	0,45	370	602	24,9			
IPE	140 MM	ASTM A572 GR50 T2	2200209	0,19	0,20	1,11	0,018	0,020	0,120	0,090	0,022	0,34	0,001	0,011	0,009	0,017	0,001	0,017	0,018	0,0002	0,44	392	578	30,4			
IPE	160 MM	ASTM A572 GR50 T2	2201214	0,15	0,30	1,18	0,011	0,005	0,140	0,120	0,020	0,33	0,002	0,001	0,010	0,017	0,033	0,029	0,001	0,0003	0,42	369	601	28,6			
IPE	160 MM	ASTM A572 GR50 T2	2200994	0,20	0,20	1,08	0,011	0,005	0,140	0,120	0,020	0,31	0,002	0,001	0,008	0,017	0,019	0,018	0,001	0,0002	0,44	372	612	29,2			
IPE	180 MM	ASTM A572 GR50 T2	2200225	0,19	0,17	1,13	0,015	0,018	0,100	0,100	0,020	0,33	0,001	0,010	0,009	0,016	0,001	0,019	0,002	0,0003	0,43	391	578	29,4			
IPE	200 MM	ASTM A572 GR50 T2	213394	0,16	0,20	1,16	0,012	0,015	0,100	0,110	0,017	0,39	0,002	0,010	0,009	0,017	0,001	0,017	0,001	0,0004	0,41	377	556	31,2			
IPE	200 MM	ASTM A572 GR50 T2	2201265	0,17	0,19	1,20	0,011	0,016	0,110	0,130	0,014	0,41	0,001	0,008	0,010	0,018	0,001	0,020	0,002	0,0002	0,43	374	550	31,4			

Tests to verify quality have been carried out - Tests de verification de la conformite de la nuance fournie- OK

Standard for surface : EN10163-3:2004, Class C, Subclass 1

Banding Test -qeno D<2o<180°

Visual Inspection and Dimensional Chock -Examen Visuel et Dimensionel de Surface- OK

The Surveyor L. expert Ensis AEX

Material are manufactured,inspected,tested and sampled in accordance with the requirement of manufacturing standard found satisfactory and comply.
Dimension and material surface appearance result is acceptable and satisfactory.
The test results are in accordance with ASTM

kardemir Çelik Sanayi